

Page Yield Test Report

Canon Individual Test Method*



Photo Test Pattern: ISO / IEC 29103



imagePROGRAF PRO-1100

PFI-4100	4x6 Photo	A3+ Color	17 x 22 Color	17 x 22 Mono
PFI-4100 MBK	7,350	2,440	1,700	1,350
PFI-4100 PBK	2,270	300	210	180
PFI-4100 GY	1,850	200	130	100
PFI-4100 PGY	3,580	500	330	240
PFI-4100 PC	4,860	830	550	1,200
PFI-4100 C	5,630	1,010	680	730
PFI-4100 PM	3,990	590	390	990
PFI-4100 M	5,530	1,500	1,070	1,480
PFI-4100 Y	3,280	440	290	1,110
PFI-4100 R	5,780	1,140	770	2,020
PFI-4100 B	5,930	1,310	870	850
PFI-4100 CO	1,890	970	500	470
Average Value*	3,540	590	390	410

Values = page yield per document type 4x6: Semi-Gloss Photo Paper

A3+/17x22: Luster Photo Paper

Note: This page yield document applies to products equipped with firmware version V2.020 or later

Canon U.S.A., Inc.

^{*}Declared yield value is the estimated value based on Canon individual test method using the ISO/IEC 29103 Photo Test Pattern
*The harmonized average is a reference value calculated to approximate typical user printing conditions.