

Canon Accessibility Conformance Report

ITI VPAT® Version 2.5

Name of Product:

Canon imagePROGRAF
TX-3300, TX-3310, TX-4300, TX-4310, TX-5330
TX-5331, TX-5430 and TX-5431

Product Description: Inkjet Printer

Date: September 1st, 2026

Contact information: accessibility@cusa.canon.com (USA)
IJ-accessibility@canon-europe.com (Europe)



Notes: High-productivity CAD SFP with enhanced line and text quality, smart roll media handling, and vivid plain paper poster printing.

Evaluation Methods Used: Inspection, measurement, and testing are performed based on product knowledge, using consistent evaluation methods across our products. Software is evaluated using JAWS. (Testing was conducted with JAWS 2021; earlier versions may not yield the same results.)

Applicable Standards / Guidelines & Table of contents:

This report evaluates conformance to the following accessibility standards and guidelines:

U.S. Section 508 Standards (2017), as amended (2018)

EN 301 549 V3.2.1 (2021)

WCAG 2.2 (2023), Level A and AA

ISO/IEC 10779:2020

Composition of evaluated product:

Hardware Device

Driver: Printer Driver Software

Web Application: Remote UI

Documents

Mobile Application: Canon PRINT V4.0

Terms: The terms used in the Conformance Level information are defined as follows:

Supports: The functionality of the product has at least one method that meets the criteria without known defects or meets with equivalent facilitation.

Partially Supports: Some functionality of the product does not meet the criteria.

Supports through Equivalent Facilitation: Some functionality of the product meet the intent of the Criteria through alternate way.

Supports when combined with Compatible AT: Some functionality of the product meet the criteria using assistive technology which is not a part of the product itself.

Does Not Support: Majority of functionality of the product does not meet the criteria.

Not Applicable: The criteria are not relevant to the product. In the WCAG section, use 'supports' instead of 'not applicable' when reporting web conformance.

Not Applicable – Fundamental Alteration Exception Applies: The criteria are relevant to the product, but fundamentally impossible to meet the criteria, because of its conditions.

Note : To align with WCAG and avoid inconsistencies in this report, we follow the expressions used in WCAG Understanding Conformance. When no target elements exist in the product and no issue is present, the result is expressed as "Supports*" rather than "Not Applicable".

US Section 508 Standards

Chapter 3: Functional Performance Criteria

Criteria	Conformance Level	Remarks and Explanations
302.1 Without Vision. Where a visual mode of operation is provided, ICT shall provide at least one mode of operation that does not require user vision.	Partially Supports	HARDWARE: The product primarily uses a touchscreen-based visual interface and does not provide speech output, such as voice guidance or audio access to screen information. Status information and indicator lamps are primarily visual, and tactile access to controls and status information is limited. Some functions can be accessed using Canon PRINT with VoiceOver or TalkBack on a mobile device or through Remote UI with a screen reader on a PC. However, certain non-text content, error information, and accessibility-related settings may not be fully accessible without vision. Remote UI: Remote UI is generally usable with a screen reader on a PC. However, some ink-level information and non-text content lack appropriate text alternatives or are not announced correctly. On some screens, the reading order and relationships between items are not fully conveyed. Some error information is not available through speech output alone, repeated navigation blocks cannot be bypassed, and certain functions are not fully operable using a keyboard. PRINTER DRIVER: The printer driver is generally operable using a keyboard with a screen reader. However, not all functions are fully accessible without vision. DOCUMENT: Text alternatives are provided for non-text content presented to users, enabling the content to be accessed without vision. Canon PRINT: Canon PRINT is generally usable with VoiceOver or TalkBack on a mobile device. However, not all applicable functions and content are fully accessible without vision. *Access to Remote UI: To access the Remote UI, enter the IP address of your Canon device (for example, http://XXX.XXX.XXX.XXX) into a web browser. Navigation within the Remote UI can be performed primarily using the arrow keys to move between user interface elements. In this version of the Remote UI, child elements are presented immediately after their corresponding parent elements in the navigation and reading order.
302.2 With Limited Vision. Where a visual mode of operation is provided, ICT shall provide at least one mode of operation that enables users to make use of limited vision.	Partially Supports	HARDWARE: Information is visually presented on the display and indicator lamps. Information conveyed by color is also available in text, and controls can generally be distinguished through contrast. However, the on-screen text size is smaller than the minimum requirement, some areas used for paper, ink, and maintenance operations have limited contrast, and the product does not provide text enlargement or display customization features. Remote UI: Remote UI supports text resizing, sufficient contrast, and information that is not conveyed by color alone. However, some ink level information and non-text content lack appropriate text alternatives, some controls do not meet target size requirements, repeated navigation blocks cannot be bypassed, certain functions do not fully support keyboard operation, and error assistance or help functions are not provided. PRINTER DRIVER: The printer driver provides sufficient contrast between text and background, enabling use by many users with limited vision.

		DOCUMENT: Non-text content is accompanied by text alternatives, enabling information to be accessed more easily by users with limited vision and through magnification tools. Canon PRINT: Canon PRINT generally supports users with limited vision through platform accessibility features such as screen magnification and high-contrast display settings. However, not all applicable accessibility criteria are fully supported.
302.3 Without Perception of Color. Where a visual mode of operation is provided, ICT shall provide at least one visual mode of operation that does not require user perception of color.	Supports	HARDWARE, Remote UI, PRINTER DRIVER and DOCUMENT: Information is not conveyed by color alone. Color-coded information is supplemented with text, and controls can be distinguished through contrast with surrounding areas. Canon PRINT: Information is generally not conveyed by color alone. However, not all applicable accessibility criteria related to color-independent use are fully supported.
302.4 Without Hearing. Where an audible mode of operation is provided, ICT shall provide at least one mode of operation that does not require user hearing.	Supports	HARDWARE: Operation of the product does not require hearing. Audible notifications, when provided, are also available through visual indicators such as the display and status lamps. Remote UI, PRINTER DRIVER, DOCUMENT and Canon PRINT: The products do not rely on auditory information and can be used without hearing.
302.5 With Limited Hearing. Where an audible mode of operation is provided, ICT shall provide at least one mode of operation that enables users to make use of limited hearing.	Supports	HARDWARE: Operation of the product does not require hearing. Audible notifications, when provided, are also available through visual indicators such as the display and status lamps. Remote UI, PRINTER DRIVER, DOCUMENT and Canon PRINT: The products do not rely on auditory information and can be used without hearing.
302.6 Without Speech. Where speech is used for input, control, or operation, ICT shall provide at least one mode of operation that does not require user speech.	Supports	The product does not require speech input, voice commands, or speech-based user identification. All functions can be operated without vocal input.
302.7 With Limited Manipulation. Where a manual mode of operation is provided, ICT shall provide at least one mode of operation that does not require fine motor control or simultaneous manual operations.	Partially Supports	HARDWARE: The product does not require multipoint gestures, path-based gestures, simultaneous actions, or motion-based operation for touchscreen use. However, maintenance tasks such as paper replacement and roll paper installation require pinching, twisting, and coordinated manual actions, and no alternative method is provided. Remote UI: Most functions can be performed without fine motor control or simultaneous actions. However, some functions are not fully operable using only a keyboard. PRINTER DRIVER: All functions can be operated using a keyboard interface without requiring simultaneous manual actions. DOCUMENT: Documentation can be accessed and navigated using standard keyboard functions without requiring simultaneous manual actions. Canon PRINT: Most functions can be operated using standard touch gestures without requiring multipoint or path-based gestures. However, not all applicable accessibility criteria related to limited manipulation are fully supported.

302.8 With Limited Reach and Strength. Where a manual mode of operation is provided, ICT shall provide at least one mode of operation that is operable with limited reach and limited strength.	Partially Supports	HARDWARE: Some operations, including ink tank replacement and roll paper replacement, require force exceeding 22.2 N. No alternative method is provided for these operations. Remote UI, PRINTER DRIVER, DOCUMENT and Canon PRINT: Use of the products does not require significant hand strength.
302.8 With Limited Reach and Strength. Where a manual mode of operation is provided, ICT shall provide at least one mode of operation that is operable with limited reach and limited strength.	Partially Supports	HARDWARE: Obstacles exceeding 865 mm are present when operating the touch screen, control panel buttons, top cover, and ink tanks. The ink replacement reach depth exceeds 610 mm. The open top cover and ink tank positions exceed 1170 mm in height. In addition, the display is difficult to view from a seated position due to its height and viewing angle. Remote UI, PRINTER DRIVER, DOCUMENT and Canon PRINT: The products can be accessed without requiring physical reach to product controls or components.
302.9 With Limited Language, Cognitive, and Learning Abilities. ICT shall provide features making its use by individuals with limited cognitive, language, and learning abilities simpler and easier.	Partially Supports	HARDWARE: The product provides labels, status indications, error notifications, and information that is not dependent on color or audio alone. Some functions can be accessed through Canon PRINT or Remote UI using assistive technologies, and certain timeout-based functions can be disabled. However, the product does not provide speech output, and some non-text content and error information may not be fully accessible. Remote UI: Remote UI supports understanding and ease of use through clear labels, consistent navigation, and predictable behavior. However, some ink level information and non-text content lack sufficient explanatory information, some content relationships are not clearly conveyed, and help or error assistance features are not provided. PRINTER DRIVER: Accessibility features support users in completing tasks with minimal interruption and consistent operation. DOCUMENT: Components with the same functionality are identified consistently, supporting understanding and learning. Canon PRINT: Canon PRINT provides features that support understanding and operation. However, not all applicable accessibility criteria related to cognition, language, and learning are fully supported.

Chapter 4: Hardware

Criteria	Conformance Level	Remarks and Explanations
402.1 General. (Closed Functionality) ICT with closed functionality shall be operable without requiring the user to attach or install assistive technology other than personal headsets or other audio couplers, and shall conform to 402.	No response required according to ITI VPAT.	
402.2.1 Information Displayed On-Screen. Speech output shall be provided for all information displayed on-screen.	Partially Supports	The product itself does not provide audio output, such as voice guidance. However, some functions can be operated using Canon PRINT with VoiceOver or TalkBack. Device status and settings can also be accessed through Remote UI using screen reader software on a PC, such as JAWS.
402.2.2 Transactional Outputs. Where transactional outputs are provided, the speech output shall audibly provide all information necessary to verify a transaction.	Supports*	The product does not provide self-service or transaction-processing functionality.

402.2.3 Speech Delivery Type and Coordination. Speech output shall be delivered through a mechanism that is readily available to all users, including, but not limited to, an industry standard connector or a telephone handset. Speech shall be recorded or digitized human, or synthesized. Speech output shall be coordinated with information displayed on the screen.	Supports*	The product itself does not provide audio output, such as voice guidance. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Access to speech output and the method of audio delivery depend on the user's computing device and screen reader software.
402.2.4 User Control. Speech output for any single function shall be automatically interrupted when a transaction is selected. Speech output shall be capable of being repeated and paused.	Supports*	Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Control of speech output, including functions such as stop and repeat, depends on the user's computing device and screen reader software.
402.2.5 Braille Instructions. Where speech output is required by 402.2, braille instructions for initiating the speech mode of operation shall be provided. Braille shall be contracted and shall conform to 36 CFR part 1191, Appendix D, Section 703.3.1.	Supports*	Speech output is not provided by the product itself.
402.3.1 Private Listening. Where ICT provides private listening, it shall provide a mode of operation for controlling the volume. Where ICT delivers output by an audio transducer typically held up to the ear, a means for effective magnetic wireless coupling to hearing technologies shall be provided.	Supports*	Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Adjustment of speech output and connectivity to hearing technologies depend on the user's computing device, screen reader software, and listening technology.
402.3.2 Non-private Listening. Where ICT provides non-private listening, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. A function shall be provided to automatically reset the volume to the default level after every use.	Supports*	Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Speech output controls, including volume adjustment, depend on the user's computing device, screen reader software, and audio output device.
402.4 Characters on Display Screens. At least one mode of characters displayed on the screen shall be in a sans serif font. Where ICT does not provide a screen enlargement feature, characters shall be 3/16 inch (4.8 mm) high minimum based on the uppercase letter "I". Characters shall contrast with their background with either light characters on a dark background or dark characters on a light background.	Partially Supports	The character size displayed on the screen is approximately 3.5 mm and does not meet the minimum size requirement specified by this criterion. However, the characters provide sufficient contrast against the background, which helps maintain a degree of readability.
402.5 Characters on Variable Message Signs. Characters on variable message signs shall conform to section 703.7 Variable Message Signs of ICC A117.1:2009.	Supports*	No variable message signs are provided.
403.1 Biometrics Where provided, biometrics shall not be the only means for user identification or control. .	Supports*	No biometric user identification is used.
404.1 Preservation of Information Provided for Accessibility ICT that transmits or converts information or communication shall not remove non-proprietary information provided for accessibility or shall restore it upon delivery.	Supports*	The import/export functions are applicable to this requirement. However, no accessibility-related information is included in the imported or exported data; therefore, there is no such information to preserve.
405.1 Privacy. The same degree of privacy of input and output shall be provided to all individuals. When speech output required by 402.2 is enabled, the screen shall not blank automatically.	Supports	Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. In accordance with Canon Global Privacy principles, privacy is provided equally to all users, regardless of disability. In addition, Remote UI does not provide a feature that conceals on-screen information while screen reader output is active.

406.1 Standard Connections Where data connections used for input and output are provided, at least one of each type of connection shall conform to industry standard non-proprietary formats.	Supports	All connection interfaces conform to industry standards.
407.2 Contrast. Where provided, keys and controls shall contrast visually from background surfaces. Characters and symbols shall contrast visually from background surfaces with either light characters or symbols on a dark background or dark characters or symbols on a light background.	Partially Supports	Some areas related to paper and ink replacement and maintenance have low contrast, making them difficult for users to visually identify during replacement.
407.3.1 Tactilely Discernible. Input controls shall be operable by touch and tactilely discernible without activation.	Does not support	The product uses a touchscreen interface and provides four physical input controls. Three of these controls are readily distinguishable by touch. The power button is tactilely discernible; however, its tactile features are less distinct and may not be readily identifiable by touch.
407.3.2 Alphabetic Keys. Where provided, individual alphabetic keys shall be arranged in a QWERTY-based keyboard layout and the "F" and "J" keys shall be tactilely distinct from the other keys.	Does not support	No alphabetic or numeric hard keys are provided. The device uses software keys on the touchscreen and does not meet the requirement.
407.3.3 Numeric Keys. Where provided, numeric keys shall be arranged in a 12-key ascending or descending keypad layout. The number five key shall be tactilely distinct from the other keys. Where the ICT provides an alphabetic overlay on numeric keys, the relationships between letters and digits shall conform to ITU-T Recommendation E.161	Does not support	No alphabetic or numeric hard keys are provided. The device uses software keys on the touchscreen and does not meet the requirement.
407.4 Key Repeat. Where a keyboard with key repeat is provided, the delay before the key repeat feature is activated shall be fixed at, or adjustable to, 2 seconds minimum.	Does not support	The key repeat function is provided and cannot be disabled by the user.
407.5 Timed Response. Where a timed response is required, the user shall be alerted visually, as well as by touch or sound, and shall be given the opportunity to indicate that more time is needed.	Supports	In certain settings screens, the display may be locked after a timeout period. The screen lock function can be disabled. When the paper type selection method is set to "Automatic", the operation is automatically executed after 5 seconds of inactivity. This behavior can also be disabled through configuration.
407.6 Operation. (General) At least one mode of operation shall be operable with one hand and shall not require tight grasping, pinching, or twisting of the wrist. The force required to activate operable parts shall be 5 pounds (22.2 N) maximum.	Partially Supports	Ink tank and roll paper replacement may require the use of both hands or forces exceeding 22.2 N in some situations, and no alternative means of operation is provided.
407.7 Tickets, Fare Cards, and Keycards. Where tickets, fare cards, or keycards are provided, they shall have an orientation that is tactilely discernible if orientation is important to further use of the ticket, fare card, or keycard.	Supports*	No cards are used.
407.8.1 Vertical Reference Plane. Operable parts shall be positioned for a side reach or a forward reach determined with respect to a vertical reference plane. The vertical reference plane shall be located in conformance to 407.8.2 or 407.8.3.	Supports	A vertical reference plane for side approach can be provided. The product is designed for side approach by seated users.
407.8.1.1 Vertical Plane for Side Reach. Where a side reach is provided, the vertical reference plane shall be 48 inches (1220 mm) long minimum.	Supports	A vertical reference plane for side approach can be provided. The product is designed for side approach by seated users.
407.8.1.2 Vertical Plane for Forward Reach. Where a forward reach is provided, the vertical reference plane shall be 30 inches (760 mm) long minimum.	Not Applicable	A vertical reference plane for side approach can be provided. The product is designed for side approach by seated users.

407.8.2 Side Reach. Operable parts of ICT providing a side reach shall conform to 407.8.2.1 or 407.8.2.2. The vertical reference plane shall be centered on the operable part and placed at the leading edge of the maximum protrusion of the ICT within the length of the vertical reference plane. Where a side reach requires a reach over a portion of the ICT, the height of that portion of the ICT shall be 34 inches (865 mm) maximum.	Does not support	When replacing ink or configuring the display, the main unit itself becomes an obstruction, as its height exceeds 865 mm.
407.8.2.1 Unobstructed Side Reach. Where the operable part is located 10 inches (255 mm) or less beyond the vertical reference plane, the operable part shall be 48 inches (1220 mm) high maximum and 15 inches (380 mm) high minimum above the floor.	Partially Supports	Some parts of the paper output basket and the stand lock are positioned less than 380 mm above the floor.
407.8.2.2 Obstructed side reach Where the operable part is located more than 10 inches (255 mm), but not more than 24 inches (610 mm), beyond the vertical reference plane, the height of the operable part shall be 46 inches (1170 mm) high maximum and 15 inches (380 mm) high minimum above the floor. The operable part shall not be located more than 24 inches (610 mm) beyond the vertical reference plane.	Partially Supports	Ink replacement requires a reach depth exceeding 610 mm.
407.8.3 Forward Reach. Operable parts of ICT providing a forward reach shall conform to 407.8.3.1 or 407.8.3.2. The vertical reference plane shall be centered, and intersect with, the operable part. Where a forward reach allows a reach over a portion of the ICT, the height of that portion of the ICT shall be 34 inches (865 mm) maximum.	Not Applicable	This product is intended for side access; therefore, no issues arise that require resolution.
407.8.3.1 Unobstructed forward reach Where the operable part is located at the leading edge of the maximum protrusion within the length of the vertical reference plane of the ICT, the operable part shall be 48 inches (1220 mm) high maximum and 15 inches (380 mm) high minimum above the floor.	Not Applicable	This product is intended for side access; therefore, no issues arise that require resolution.
407.8.3.2 Obstructed Forward Reach. Where the operable part is located beyond the leading edge of the maximum protrusion within the length of the vertical reference plane, the operable part shall conform to 407.12.3.2. The maximum allowable forward reach to an operable part shall be 25 inches (635 mm).	Not Applicable	This product is intended for side access by a wheelchair user.
407.8.3.2.1 Height. Where the operable part is located less than 20 inches (510 mm) beyond the vertical reference plane, the operable part shall be 48 inches (1220 mm) high maximum. Where the operable part is located 20 inches (510 mm) to 25 inches (635 mm) beyond the vertical reference plane, the operable part shall be 44 inches (1120 mm) high maximum.	Not Applicable	This product is intended for side access by a wheelchair user.
407.8.3.2.2 Knee and Toe Space. Knee and toe space under ICT shall be 27 inches (685 mm) high minimum, 25 inches (635 mm) deep maximum, and 30 inches (760 mm) wide minimum and shall be clear of obstructions.	Not Applicable	This product is intended for side access; therefore, no issues arise that require resolution.
408.2 Display Screens (General) Where stationary ICT provides one or more display screens, at least one of each type of display screen shall be visible from a point located 40 inches (1015 mm) above the floor space where the display screen is viewed.	Does not support	The display is positioned 1015 mm above the floor and may be difficult to view due to its height and viewing angle.
408.3 General. (Flashing) Where ICT emits lights in flashes, there shall be no more than three flashes in any one-second period.	Supports	Lights emitted by the product do not flash more than three times within a one-second period.
409.1 Status Indicators. Status indicators, including all locking or toggle controls or keys (e.g., Caps Lock and Num Lock keys), shall be discernible visually and by touch or sound.	Supports through Equivalent Facilitation	Status information presented on the operation panel and the illuminated state of indicator lamps are visually discernible. The product does not provide tactile or auditory indication of these states on the device itself. However, many status monitoring and configuration functions are available through Remote UI, which can be accessed using screen reader software on a PC.
410.1 Color Coding. Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	Supports	Information conveyed through the use of color is also conveyed through text. In addition, controls and visual elements that use color can be distinguished from surrounding elements by contrast.

411.1 Audible Signals. Where provided, audible signals or cues shall not be used as the only means of conveying information, indicating an action, or prompting a response.	Supports	All the information of audible signals or cues during operation are also given by the LED lights and other components visually.
--	----------	---

Chapter 5: Software

Criteria	Conformance Level	Remarks and Explanations
501.1 Scope. The requirements of Chapter 5 shall apply to software where required by 508 Chapter 2. (E207.2 WCAG Conformance. User interface components, as well as the content of platforms and applications, shall conform to Level A and Level AA Success Criteria and Conformance Requirements in WCAG 2.0)	See WCAG section.	
502.2.1 User Control of Accessibility Features. Platforms shall provide user control over platform features that are defined in the platform documentation as accessibility features.	PRINTER DRIVER: Supports* Canon PRINT: Not applicable	PRINTER DRIVER: The printer driver is not a platform. Canon PRINT: Canon PRINT is not a platform.
502.2.2 No Disruption of Accessibility Features. Software shall not disrupt platform features that are defined in the platform documentation as accessibility features.	PRINTER DRIVER: Supports Canon PRINT: Partially Supports	PRINTER DRIVER: The printer driver can be used without disruption of the accessibility features of the platform (verified with the accessibility functionality of Windows 10). Canon PRINT: Most platform accessibility features are applied without disruption, but there is a small minority which cannot be applied.
502.3.1 Object Information. The object role, state(s), boundary, name, and description shall be programmatically determinable.	PRINTER DRIVER: Partially Supports Canon PRINT: Supports	PRINTER DRIVER: The roles, states, boundary, names, and description of UI objects in the printer driver can be recognized programmatically. However, information of some UI objects is not read. Canon PRINT: Function names, operation methods, and settings status can all be correctly read.
502.3.2 Modification of Object Information. States and properties that can be set by the user shall be capable of being set programmatically, including through assistive technology.	PRINTER DRIVER: Partially Supports Canon PRINT: Supports	PRINTER DRIVER: The roles, states, boundary, names, and description of UI objects in the printer driver can be recognized programmatically. However, there are some UI objects not able to change the setting. Canon PRINT: Function names, operation methods, and settings status can all be correctly read.
502.3.3 Row, Column, and Headers. If an object is in a table, the occupied rows and columns, and any headers associated with those rows or columns, shall be programmatically determinable.	PRINTER DRIVER: Does not Support Canon PRINT: Not applicable	PRINTER DRIVER: Header cell and job data cells below the header are not read as set, and these are read in each row. Canon PRINT: There are no tables in Canon PRINT.

502.3.4 Values. Any current value(s), and any set or range of allowable values associated with an object, shall be programmatically determinable.	PRINTER DRIVER: Supports when combined with Compatible AT Canon PRINT: Supports	PRINTER DRIVER: The currently set value can be recognized programmatically for any UI object in the printer driver for which a value can be entered. However, for recognizing range of value, the use of assistive technology (e.g.JAWS) is needed. Canon PRINT: Setting ranges and current setting values can all be correctly read.
502.3.5 Modification of Values. Values that can be set by the user shall be capable of being set programmatically, including through assistive technology.	PRINTER DRIVER: Supports Canon PRINT: Supports	PRINTER DRIVER: Values that can be set by the user are capable of being set through the program. Canon PRINT: Function names, operation methods, and settings status can all be correctly read.
502.3.6 Label Relationships. Any relationship that a component has as a label for another component, or of being labeled by another component, shall be programmatically determinable.	PRINTER DRIVER: Partially Supports Canon PRINT: Supports	PRINTER DRIVER: The labels associated with UI components in the printer driver can be recognized programmatically. However, for recognizing some labels, the use of assistive technology (e.g. JAWS) is needed. Canon PRINT: The Canon PRINT UI screen has a list structure such that the screen is read in the correct order starting from the top.
502.3.7 Hierarchical Relationships. Any hierarchical (parent-child) relationship that a component has as a container for, or being contained by, another component shall be programmatically determinable.	PRINTER DRIVER: Supports Canon PRINT: Supports	PRINTER DRIVER: The labels associated with UI components in the printer driver can be recognized programmatically. Canon PRINT: The Canon PRINT UI screen has a list structure in which all hierarchical relationships are determinable.
502.3.8 Text The content of text objects, text attributes, and the boundary of text rendered to the screen, shall be programmatically determinable.	PRINTER DRIVER: Supports Canon PRINT: Supports	PRINTER DRIVER: In the printer driver, the attributes of UI objects for which text can be entered, as well as the boundary of text displayed on the screen, can be recognized programmatically. Canon PRINT: In Canon PRINT, the attributes of UI objects for which text can be entered, as well as the boundary of text displayed on the screen, can be recognized programmatically.
502.3.9 Modification of Text Text that can be set by the user shall be capable of being set programmatically, including through assistive technology.	PRINTER DRIVER: Supports Canon PRINT: Supports	PRINTER DRIVER: Texts that can be set by user are capable to be set programmatically through the program. Canon PRINT: Text can be changed programmatically for any UI object in Canon PRINT for which text can be entered.
502.3.10 List of Actions A list of all actions that can be executed on an object shall be programmatically determinable.	PRINTER DRIVER: Partially Supports Canon PRINT: Supports	PRINTER DRIVER: Operations that can be executed on a UI object in the printer driver can be recognized with the use of screen readers. However, for some of them, the use of assistive technology (e.g. JAWS) is needed for cursor movement. Canon PRINT: The Canon PRINT UI screen has a list structure in which all executable actions are determinable.

502.3.11 Actions on Objects. Applications shall allow assistive technology to programmatically execute available actions on objects.	PRINTER DRIVER: Partially Supports Canon PRINT: Supports	PRINTER DRIVER: Operations that can be executed on a UI object in the printer driver can be recognized with the use of screen readers. However, for some of them, the use of assistive technology (e.g. JAWS) is needed for cursor movement. Canon PRINT: The Canon PRINT UI screen has a list structure in which all executable actions are determinable.
502.3.12 Focus Cursor. Applications shall expose information and mechanisms necessary to track focus, text insertion point, and selection attributes of user interface components.	PRINTER DRIVER: Partially Supports Canon PRINT: Supports	PRINTER DRIVER: Changes of focus, component attributes, and text insertion points can be recognized in the printer driver. However, for some of them, the use of assistive technology (e.g. JAWS) is needed for cursor movement. Canon PRINT: Changes of focus, component attributes, and text insertion points can be recognized by Canon PRINT.
502.3.13 Modification of Focus Cursor. Focus, text insertion point, and selection attributes that can be set by the user shall be capable of being set programmatically, including through the use of assistive Technology.	PRINTER DRIVER: Partially Supports Canon PRINT: Supports	PRINTER DRIVER: Changes of focus, component attributes, and text insertion points can be recognized in the printer driver. However, for some of them, the use of assistive technology (e.g. JAWS) is needed for cursor movement. Canon PRINT: Changes of focus, component attributes, and text insertion points can be recognized and set programmatically by Canon PRINT.
502.3.14 Event Notification. Notification of events relevant to user interactions, including but not limited to, changes in the component's state(s), value, name, description, or boundary, shall be available to assistive technology.	PRINTER DRIVER: Supports Canon PRINT: Supports	PRINTER DRIVER: When changes of UI components occur, the printer driver can notify it programmatically. Canon PRINT: Canon PRINT supports notification of changes to components when such changes occur.
502.4 Platform Accessibility Features. Platforms and platform software shall conform to the requirements in ANSI/HFES 200.2, Human Factors Engineering of Software User Interfaces — Part 2: Accessibility (incorporated by reference in Chapter 1) listed below: Section 9.3.3 Enable sequential entry of multiple (chorded) keystrokes. 2. Section 9.3.4 Provide adjustment of delay before key acceptance. 3. Section 9.3.5 Provide adjustment of same-key double-strike acceptance. 4. Section 10.6.7 Allow users to choose visual alternative for audio output. 5. Section 10.6.8 Synchronize audio equivalents for visual events. 6. Section 10.6.9 Provide speech output services. 7. Section 10.7.1 Display any captions provided.	PRINTER DRIVER: Supports* Canon PRINT: Not applicable	PRINTER DRIVER: The product is not a platform. Canon PRINT: Canon PRINT is neither a platform nor platform software.
503.2 User Preferences. Applications shall permit user preferences from platform settings for color, contrast, font type, font size, and focus cursor.	PRINTER DRIVER: Supports Canon PRINT: Partially Supports	PRINTER DRIVER: The printer driver can be used without disruption of the accessibility features of the platform (verified with the accessibility functionality of Windows 10). Canon PRINT: User preferences for color, font type, and focus cursor are applied. However, some settings for font size and contrast cannot be applied.

503.3 Alternative User Interfaces. Where an application provides an alternative user interface that functions as assistive technology, the application shall use platform and other industry standard accessibility services.	PRINTER DRIVER: Supports* Canon PRINT: Not applicable	PRINTER DRIVER: The printer driver does not provide functionality relating to accessibility. Canon PRINT: Canon PRINT does not provide functionality relating to accessibility.
503.4.1 Caption Controls. Where user controls are provided for volume adjustment, ICT shall provide user controls for the selection of captions at the same menu level as the user controls for volume or program selection.	PRINTER DRIVER: Supports* Canon PRINT: Not applicable	PRINTER DRIVER: The printer driver does not provide any video content with synchronized audio. Canon PRINT: Canon PRINT does not include any video content.
503.4.2 Audio Description Controls. Where user controls are provided for program selection, ICT shall provide user controls for the selection of audio description at the same menu level as the user controls for volume or program selection.	PRINTER DRIVER: Supports* Canon PRINT: Not applicable	PRINTER DRIVER: The printer driver does not provide any video content with synchronized audio. Canon PRINT: Canon PRINT does not include any video content.
504.2 Content Creation or Editing. Authoring tools shall provide a mode of operation to create or edit content that conforms to Level A and Level AA Success Criteria and Conformance Requirements in WCAG (incorporated by reference, see 702.10.1) for all supported features and, as applicable, to file formats supported by the authoring tool. Authoring tools shall permit authors the option of overriding information required for accessibility.	PRINTER DRIVER:Not applicable Canon PRINT: Not applicable	Canon PRINT: Canon PRINT is not an authoring tool.
504.2.1 Preservation of Information Provided for Accessibility in Format Conversion. Authoring tools shall, when converting content from one format to another or saving content in multiple formats, preserve the information required for accessibility to the extent that the information is supported by the destination format.	PRINTER DRIVER:Not applicable Canon PRINT: Not applicable	Canon PRINT: Canon PRINT is not an authoring tool.
504.2.2 PDF Export. Authoring tools capable of exporting PDF files that conform to ISO 32000?1:2008 (PDF 1.7) shall also be capable of exporting PDF files that conform to ANSI/AIIM/ISO 14289?1:2016 (PDF/UA-1)	PRINTER DRIVER:Not applicable Canon PRINT: Not applicable	Canon PRINT: Canon PRINT has PDF creation functionality but is not an authoring tool.
504.3 Prompts. Authoring tools shall provide a mode of operation that prompts authors to create content that conforms to all Level A and Level AA Success Criteria and all Conformance Requirements in WCAG (incorporated by reference in Chapter 1). Authoring tools shall provide the option for prompts during initial content creation or when the content is saved.	PRINTER DRIVER:Not applicable Canon PRINT: Not applicable	Canon PRINT: Canon PRINT is not an authoring tool.
504.4 Templates. Where templates are provided, templates allowing content creation that conforms to all Level A and Level AA Success Criteria and all Conformance Requirements in WCAG (incorporated by reference in Chapter 1) shall be provided for a range of template uses.	PRINTER DRIVER:Not applicable Canon PRINT: Not applicable	Canon PRINT: Canon PRINT is not an authoring tool.

Chapter 6: Support Documentation and Services

Criteria	Conformance Level	Remarks and Explanations
602.2 Accessibility and Compatibility Features. Documentation shall list and explain how to use the accessibility and compatibility features required by Chapters 4 and 5. Documentation shall include accessibility features that are built-in and accessibility features that provide compatibility with assistive technology.	Supports	This VPAT lists and explains the features required by Section 508 Standard (2017) Chapters 4 and 5.
602.3 Electronic Support Documentation. Documentation in electronic format, including Web-based self-service support, shall conform to Level A and Level AA Success Criteria and Conformance Requirements in WCAG (incorporated by reference, see 702.10.1).	Supports	The WCAG is applied to the documentation. See WCAG section for the results.

602.4 Alternate Formats for Non-electronic Support Documentation. Where support documentation is only provided in non-electronic formats, alternate formats usable by individuals with disabilities shall be provided upon request.	Supports	Product support documentation will be provided upon request in electronic format.
603.2 Information on Accessibility and Compatibility Features. ICT support services shall include information on the accessibility and compatibility features required by 602.2.	Supports	Support services will provide information about functions related to accessibility by means according to user's requests.
603.3 Accommodation of Communication Needs. Support services shall be provided directly to the user or through a referral to a point of contact. Such ICT support services shall accommodate the communication needs of individuals with disabilities.	Supports	Canon U.S.A., Inc. provides support services accommodating users with disabilities through 1(800) OKCANON (652-2666) assistance, TTY support at (866)251-3752. Canon otherwise available to U.S. federal government agencies through Federal Relay.

Clause 4: Functional Performance Statements

Criteria	Conformance Level	Remarks and Explanations
4.2.1 Usage without vision Where ICT provides visual modes of operation, the ICT provides at least one mode of operation that does not require vision. This is essential for users without vision and benefits many more users in different situations.	Partially Supports	HARDWARE: The product primarily uses a touchscreen-based visual interface and does not provide speech output, such as voice guidance or audio access to screen information. Status information and indicator lamps are primarily visual, and tactile access to controls and status information is limited. Some functions can be accessed using Canon PRINT with VoiceOver or TalkBack on a mobile device or through Remote UI with a screen reader on a PC. However, certain non-text content, error information, and accessibility-related settings may not be fully accessible without vision. Remote UI: Remote UI is generally usable with a screen reader on a PC. However, some ink-level information and non-text content lack appropriate text alternatives or are not announced correctly. On some screens, the reading order and relationships between items are not fully conveyed. Some error information is not available through speech output alone, repeated navigation blocks cannot be bypassed, and certain functions are not fully operable using a keyboard. PRINTER DRIVER: The printer driver is generally operable using a keyboard with a screen reader. However, not all functions are fully accessible without vision. DOCUMENT: Text alternatives are provided for non-text content presented to users, enabling the content to be accessed without vision. Canon PRINT: Canon PRINT is generally usable with VoiceOver or TalkBack on a mobile device. However, not all applicable functions and content are fully accessible without vision. *Access to Remote UI: To access the Remote UI, enter the IP address of your Canon device (for example, http://XXX.XXX.XXX.XXX) into a web browser. Navigation within the Remote UI can be performed primarily using the arrow keys to move between user interface elements. In this version of the Remote UI, child elements are presented immediately after their corresponding parent elements in the navigation and reading order.
4.2.2 Usage with limited vision Where ICT provides visual modes of operation, the ICT provides features that enable users to make better use of their limited vision. This is essential for users with limited vision and benefits many more users in different situations.	Partially Supports	HARDWARE: Information is visually presented on the display and indicator lamps. Information conveyed by color is also available in text, and controls can generally be distinguished through contrast. However, the on-screen text size is smaller than the minimum requirement, some areas used for paper, ink, and maintenance operations have limited contrast, and the product does not provide text enlargement or display customization features. Remote UI: Remote UI supports text resizing, sufficient contrast, and information that is not conveyed by color alone. However, some ink level information and non-text content lack appropriate text alternatives, some controls do not meet target size requirements, repeated navigation blocks cannot be bypassed, certain functions do not fully support keyboard operation, and error assistance or help functions are not provided. PRINTER DRIVER: The printer driver provides sufficient contrast between text and background, enabling use by many users with limited vision.

		DOCUMENT: Non-text content is accompanied by text alternatives, enabling information to be accessed more easily by users with limited vision and through magnification tools. Canon PRINT: Canon PRINT generally supports users with limited vision through platform accessibility features such as screen magnification and high-contrast display settings. However, not all applicable accessibility criteria are fully supported.
4.2.3 Usage without perception of colour Where ICT provides visual modes of operation, the ICT provides a visual mode of operation that does not require user perception of colour. This is essential for users with limited colour perception and benefits many more users in different situations.	Supports	HARDWARE, Remote UI, PRINTER DRIVER and DOCUMENT: Information is not conveyed by color alone. Color-coded information is supplemented with text, and controls can be distinguished through contrast with surrounding areas. Canon PRINT: Information is generally not conveyed by color alone. However, not all applicable accessibility criteria related to color-independent use are fully supported.
4.2.4 Usage without hearing Where ICT provides auditory modes of operation, the ICT provides at least one mode of operation that does not require hearing. This is essential for users without hearing and benefits many more users in different situations.	Supports	HARDWARE: Operation of the product does not require hearing. Audible notifications, when provided, are also available through visual indicators such as the display and status lamps. Remote UI, PRINTER DRIVER, DOCUMENT and Canon PRINT: The products do not rely on auditory information and can be used without hearing.
4.2.5 Usage with limited hearing Where ICT provides auditory modes of operation, the ICT provides enhanced audio features. This is essential for users with limited hearing and benefits many more users in different situations.	Supports	HARDWARE: Operation of the product does not require hearing. Audible notifications, when provided, are also available through visual indicators such as the display and status lamps. Remote UI, PRINTER DRIVER, DOCUMENT and Canon PRINT: The products do not rely on auditory information and can be used without hearing.
4.2.6 Usage with no or limited vocal capability Where ICT requires vocal input from users, the ICT provides at least one mode of operation that does not require them to generate vocal output. This is essential users with no or limited vocal capability and benefits many more users in different situations.	Supports	The product does not require speech input, voice commands, or speech-based user identification. All functions can be operated without vocal input.
4.2.7 Usage with limited manipulation or strength Where ICT requires manual actions, the ICT provides features that enable users to make use of the ICT through alternative actions not requiring manipulation, simultaneous action or hand strength. This is essential for users with limited manipulation or strength and benefits many more users in different situations.	Partially Supports	HARDWARE: The product does not require multipoint gestures, path-based gestures, simultaneous actions, or motion-based operation for touchscreen use. However, maintenance tasks such as paper replacement and roll paper installation require pinching, twisting, and coordinated manual actions, and no alternative method is provided. Remote UI: Most functions can be performed without fine motor control or simultaneous actions. However, some functions are not fully operable using only a keyboard. PRINTER DRIVER: All functions can be operated using a keyboard interface without requiring simultaneous manual actions. DOCUMENT: Documentation can be accessed and navigated using standard keyboard functions without requiring simultaneous manual actions. Canon PRINT: Most functions can be operated using standard touch gestures without requiring multipoint or path-based gestures. However, not all applicable accessibility criteria related to limited manipulation are fully supported.

4.2.7 Usage with limited manipulation or strength Where ICT requires manual actions, the ICT provides features that enable users to make use of the ICT through alternative actions not requiring manipulation, simultaneous action or hand strength. This is essential for users with limited manipulation or strength and benefits many more users in different situations.	Partially Supports	HARDWARE: Some operations, including ink tank replacement and roll paper replacement, require force exceeding 22.2 N. No alternative method is provided for these operations. Remote UI, PRINTER DRIVER, DOCUMENT and Canon PRINT: Use of the products does not require significant hand strength.
4.2.8 Usage with limited reach Where ICT products are free-standing or installed, all the elements required for operation will need to be within reach of all users. This is essential for users with limited reach and benefits many more users in different situations.	Partially Supports	HARDWARE: Obstacles exceeding 865 mm are present when operating the touch screen, control panel buttons, top cover, and ink tanks. The ink replacement reach depth exceeds 610 mm. The open top cover and ink tank positions exceed 1170 mm in height. In addition, the display is difficult to view from a seated position due to its height and viewing angle. Remote UI, PRINTER DRIVER, DOCUMENT and Canon PRINT: The products can be accessed without requiring physical reach to product controls or components.
4.2.9 Minimize photosensitive seizure triggers Where ICT provides visual modes of operation, the ICT provides at least one mode of operation that minimizes the potential for triggering photosensitive seizures. This is essential for users with photosensitive seizure triggers.	Supports	The product does not contain flashing content that may trigger photosensitive seizures. Display indicators and status lamps do not flash in a manner that may adversely affect users.
4.2.10 Usage with limited cognition, language or learning The ICT provides features and/or presentation that makes it simpler and easier to understand, operate and use. This is essential for users with limited cognition, language or learning, and benefits many more users in different situations.	Partially Supports	HARDWARE: The product provides labels, status indications, error notifications, and information that is not dependent on color or audio alone. Some functions can be accessed through Canon PRINT or Remote UI using assistive technologies, and certain timeout-based functions can be disabled. However, the product does not provide speech output, and some non-text content and error information may not be fully accessible. Remote UI: Remote UI supports understanding and ease of use through clear labels, consistent navigation, and predictable behavior. However, some ink level information and non-text content lack sufficient explanatory information, some content relationships are not clearly conveyed, and help or error assistance features are not provided. PRINTER DRIVER: Accessibility features support users in completing tasks with minimal interruption and consistent operation. DOCUMENT: Components with the same functionality are identified consistently, supporting understanding and learning. Canon PRINT: Canon PRINT provides features that support understanding and operation. However, not all applicable accessibility criteria related to cognition, language, and learning are fully supported.
4.2.11 Privacy Where ICT provides features for accessibility, the ICT maintains the privacy of users of these features at the same level as other users.	Supports	The product provides the same level of privacy to users with disabilities as to users without disabilities. No accessibility features were identified that reduce user privacy.

Clause 5: Generic Requirements

Criteria	Conformance Level	Remarks and Explanations
5.1.2.2 Assistive technology Where ICT has closed functionality, that closed functionality shall be operable without requiring the user to attach, connect or install assistive technology and shall conform to the generic requirements of clauses 5.1.3 to 5.1.6 as applicable. Personal headsets and personal induction loops shall not be classed as assistive technology for the purpose of this clause.	See information in 5.1.3 through 5.1.6	
5.1.3.1 Audio output of visual information Where visual information is needed to enable the use of those functions of ICT that are closed to assistive technologies for screen reading, ICT shall provide at least one mode of operation using non-visual access to enable the use of those functions.	HARDWARE: Partially Supports PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Supports	HARDWARE: The product itself does not provide audio output, such as voice guidance. However, some functions can be operated using Canon PRINT with VoiceOver or TalkBack. Device status and settings can also be accessed through Remote UI using screen reader software on a PC, such as JAWS. PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. Remote UI: This requirement is not applied to the product, which is not closed to AT. Canon PRINT: Canon PRINT supports the screen reading functionality of the operating system.
5.1.3.2 Auditory output delivery including speech Where auditory output is provided as non-visual access to closed functionality, the auditory output shall be delivered: a) either directly by a mechanism included in or provided with the ICT; b) or by a personal headset that can be connected through a 3,5 mm audio jack, or an industry standard connection, without requiring the use of vision.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Not applicable	HARDWARE: The product itself does not provide audio output, such as voice guidance. However, some on-screen functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Access to speech output and the method of audio delivery depend on the user's computing device and screen reader software. PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. Remote UI: This requirement is not applied to the product, which is not closed to AT. Canon PRINT: Auditory output is not part of the functionality of the Canon PRINT product itself, so this guideline is not applicable to Canon PRINT.
5.1.3.3 Auditory output correlation Where auditory output is provided as non-visual access to closed functionality, and where information is displayed on the screen, the ICT should provide auditory information that allows the user to correlate the audio with the information displayed on the screen.	HARDWARE: Partially Supports PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Supports	HARDWARE: Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Because the product display and Remote UI use different layouts, the information available through speech output does not correspond one-to-one with the information displayed on the product screen. PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. Remote UI: This requirement is not applied to the product, which is not closed to AT. (Ref.: The result for WCAG 1.3.1 is "Partially supports".) Canon PRINT: The application conforms with WCAG Criteria 1.3.1, and consequently with this requirement too.

5.1.3.4 Speech output user control Where speech output is provided as non-visual access to closed functionality, the speech output shall be capable of being interrupted and repeated when requested by the user, where permitted by security requirements.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Not applicable	HARDWARE: Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Control of speech output, including functions such as stop and repeat, depends on the user's computing device and screen reader software. PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. Remote UI: This requirement is not applied to the product, which is not closed to AT. (Ref.: There is no interference with the accessibility function of OS.) Canon PRINT: Speech output is provided through the accessibility features of the operating system, not directly from Canon PRINT. Hence this criterion is not applicable.
5.1.3.5 Speech output automatic interruption Where speech output is provided as non-visual access to closed functionality, the ICT shall interrupt current speech output when a user action occurs and when new speech output begins.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Not applicable	HARDWARE: Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Control of speech output, including automatic interruption when a user action occurs or when new speech output begins, depends on the user's computing device and screen reader software. PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. Remote UI: This requirement is not applied to the product, which is not closed to AT. (Ref.: There is no interference with the function of assistive technology.) Canon PRINT: Speech output is provided through the accessibility features of the operating system, not directly from Canon PRINT. Hence this criterion is not applicable.
5.1.3.6 Speech output for non-text content Where ICT presents non-text content, the alternative for non-text content shall be presented to users via speech output unless the non-text content is pure decoration or is used only for visual formatting. The speech output for non-text content shall follow the guidance for "text alternative" described in WCAG 2.1 Success Criterion 1.1.1.	HARDWARE: Partially Supports PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Supports	HARDWARE: The product itself does not provide audio output, such as voice guidance. Some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. However, some non-text content within Remote UI is not accessible to screen readers. PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. Remote UI: This requirement is not applied to the product, which is not closed to AT. (Ref.: The result for WCAG 1.1.1 is "Partially supports".) Canon PRINT: Canon PRINT supports the screen reading functionality of the operating system.

5.1.3.7 Speech output for video information Where pre-recorded video content is needed to enable the use of closed functions of ICT and where speech output is provided as non-visual access to closed functionality, the speech output shall present equivalent information for the pre-recorded video content.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Not applicable	HARDWARE: No video content is used. PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. Remote UI: This requirement is not applied to the product, which is not closed to AT. (Ref.: There is no video content.) Canon PRINT: Canon PRINT does not include any video content.
5.1.3.8 Masked entry Where auditory output is provided as non-visual access to closed functionality, and the characters displayed are masking characters, the auditory output shall not be a spoken version of the characters entered unless the auditory output is known to be delivered only to a mechanism for private listening, or the user explicitly chooses to allow non-private auditory output.	HARDWARE: Supports PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Supports	HARDWARE: Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Characters entered in masked fields, such as password fields, are not spoken by screen readers. PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. Remote UI: This requirement is not applied to the product, which is not closed to AT. (Ref.: Masking characters are not read out while using assistive technology.) Canon PRINT: The masking characters are read as displayed, and the entered characters are not read.
5.1.3.9 Private access to personal data Where auditory output is provided as non-visual access to closed functionality, and the output contains data that is considered to be private according to the applicable privacy policy, the corresponding auditory output shall only be delivered through a mechanism for private listening that can be connected without requiring the use of vision, or through any other mechanism explicitly chosen by the user.	HARDWARE: Supports PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Supports	HARDWARE: Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on a mobile device or computer. In accordance with the Canon Global Privacy Statement, the privacy of all individuals is protected equally, regardless of disability. PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. Remote UI: This requirement is not applied to the product, which is not closed to AT. (Ref.: Personal listening is not eliminated while using assistive technology.) Canon PRINT: By using earphones, auditory output of personal information output by the operating system's assistive technology can be provided privately.

5.1.3.10 Non-interfering audio output Where auditory output is provided as non-visual access to closed functionality, the ICT shall not automatically play, at the same time, any interfering audible output that lasts longer than three seconds.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Supports	HARDWARE: Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Whether interfering audible output is played simultaneously with speech output depends on the user's computing device, screen reader software, and audio configuration. PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. Remote UI: This requirement is not applied to the product, which is not closed to AT. Canon PRINT: Canon PRINT does not produce any interfering sounds lasting longer than three seconds at the same time as auditory output.
5.1.3.11 Private listening Where auditory output is provided as non-visual access to closed functionality and is delivered through a mechanism for private listening, ICT shall provide at least one non-visual mode of operation for controlling the volume.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Not applicable	HARDWARE: Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Speech output controls, including volume adjustment, depend on the user's computing device, screen reader software, and listening technology. PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. Remote UI: This requirement is not applied to the product, which is not closed to AT. (Ref.: It does not interfere with PC or OS functions using AT.) Canon PRINT: Canon PRINT does not provide a mechanism for private listening directly from the application.
5.1.3.12 Speaker volume Where auditory output is provided as non-visual access to closed functionality and is delivered through speakers on ICT, a non-visual incremental volume control shall be provided with output amplification up to a level of at least 65 dBA (-29 dBPaA).	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Not applicable	HARDWARE: Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Speech output controls, including volume adjustment, depend on the user's computing device, screen reader software, and audio output device. PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. Remote UI: This requirement is not applied to the product, which is not closed to AT. Canon PRINT: Speech output is provided through the accessibility features of the operating system, not directly from Canon PRINT. Hence this criterion is not applicable.

5.1.3.13 Volume reset Where auditory output is provided as non-visual access to closed functionality, a function that resets the volume to be at a level of 65 dBA or less after every use, shall be provided, unless the ICT is dedicated to a single user.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Not applicable	HARDWARE: Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Speech output controls, including volume adjustment and volume reset, depend on the user's computing device, screen reader software, and audio output device. PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. Remote UI: This requirement is not applied to the product, which is not closed to AT. Canon PRINT: Speech output is provided through the accessibility features of the operating system, not directly from Canon PRINT. Hence this criterion is not applicable.
5.1.3.14 Spoken languages Where speech output is provided as non-visual access to closed functionality, speech output shall be in the same human language as the displayed content provided, except: a) for proper names, technical terms, words of indeterminate language, and words or phrases that have become part of the vernacular of the immediately surrounding text; b) where the content is generated externally and not under the control of the ICT vendor, the present clause shall not be required to apply for languages not supported by the ICT's speech synthesizer; c) for displayed languages that cannot be selected using non-visual access; d) where the user explicitly selects a speech language that is different from the language of the displayed content.	HARDWARE: Partially Supports PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Supports	HARDWARE: The product itself does not provide audio output, such as voice guidance. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Text and speech output are provided in the same language. PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. Remote UI: This requirement is not applied to the product, which is not closed to AT. (Ref.: The speech output uses the same human language as displayed.) Canon PRINT: The language read by the screen reader matches the language of the text.
5.1.3.15 Non-visual error identification Where speech output is provided as non-visual access to closed functionality and an input error is automatically detected, speech output shall identify and describe the item that is in error.	HARDWARE: Partially Supports PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Supports	HARDWARE: The product itself does not provide audio output, such as voice guidance. Some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. However, some error information within Remote UI is not accessible to screen readers. PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. Remote UI: This requirement is not applied to the product, which is not closed to AT. (Ref.: Errors are shown, but not read automatically) Canon PRINT: In Canon Print, when errors are displayed, the display of the error can be recognized programmatically and the error is displayed using an item name together with error content, which can be read by screen readers.

5.1.3.16 Receipts, tickets, and transactional outputs Where ICT is closed to visual access and provides receipts, tickets or other outputs as a result of a self-service transaction, speech output shall be provided which shall include all information necessary to complete or verify the transaction. In the case of ticketing machines, printed copies of itineraries and maps shall not be required to be audible.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Supports	HARDWARE: The product does not provide self-service or transaction-processing functionality. PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. Remote UI: This requirement is not applied to the product, which is not a self-service equipment, nor a product closed to AT. Canon PRINT: Canon ID and subscription services connected to this application all support text-to-speech.
5.1.4 Functionality closed to text enlargement Where any functionality of ICT is closed to the text enlargement features of platform or assistive technology, the ICT shall provide a mode of operation where the text and images of text necessary for all functionality is displayed in such a way that a non-accented capital "H" subtends an angle of at least 0,7 degrees at a viewing distance specified by the supplier. The subtended angle, in degrees, may be calculated from: $\Psi = (180 \times H) / (\pi \times D)$ Where: ψ is the subtended angle in degrees H is the height of the text D is the viewing distance D and H are expressed in the same units	HARDWARE: Supports PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Supports	HARDWARE: The requirement can be met by viewing the display from a distance of approximately 29 cm. Maintaining this viewing distance is readily achievable. PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. Remote UI: This requirement is not applied to the product, which is not closed to AT. (Ref.: The character enlargement function of the OS can be used.) Canon PRINT: Canon PRINT fully supports the text enlargement features of the operating system.
5.1.5 Visual output for auditory information Where auditory information is needed to enable the use of closed functions of ICT, the ICT shall provide visual information that is equivalent to the auditory output.	HARDWARE: Supports PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Not applicable	HARDWARE: Auditory information is not required to operate or use the product. PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. Remote UI: This requirement is not applied to the product, which is not closed to AT. (Ref.: Visual information can be provided using assistive technology.) Canon PRINT: Canon PRINT does not have any functionality that plays audio data.
5.1.6.1 Closed functionality Where ICT functionality is closed to keyboards or keyboard interfaces, all functionality shall be operable without vision as required by clause 5.1.3.	See information in 5.1.3.1 through 5.1.3.16	
5.1.6.2 Input focus Where ICT functionality is closed to keyboards or keyboard interfaces and where input focus can be moved to a user interface element, it shall be possible to move the input focus away from that element using the same mechanism, in order to avoid trapping the input focus.	HARDWARE: Supports* PRINTER DRIVER: Supports Remote UI: Supports* Canon PRINT: Not applicable	HARDWARE: The display is operated via a touchscreen and does not provide keyboard-based focus navigation. PRINTER DRIVER: Focus can be moved away from the component using only a keyboard interface. Remote UI: This requirement is not applied to the product, which is not closed to keyboard interface. (Ref.: Remote UI is keyboard-accessible with assistive technology.) Canon PRINT: Canon PRINT functionality is fully operable by keyboard.

5.1.7 Access without speech Where speech is needed to operate closed functions of ICT, the ICT shall provide at least one mode of operation using an alternative input mechanism that does not require speech.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Not applicable	HARDWARE: The product does not require voice input. PRINTER DRIVER: This requirement is not applied to the product, which is software. (There is no access requiring speech.) Remote UI: There is no access requiring speech. Canon PRINT: Canon PRINT does not have functions that require voice input to operate.
5.2 Activation of accessibility features Where ICT has documented accessibility features, it shall be possible to activate those documented accessibility features that are required to meet a specific need without relying on a method that does not support that need.	HARDWARE: Partially Supports PRINTER DRIVER: Supports Remote UI: Supports Canon PRINT: Not applicable	HARDWARE: The product provides a buzzer volume adjustment feature. However, activating and operating this feature without vision is difficult. PRINTER DRIVER: The printer driver can be used without disruption and prevention of activating of the accessibility features of the platform (verified with the accessibility functionality of Windows 10). Remote UI: The product does not interfere with the accessibility functions of the OS or the functions of assistive technologies such as screen reading. Canon PRINT: Canon PRINT does not have its own accessibility features. Accessibility functionality is provided by supporting the features provided by the operating system.
5.3 Biometrics Where ICT uses biological characteristics, it shall not rely on the use of a particular biological characteristic as the only means of user identification or for control of ICT.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Not applicable	HARDWARE: No biometric user identification is used. PRINTER DRIVER: The printer driver does not require biometric authentication. Remote UI: There is no biometrics. Canon PRINT: Canon PRINT does not support the use of biological characteristics for user identification.
5.4 Preservation of accessibility information during conversion Where ICT converts information or communication it shall preserve all documented non-proprietary information that is provided for accessibility, to the extent that such information can be contained in or supported by the destination format.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Not applicable	HARDWARE: The import/export functions are applicable to this requirement. However, no accessibility-related information is included in the imported or exported data; therefore, there is no such information to preserve. PRINTER DRIVER: The printer driver does not have an information conversion function. Remote UI: There is no information conversion function. Canon PRINT: Canon PRINT does not provide functionality relating to accessibility.

5.5.1 Means of operation Where ICT has operable parts that require grasping, pinching, or twisting of the wrist to operate, an accessible alternative means of operation that does not require these actions shall be provided.	HARDWARE: Partially Supports PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Not applicable	HARDWARE: Paper replacement requires pinching and gripping for some components, and no alternative method is provided. PRINTER DRIVER: This requirement is not applied to the product, which is software. Remote UI: This requirement is not applied to the product, which is software. Canon PRINT: This is not applicable because Canon PRINT is software.
5.5.2 Operable parts discernibility Where ICT has operable parts, it shall provide a means to discern each operable part, without requiring vision and without performing the action associated with the operable part.	HARDWARE: Does not support PRINTER DRIVER: Supports Remote UI: Partially Supports Canon PRINT: Supports	HARDWARE: The product uses a touchscreen interface and provides four physical input controls. Three of these controls are readily distinguishable by touch. The power button is tactilely discernible; however, its tactile features are less distinct and may not be readily identifiable by touch. PRINTER DRIVER: In case of softwares, this requirement can be comprehended to meet by operating through keyboards, the focus moving without stucked at specific elements, and the elements not activating just by receiving focus. The product does meet them. Remote UI: Basically, the focus moves to the operable parts and the voice output is provided through AT, however, operation through a keyboard are not provided in some specific functions. Canon PRINT: The screen reader functionality provided through the operating system allows operable parts to be discerned without requiring vision. As the speech is activated by moving focus, it is not required to perform the action associated with the operable part.
5.6.1 Tactile or auditory status Where ICT has a locking or toggle control and the status of that control is visually presented to the user, the ICT shall provide at least one mode of operation where the status of the control can be determined either through touch or sound without operating the control.	HARDWARE: Supports through Equivalent Facilitation PRINTER DRIVER: Partially Supports Remote UI: Partially Supports Canon PRINT: Supports	HARDWARE: Status information presented on the operation panel and the illuminated state of indicator lamps are visually discernible. The product does not provide tactile or auditory indication of these states on the device itself. However, many status monitoring and configuration functions are available through Remote UI, which can be accessed using screen reader software on a PC. PRINTER DRIVER: Text is provided for structures and information that can be interpreted programmatically. However, for some of them, the use of assistive technology (e.g. JAWS) is needed for cursor movement. Remote UI: Voice identification of selection status using assistive technology. In some contents, the item name of the check box is read out one step apart. Canon PRINT: The status of operable parts for locking or other toggles can be visually confirmed on Canon PRINT, and auditory confirmation is possible with assistive technology via the operating system.

5.6.2 Visual status Where ICT has a locking or toggle control and the status of the control is non-visually presented to the user, the ICT shall provide at least one mode of operation where the status of the control can be visually determined when the control is presented.	HARDWARE: Supports through Equivalent Facilitation PRINTER DRIVER: Supports Remote UI: Supports* Canon PRINT: Supports	HARDWARE: Status information presented on the operation panel and the illuminated state of indicator lamps are visually discernible. The product does not provide tactile or auditory indication of these states on the device itself. However, many status monitoring and configuration functions are available through Remote UI, which can be accessed using screen reader software on a PC. PRINTER DRIVER: The visual status can be determined whichever it is a locking or toggle control. Remote UI: There is no non-visually presented status. Canon PRINT: The status of operable parts for locking or other toggles can be visually confirmed on Canon PRINT, and auditory confirmation is possible with assistive technology via the operating system.
5.7 Key repeat Where ICT has a key repeat function that cannot be turned off: a) the delay before the key repeat shall be adjustable to at least 2 seconds; and b) the key repeat rate shall be adjustable down to one character per 2 seconds.	HARDWARE: Does not support PRINTER DRIVER: Supports Remote UI: Supports Canon PRINT: Supports	HARDWARE: The key repeat function is provided and cannot be disabled by the user. For manual roll paper operation, paper feeding begins less than 2 seconds after a button is pressed and held. PRINTER DRIVER: The printer driver can be used with the "Filter key function" of the OS function. Remote UI: Key repeat and bounce key settings provided by the OS are not inhibited. Canon PRINT: Key repeat can be prevented with functionality in the OS that Canon PRINT runs on, and Canon PRINT does not interfere with that functionality.
5.8 Double-strike key acceptance Where ICT has a keyboard or keypad, the delay after any keystroke, during which an additional key-press will not be accepted if it is identical to the previous keystroke, shall be adjustable up to at least 0,5 seconds.	HARDWARE: Does not support PRINTER DRIVER: Supports Remote UI: Supports Canon PRINT: Supports	HARDWARE: The product does not provide a configurable bounce key function. PRINTER DRIVER: The printer driver can be used with the "Filter key function" of the OS function. Remote UI: Key repeat and bounce key settings provided by the OS are not inhibited. Canon PRINT: An accidental additional key-press of the same key can be prevented with functionality in the OS that Canon PRINT runs on, and Canon PRINT does not interfere with that functionality.

5.9 Simultaneous user actions Where ICT has a mode of operation requiring simultaneous user actions for its operation, such ICT shall provide at least one mode of operation that does not require simultaneous user actions to operate the ICT.	HARDWARE: Partially Supports PRINTER DRIVER: Supports Remote UI: Supports Canon PRINT: Partially Supports	HARDWARE: Paper replacement requires coordinated actions, and no alternative method is provided. PRINTER DRIVER: In case of softwares, this requirement can be met by avoid pressing two or more keys at the same time. The product can be operated by using keyboards, and can be used without disruption of the accessibility features of the platform (verified with the accessibility functionality of Windows 10). Remote UI: A simultaneous user action is not required. Canon PRINT: The preview screen can only be enlarged/reduced using a pinch operation requiring two fingers.
--	---	--

Clause 8: Hardware

Criteria	Conformance Level	Remarks and Explanations
8.1.2 Standard connections Where an ICT provides user input or output device connection points, the ICT shall provide at least one input and/or output connection that conforms to an industry standard non-proprietary format, directly or through the use of commercially available adapters.	Supports	All connection interfaces conform to industry standards.
8.1.3 Colour Where the ICT has hardware aspects that use colour, colour shall not be used as the only visual means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	Supports	Information conveyed through the use of color is also conveyed through text. In addition, controls and visual elements that use color can be distinguished from surrounding elements by contrast.
8.3.4.1 Change in level Where stationary ICT has a floor within it, then any change of floor level within it or entering it shall be ramped with a slope no steeper than 1:48.	Not Applicable	The product is intended to be installed on a level floor and must be installed without any inclination.
8.3.4.2 Clear floor or ground space Where stationary ICT has an operating area within it, it shall provide a clear floor area that has the minimum dimensions of 760 mm (30 inches) by 1 220 mm (48 inches) from which to operate the ICT.	Not Applicable	The product itself does not provide an operating area. Appropriate clear floor or ground space for operation must be ensured during installation.
8.3.4.3.1 General Where stationary ICT has an access space inside it, at least one full side of the space shall be unobstructed.	Not Applicable	The product itself does not provide an operating area. Any clear floor or ground space required to access and operate the product is expected to be provided by the installation environment.
8.3.4.3.2 Forward approach Where the operating area is inside an alcove within the stationary ICT, the alcove is deeper than 610 mm (24 inches), and where a forward approach is necessary, the dimension of the access space shall be a minimum of 915 mm (36 inches) wide.	Not Applicable	The product itself does not provide access space to an operating area. In addition, the product is intended to be operated from the side rather than by a forward approach from a wheelchair.
8.3.4.3.3 Parallel approach Where the operating area is inside an alcove within the stationary ICT, the alcove is deeper than 380 mm (15 inches), and where a parallel approach is possible, the dimension of the access space shall be a minimum of 1 525 mm (60 inches) wide.	Not Applicable	The product itself does not provide access space to an operating area. Access to the operating area must be ensured at the installation site.
8.3.2.4 Knee and toe clearance width Where the space under an obstacle that is an integral part of the stationary ICT is part of access space, the clearance shall be at least 760 mm (30 inches) wide.	Not Applicable	This product is intended for side access; therefore, no issues arise that require resolution.

8.3.2.5 Toe clearance Where an obstacle is an integral part of the stationary ICT, a space under the obstacle that is less than 230 mm (9 inches) above the floor is considered toe clearance and shall: a) extend 635 mm (25 inches) maximum under the whole obstacle; b) provide a space at least 430 mm (17 inches) deep and 230 mm (9 inches) above the floor under the obstacle; c) extend no more than 150 mm (6 inches) beyond any obstruction at 230 mm (9 inches) above the floor.	Not Applicable	This product is intended for side access; therefore, no issues arise that require resolution.
8.3.2.6 Knee clearance Where an obstacle is an integral part of the stationary ICT, the space under the obstacle that is between 230 mm (9 inches) and 685 mm (25 inches) above the floor is considered knee clearance and shall: a) extend no more than 635 mm (25 inches) under the obstacle at a height of 230 mm (9 inches) above the floor; b) extend at least 280 mm (11 inches) under the obstacle at a height of 230 mm (9 inches) above the floor; c) extend at least 205 mm (8 inches) under the obstacle at a height of 685 mm (27 inches) above the floor; d) be permitted to be reduced in depth at a rate of 25 mm (1 inch) for each 150 mm (6 inches) in height.	Not Applicable	This product is intended for side access; therefore, no issues arise that require resolution.
8.3.2.1 Unobstructed high forward reach Where no part of the stationary ICT obstructs the forward reach, at least one of each type of operable part shall be located no higher than 1 220 mm (48 inches) above the floor of the access space.	Not Applicable	This product is intended for side access; therefore, no issues arise that require resolution.
8.3.2.2 Unobstructed low forward reach Where no part of the stationary ICT obstructs the forward reach, at least one of each type of operable part shall be located no lower than 380 mm (15 inches) above the floor of the access space.	Not Applicable	This product is intended for side access; therefore, no issues arise that require resolution.
8.3.2.3.1 Clear space Where an obstruction is an integral part of the stationary ICT and hinders the access to any type of operable part, the ICT shall provide a clear space which extends beneath the obstructing element for a distance not less than the required reach depth over the obstruction.	Not Applicable	This product is intended for side access by a wheelchair user.
8.3.2.3.2 Obstructed (< 510 mm) forward reach Where the stationary ICT has an obstruction which is an integral part of the ICT and which is less than 510 mm (20 inches), the forward reach to at least one of each type of operable part shall be no higher than 1 220 mm (48 inches) above the floor contact of the ICT.	Not Applicable	This product is intended for side access by a wheelchair user.
8.3.2.3.3 Obstructed (< 635 mm) forward reach Where the stationary ICT has an obstruction which is an integral part of the ICT and which is not less than 510 mm (20 inches) but is less than 635 mm (25 inches) maximum, the forward reach to at least one of each type of operable part shall be no higher than 1 120 mm (44 inches) above the floor contact of the ICT.	Not Applicable	This product is intended for side access by a wheelchair user.
8.3.3.1 Unobstructed high side reach Where the side reach is unobstructed or obstructed by an element that is an integral part of the stationary ICT and which is less than 255 mm (10 inches), at least one of each type of operable part shall be within a high side reach which is less than or equal to 1 220 mm (48 inches) above the floor of the access space.	Supports	Operable parts within 255 mm in depth are located below 1220 mm in height.
8.3.3.2 Unobstructed low side reach Where the side reach is unobstructed or obstructed by an element that is an integral part of the stationary ICT and which is less than 255 mm (10 inches), at least one of each type of operable part shall be within a low side reach which is greater than or equal to 380 mm (15 inches) above the floor of the access space.	Partially Supports	Some portions of the paper output basket and the stand lock are positioned close to the floor of the access space and may be difficult for some users to access.
8.3.3.3.1 Obstructed ($\leq$ 255 mm) side reach Where stationary ICT has an obstruction which is an integral part of the ICT, the height of the obstruction shall be less than 865 mm (34 inches). Where the depth of the obstruction is less than or equal to 255 mm (10 inches), the high side reach to at least one of each type of operable part shall be no higher than 1 220 mm (48 inches) above the floor of the access space.	Does not support	When replacing ink or adjusting screen settings, portions of the product structure obstruct side reach to the operable parts, and the height of the obstruction exceeds 865 mm.

8.3.3.3.2 Obstructed (≤ 610 mm) side reach Where stationary ICT has an obstruction which is an integral part of the ICT, the height of the obstruction shall be less than 865 mm (34 inches). Where the depth of the obstruction is greater than 255 mm (10 inches) with a maximum depth of 610 mm (24 inches), the high side reach to at least one of each type of operable part shall be no higher than 1 170 mm (46 inches) above the floor of the access space.	Does not support	Closing the top cover, replacing the ink tank, and operating the touch screen require reaching over an obstacle exceeding 865 mm in height. In addition, the open top cover and the ink tank are positioned above 1170 mm.
8.3.5 Visibility Where stationary ICT provides one or more display screens, at least one of each type of display screen shall be positioned such that the information on the screen is legible from a point located 1 015 mm (40 inches) above the centre of the floor of the operating area).	Does not support	The display is positioned 1015 mm above the floor and may be difficult to view due to its height and viewing angle.
8.3.6 Installation instructions Installation instructions shall be made available for all stationary ICT. These instructions shall give guidance on how to install the ICT in a manner that takes into account applicable requirements for accessibility of the built environment as they apply to the installation of the ICT. Where there are no such requirements the instructions should require that the dimensions of the installed ICT conform to clauses 8.3.2 to 8.3.5 of the present document.	Partially Supports	In addition to dimensional information provided by the sales company, this VPAT provides dimensional and operable-part information that may be used as a reference during installation.
8.4.1 Numeric keys Where provided, physical numeric keys arranged in a rectangular keypad layout shall have the number five key tactilely distinct from the other keys of the keypad.	Supports*	No mechanical numeric keys are provided.
8.4.2.1 Means of Operation of mechanical parts Where a control requires grasping, pinching, or twisting of the wrist to operate it, an accessible alternative means of operation that does not require these actions shall be provided. .	Partially Supports	Paper replacement requires pinching and gripping for some components, and no alternative method is provided.
8.4.2.2 Force of operation of mechanical parts Where a control requires a force greater than 22,2 N to operate it, an accessible alternative means of operation that requires a force less than 22,2 N shall be provided. .	Partially Supports	Replacing the ink tank or roll paper requires more than 22.2 N of force in some cases; however, no alternative method is provided.
8.4.3 Keys, tickets and fare cards Where ICT provides keys, tickets or fare cards, and their orientation is important for further use, they shall have an orientation that is tactilely discernible.	Supports*	No cards are used.
8.5 Tactile indication of speech mode Where ICT is designed for shared use and speech output is available, a tactile indication of the means to initiate the speech mode of operation shall be provided.	Supports*	Speech output is not provided by the product itself.

Clause 9: Web

Criteria	Conformance Level	Remarks and Explanations
9.1.1.1 through 9.4.1.3	See WCAG section.	

Clause 10: Non-web Documents

Criteria	Conformance Level	Remarks and Explanations
10.1.1.1 through 10.4.1.3	See WCAG section.	
10.5 Caption positioning Where ICT is a non-web document that contains synchronized media with captions, the captions should not obscure relevant information in the synchronized media.	Canon PRINT: Not applicable DOCUMENT: Supports*	Canon PRINT: Canon PRINT does not include any video content. DOCUMENT: Non-web document is not provided.
10.6 Audio description timing Where ICT is a non-web document that contains synchronized media with audio description, the audio description should not interfere with relevant audio information in the synchronized media.	Canon PRINT: Not applicable DOCUMENT: Supports*	Canon PRINT: Canon PRINT does not include any video content. DOCUMENT: Non-web document is not provided.

Clause 11: Software

Criteria	Conformance Level	Remarks and Explanations
11.1.1.1 through 11.4.1.3	See WCAG section.	
11.5.2.1 Platform accessibility service support for software that provides a user interface Platform software shall provide a set of documented platform services that enable software that provides a user interface running on the platform software to interoperate with assistive technology. Where a user interface concept corresponding to one of the clauses 11.5.2.5 to 11.5.2.17 is supported within the software environment, the platform software should support that requirement. For example, selection attributes from 11.5.2.14 (Modification of focus and selection attributes) may not exist in environments that do not allow selection, which is most commonly associated with copy and paste.	See information in 11.5.2.5 through 11.5.2.17	Canon PRINT: See information in 11.5.2.5 through 11.5.2.17
11.5.2.2 Platform accessibility service support for assistive technologies Platform software shall provide a set of documented platform accessibility services that enable assistive technology to interoperate with software that provides a user interface running on the platform software. Where a user interface concept corresponding to one of the clauses 11.5.2.5 to 11.5.2.17 is supported within the software environment, the platform software should support that requirement. For example, selection attributes from 11.5.2.14 (Modification of focus and selection attributes) may not exist in environments that do not allow selection, which is most commonly associated with copy and paste.	See information in 11.5.2.5 through 11.5.2.17	Canon PRINT: See information in 11.5.2.5 through 11.5.2.17
11.5.2.3 Use of accessibility services Where the software provides a user interface it shall use the applicable documented platform accessibility services. If the documented platform accessibility services do not allow the software to meet the applicable requirements of clauses 11.5.2.5 to 11.5.2.17, then software that provides a user interface shall use other documented services to interoperate with assistive technology.	PRINTER DRIVER: Partially Supports Canon PRINT: See information in 11.5.2.5 through 11.5.2.17	PRINTER DRIVER: The result of cited requirements 11.5.2.5-11.5.2.17 consists 1 'Does not Supports', other 8 Supports with some conditions, and 3 'Supports'. Canon PRINT: Canon PRINT meets the applicable requirements of clauses 11.5.2.5 to 11.5.2.17.
11.5.2.4 Assistive technology Where the ICT is assistive technology it shall use the documented platform accessibility services.	PRINTER DRIVER: Supports* Canon PRINT: Not applicable	PRINTER DRIVER: The product is not an assistive technology. Canon PRINT: Canon PRINT is not assistive technology.
11.5.2.5 Object information Where the software provides a user interface it shall, by using the services as described in clause 11.5.2.3, make the user interface elements' role, state(s), boundary, name, and description programmatically determinable by assistive technologies.	PRINTER DRIVER: Partially Supports Canon PRINT: Supports	PRINTER DRIVER: The roles, states, boundary, names, and description of UI objects in the printer driver can be recognized programmatically. However, there are some UI objects not able to change the setting. Canon PRINT: Function names, operation methods, and settings status can all be correctly read.
11.5.2.6 Row, column, and headers Where the software provides a user interface it shall, by using the services as described in clause 11.5.2.3, make the row and column of each cell in a data table, including headers of the row and column if present, programmatically determinable by assistive technologies.	PRINTER DRIVER: Does not Support Canon PRINT: Not applicable	PRINTER DRIVER: Header cell and job data cells below the header are not read as set, and these are read in each row. Therefore it is hard to understand the meaning. Canon PRINT: There are no tables in Canon PRINT.

11.5.2.7 Values Where the software provides a user interface, it shall, by using the services as described in clause 11.5.2.3, make the current value of a user interface element and any minimum or maximum values of the range, if the user interface element conveys information about a range of values, programmatically determinable by assistive technologies.	PRINTER DRIVER: Supports when combined with Compatible AT Canon PRINT: Supports	PRINTER DRIVER: The currently set value can be recognized programmatically for any UI object in the printer driver for which a value can be entered. However, for recognizing range of value, the use of assistive technology (e.g.JAWS) is needed. Canon PRINT: Setting ranges and current setting values can all be correctly read.
11.5.2.8 Label relationships Where the software provides a user interface it shall expose the relationship that a user interface element has as a label for another element, or of being labelled by another element, using the services as described in clause 11.5.2.3, so that this information is programmatically determinable by assistive technologies.	PRINTER DRIVER: Partially Supports Canon PRINT: Supports	PRINTER DRIVER: The labels associated with UI components in the printer driver can be recognized programmatically. However, for recognizing some labels, the use of assistive technology (e.g. JAWS) is needed. Canon PRINT: The Canon PRINT UI screen has a list structure such that the screen is read in the correct order starting from the top.
11.5.2.9 Parent-child relationships Where the software provides a user interface it shall, by using the services as described in clause 11.5.2.3, make the relationship between a user interface element and any parent or children elements programmatically determinable by assistive technologies.	PRINTER DRIVER: Supports Canon PRINT: Supports	PRINTER DRIVER: The labels associated with UI components in the printer driver can be recognized programmatically. Canon PRINT: The Canon PRINT UI screen has a list structure in which all hierarchical relationships are determinable.
11.5.2.10 Text Where the software provides a user interface it shall, by using the services as described in clause 11.5.2.3, make the text contents, text attributes, and the boundary of text rendered to the screen programmatically determinable by assistive technologies.	PRINTER DRIVER: Supports Canon PRINT: Supports	PRINTER DRIVER: In the printer driver, the attributes of UI objects for which text can be entered, as well as the boundary of text displayed on the screen, can be recognized programmatically. Canon PRINT: In Canon PRINT, the attributes of UI objects for which text can be entered, as well as the boundary of text displayed on the screen, can be recognized programmatically.
11.5.2.11 List of available actions Where the software provides a user interface it shall, by using the services as described in clause 11.5.2.3, make a list of available actions that can be executed on a user interface element, programmatically determinable by assistive technologies.	PRINTER DRIVER: Partially Supports Canon PRINT: Supports	PRINTER DRIVER: Operations that can be executed on a UI object in the printer driver can be recognized with the use of screen readers. However, for some of them, the use of assistive technology (e.g. JAWS) is needed for cursor movement. Canon PRINT: The Canon PRINT UI screen has a list structure in which all executable actions are determinable.
11.5.2.12 Execution of available actions Where permitted by security requirements, software that provides a user interface shall, by using the services as described in clause 11.5.2.3, allow the programmatic execution of the actions exposed according to clause 11.5.2.11 by assistive technologies.	PRINTER DRIVER: Partially Supports Canon PRINT: Supports	PRINTER DRIVER: Operations that can be executed on a UI object in the printer driver can be recognized with the use of screen readers. However, for some of them, the use of assistive technology (e.g. JAWS) is needed for cursor movement. Canon PRINT: The Canon PRINT UI screen has a list structure in which all executable actions are determinable.

11.5.2.13 Tracking of focus and selection attributes Where software provides a user interface it shall, by using the services as described in clause 11.5.2.3, make information and mechanisms necessary to track focus, text insertion point, and selection attributes of user interface elements programmatically determinable by assistive technologies.	PRINTER DRIVER: Partially Supports Canon PRINT: Supports	PRINTER DRIVER: Changes of focus, component attributes, and text insertion points can be recognized in the printer driver. However, for some of them, the use of assistive technology (e.g. JAWS) is needed for cursor movement. Canon PRINT: Changes of focus, component attributes, and text insertion points can be recognized and set programmatically by Canon PRINT.
11.5.2.14 Modification of focus and selection attributes Where permitted by security requirements, software that provides a user interface shall, by using the services as described in clause 11.5.2.3, allow assistive technologies to programmatically modify focus, text insertion point, and selection attributes of user interface elements where the user can modify these items.	PRINTER DRIVER: Partially Supports Canon PRINT: Supports	PRINTER DRIVER: Changes of focus, component attributes, and text insertion points can be recognized in the printer driver. However, for some of them, the use of assistive technology (e.g. JAWS) is needed for cursor movement. Canon PRINT: Changes of focus, component attributes, and text insertion points can be recognized and set programmatically by Canon PRINT.
11.5.2.15 Change notification Where software provides a user interface it shall, by using the services as described in clause 11.5.2.3, notify assistive technologies about changes in those programmatically determinable attributes of user interface elements that are referenced in requirements 11.5.2.5 to 11.5.2.11 and 11.5.2.13.	PRINTER DRIVER: Supports Canon PRINT: Supports	PRINTER DRIVER: When changes of UI components occur, the printer driver can notify it programmatically. Canon PRINT: Canon PRINT supports notification of changes to components when such changes occur.
11.5.2.16 Modifications of states and properties Where permitted by security requirements, software that provides a user interface shall, by using the services as described in clause 11.5.2.3, allow assistive technologies to programmatically modify states and properties of user interface elements, where the user can modify these items.	PRINTER DRIVER: Partially Supports Canon PRINT: Supports	PRINTER DRIVER: The roles, states, boundary, names, and description of UI objects in the printer driver can be recognized programmatically. However, there are some UI objects not able to change the setting. Canon PRINT: Function names, operation methods, and settings status can all be correctly read.
11.5.2.17 Modifications of values and text Where permitted by security requirements, software that provides a user interface shall, by using the services as described in clause 11.5.2.3, allow assistive technologies to modify values and text of user interface elements using the input methods of the platform, where a user can modify these items without the use of assistive technology.	PRINTER DRIVER: Supports Canon PRINT: Supports	PRINTER DRIVER: Texts and Values can be set by user are capable to be set programmatically through the program. Canon PRINT: Text can be changed programmatically for any UI object in Canon PRINT for which text can be entered.
11.6.1 User control of accessibility features Where software is a platform it shall provide sufficient modes of operation for user control over those platform accessibility features documented as intended for users.	PRINTER DRIVER: Supports* Canon PRINT: Not applicable	PRINTER DRIVER: The printer driver is not a platform. Canon PRINT: Canon PRINT is not a platform.
11.6.2 No disruption of accessibility features Where software provides a user interface it shall not disrupt those documented accessibility features that are defined in platform documentation except when requested to do so by the user during the operation of the software.	PRINTER DRIVER: Supports Canon PRINT: Partially Supports	PRINTER DRIVER: The printer driver can be used without disruption of the accessibility features of the platform (verified with the accessibility functionality of Windows 10). Canon PRINT: Most platform accessibility features are applied without disruption, but there is a small minority which cannot be applied.

11.7 User preferences Where software is not designed to be isolated from its platform, and provides a user interface, that user interface shall follow the values of the user preferences for platform settings for: units of measurement, colour, contrast, font type, font size, and focus cursor except where they are overridden by the user.	PRINTER DRIVER: Supports Canon PRINT: Partially Supports	PRINTER DRIVER: The printer driver can be used without disruption of the accessibility features of the platform (verified with the accessibility functionality of Windows 10). Canon PRINT: User preferences for color, font type, and focus cursor are applied. However, some settings for font size and contrast cannot be applied.
11.8.2 Accessible content creation Authoring tools shall enable and guide the production of content that conforms to clauses 9 (Web content) or 10 (Non-Web content) as applicable.	PRINTER DRIVER: Not applicable Canon PRINT: See information in WCAG section	
11.8.3 Preservation of accessibility information in transformations If the authoring tool provides restructuring transformations or re-coding transformations, then accessibility information shall be preserved in the output if equivalent mechanisms exist in the content technology of the output.	PRINTER DRIVER: Not applicable Canon PRINT: Not applicable	Canon PRINT: Canon PRINT is not an authoring tool.
11.8.4 Repair assistance If the accessibility checking functionality of an authoring tool can detect that content does not meet a requirement of clauses 9 (Web) or 10 (Non-web documents) as applicable, then the authoring tool shall provide repair suggestion(s).	PRINTER DRIVER: Not applicable Canon PRINT: Not applicable	Canon PRINT: Canon PRINT is not an authoring tool.
11.8.5 Templates When an authoring tool provides templates, at least one template that supports the creation of content that conforms to the requirements of clauses 9 (Web) or 10 (Non-web documents) as applicable shall be available and identified as such.	PRINTER DRIVER: Not applicable Canon PRINT: Not applicable	Canon PRINT: Canon PRINT is not an authoring tool.

Clause 12: Documentation and Support Services

Criteria	Conformance Level	Remarks and Explanations
12.1.1 Accessibility and compatibility features Product documentation provided with the ICT whether provided separately or integrated within the ICT shall list and explain how to use the accessibility and compatibility features of the ICT.	Supports	This VPAT lists and explains the features required by EN 301 549 requirements.
12.1.2 Accessible documentation Product documentation provided with the ICT shall be made available in at least one of the following electronic formats: a) a Web format that conforms to the requirements of clause 9, or b) a non-web format that conforms to the requirements of clause 10.	Supports	The WCAG, which is clause9, is applied to the documentation. See WCAG section for the results.
12.2.2 Information on accessibility and compatibility features ICT support services shall provide information on the accessibility and compatibility features that are mentioned in the product documentation.	Supports	Support services will provide information about functions related to accessibility by means according to user's requests.
12.2.3 Effective communication ICT support services shall accommodate the communication needs of individuals with disabilities either directly or through a referral point.	Supports	You can reach contact support from below URL. https://www.canon-europe.com/support/consumer_products/contact_support/ Please choose proper country. Phone number and e-mail address are described. If there is not proper country, please access below and contact each office in your country. https://www.canon-europe.com/contact_us/canon_europe_middle_east_and_africa_offices/
12.2.4 Accessible documentation Documentation provided by support services shall be made available in at least one of the following electronic formats: a) a Web format that conforms to clause 9, or b) a non-web format that conforms to clause 10.	Supports	The WCAG, which is clause9, is applied to the documentation. See WCAG section for the results.

WCAG Web Contents Accessibility Guidelines

WCAG Report (Level A & AA)

Criteria	Conformance Level	Remarks and Explanations
1.1.1 Non-text Content(A): All non-text content that is presented to the user has a text alternative that serves the equivalent purpose, except for the situations listed below.	HARDWARE: Does not Support PRINTER DRIVER: Partially Supports Remote UI: Partially Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: Some non-text content, such as footers on product screens, have no accompanying text. All information on the screen can not be audio-output by the unit. PRINTER DRIVER: The non-text content items in the UI of the printer driver are visual representations of various setting values, and provide text alternative for them. However, alternative means are necessary for some of them to give their information. Remote UI: The remaining ink level and some of the non-text content items (icons) have no text explanation. Canon PRINT: Images that convey important information have text that explains the purpose or meaning of the image. DOCUMENT: All non-text content that is presented to the user has a text alternative that serves the equivalent purpose.
1.2.1 Audio-only and Video-only (Prerecorded)(A): For prerecorded audio-only and prerecorded video-only media, the following are true, except when the audio or video is a media alternative for text and is clearly labeled as such: - Prerecorded Audio-only - Prerecorded Video-only	HARDWARE: Does not Support PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: Prerecorded audio content is not used. There are no audio alternatives for prerecorded video content. PRINTER DRIVER: Prerecorded audio-only and prerecorded video-only contents are not used. Remote UI: Prerecorded audio-only and prerecorded video-only contents are not used. Canon PRINT: Canon PRINT does not use any multimedia presentations. DOCUMENT: Information equal to prerecorded video is provided by using screen reader.
1.2.2 Captions (Prerecorded)(A): Captions are provided for all prerecorded audio content in synchronized media, except when the media is a media alternative for text and is clearly labeled as such.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Supports DOCUMENT: Not Applicable	HARDWARE: No video content is used. PRINTER DRIVER: Prerecorded audio content is not included in synchronized media. Remote UI: Prerecorded audio-only and prerecorded video-only contents are not used. Canon PRINT: Canon PRINT does not use any multimedia presentations. DOCUMENT: Captions are provided for the prerecorded audio contents, however the captions can not be read out.

1.2.3 Audio Description or Media Alternative (Prerecorded)(A): An alternative for time-based media or audio description of the prerecorded video content is provided for synchronized media, except when the media is a media alternative for text and is clearly labeled as such.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Supports DOCUMENT: Not Applicable	HARDWARE: Prerecorded video content with synchronized audio is not being used. PRINTER DRIVER: Prerecorded video content is not included in synchronized media. Remote UI: Prerecorded audio-only and prerecorded video-only contents are not used. Canon PRINT: Canon PRINT does not use any multimedia presentations. DOCUMENT: Audio description is not provided, however the contents can be read out with screen reader.
1.2.4 Captions (Live)(AA): Captions are provided for all live audio content in synchronized media.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Supports DOCUMENT: Supports*	HARDWARE: No audio content is used. PRINTER DRIVER: Live audio content is not included in synchronized media. Remote UI: Prerecorded audio-only and prerecorded video-only contents are not used. Canon PRINT: Canon PRINT does not use any multimedia presentations. DOCUMENT: Live audio is not provided.
1.2.5 Audio Description (Prerecorded)(AA): Audio description is provided for all prerecorded video content in synchronized media.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Supports DOCUMENT: Not Applicable	HARDWARE: Prerecorded video content with synchronized audio is not being used. PRINTER DRIVER: Prerecorded video content is not included in synchronized media. Remote UI: Prerecorded audio-only and prerecorded video-only contents are not used. Canon PRINT: Canon PRINT does not use any multimedia presentations. DOCUMENT: Audio description is not provided, however the contents can be read out with screen reader.

1.3.1 Info and Relationships(A): Information, structure, and relationships conveyed through presentation can be programmatically determined or are available in text.	HARDWARE: Does not Support PRINTER DRIVER: Partially Supports Remote UI: Partially Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: Speech output is not provided by the product itself. PRINTER DRIVER: Text is provided for structures that can be interpreted programmatically. However, for some of them, the use of assistive technology (e.g. JAWS) is needed for cursor movement. Remote UI: Some ink levels and some non-text content (icons) are not read or have no information. Users need to acknowledge that the items in lower hierarchies are read out directly after a series of upper hierarchies. (JAWS 2021) Canon PRINT: The Canon PRINT UI screen has a list structure such that the screen is read in top-to-bottom order. Text for this purpose is provided. DOCUMENT: Explanations are conveyed primarily via text.
1.3.2 Meaningful Sequence(A): When the sequence in which content is presented affects its meaning, a correct reading sequence can be programmatically determined.	HARDWARE: Does not Support PRINTER DRIVER: Partially Supports Remote UI: Partially Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: Speech output is not provided by the product itself. PRINTER DRIVER: In the printer driver, the order in which the UI content is read by screen readers matches the order in which it is presented, and information can be provided in the correct order. However, for some UI contents, the use of assistive technology (e.g.JAWS) is needed. Remote UI: Some ink level reports and some non-text content (icons) are not read. Users need to acknowledge that the items in lower hierarchies are read out directly after a series of upper hierarchies. Canon PRINT: The Canon PRINT UI screen has a list structure such that the screen is read in the correct order starting from the top. DOCUMENT: For cases where the order in which information is presented could affect its meaning, that information is presented in the same order. A part of contents can be recognized by using assistive technology (e.g.JAWS).
1.3.3 Sensory Characteristics(A): Instructions provided for understanding and operating content do not rely solely on sensory characteristics of components such as shape, color, size, visual location, orientation, or sound.	HARDWARE: Does not Support PRINTER DRIVER: Partially Supports Remote UI: Partially Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: Speech output is not provided by the product itself. PRINTER DRIVER: Printer Driver provides texts for understanding and operating contents in UI. Therefore, it does not rely solely on sensory characteristics. However, some non-text contents (icons) do not have texts. Remote UI: Some ink level reports and some non-text content (icons) are not read. Canon PRINT: All applicable areas of this application meet the requirements. DOCUMENT: There is no content that rely on sensory characteristics of components.

1.3.4 Orientation(AA):Content does not restrict its view and operation to a single display orientation, such as portrait or landscape, unless a specific display orientation is essential.	HARDWARE: Supports* PRINTER DRIVER: Supports Remote UI: Supports Canon PRINT: Partially Supports DOCUMENT: Supports	HARDWARE: The product is not a mobile equipment, and is to be stationed on a desk or other pedestals to work properly. It is essential that the display orientation is limited to the view angle. PRINTER DRIVER: Printer Driver does not restrict its view to a single display orientation. Remote UI: Remote UI does not restrict its view and operation to a single display orientation. Canon PRINT: Both landscape and portrait orientation are supported for tablet display, but only portrait orientation is supported for smartphone display. DOCUMENT: It does not restrict its view to a single display orientation.
1.3.5 Identify Input Purpose(AA):The purpose of each input field collecting information about the user can be programmatically determined when: The input field serves a purpose identified in the Input Purposes for User Interface Components section; and The content is implemented using technologies with support for identifying the expected meaning for form input data.	HARDWARE: Does not Support PRINTER DRIVER: Supports* Remote UI: Supports Canon PRINT: Supports DOCUMENT: Supports*	HARDWARE: Speech output is not provided by the product itself. PRINTER DRIVER: Printer Driver does not provide any input field collecting user information. Remote UI: The purpose of each input field collecting information about the user is obvious. Canon PRINT: Entry fields for user information in Canon PRINT have labels or additional guidance messages that allow the purpose of each field to be understood. DOCUMENT: It does not provide any input field collecting user information.
1.4.1 Use of Color(A): Color is not used as the only visual means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	HARDWARE: Supports PRINTER DRIVER: Supports Remote UI: Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: Text is attached to elements that have meaning for the color. PRINTER DRIVER: Printer Driver does not use of color for the only means of conveying information. Remote UI: Remote UI does not use color-coding as the only means of conveying information. Canon PRINT: Canon PRINT does not use color-coding as the only means of conveying information. It has text information with color-coding. DOCUMENT: Color on display and on operable parts are not used as the only visual means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.

1.4.2 Audio Control(A): If any audio on a Web page plays automatically for more than 3 seconds, either a mechanism is available to pause or stop the audio, or a mechanism is available to control audio volume independently from the overall system volume level.	HARDWARE: Supports PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Supports DOCUMENT: Supports*	HARDWARE: The product has no audio content. PRINTER DRIVER: Printer Driver have no audio that plays automatically more than 3 seconds. Remote UI: The remote UI for this product does not play any audio. Canon PRINT: Canon PRINT does not play any audio. DOCUMENT: Audio that plays automatically is not provided.
1.4.3 Contrast (Minimum)(AA): The visual presentation of text and images of text has a contrast ratio of at least 4.5:1, except for the following:	HARDWARE: Supports PRINTER DRIVER: Supports Remote UI: Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: The contrast is satisfying. PRINTER DRIVER: Displayed text meets contrast requirements/standards. Remote UI: Displayed text meets contrast requirements/standards. Canon PRINT: All applicable areas of this application meet the requirements. DOCUMENT: Displayed text meets contrast requirements/standards.
1.4.4 Resize text(AA): Except for captions and images of text, text can be resized without assistive technology up to 200 percent without loss of content or functionality.	HARDWARE: Does not Support PRINTER DRIVER: Supports Remote UI: Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: The text on display cannot be enlarged. PRINTER DRIVER: The UI text in the printer driver can be resized using functionality provided by the OS without loss of printer driver functionality, and there is no functionality in the printer driver that impedes there sizing of text. Remote UI: Users may resize text while operating the device via the remote UI on a standard PC browser without any loss of functionality. Canon PRINT: Text can be resized to 200% or more using the OS functionality without loss of content or functionality in the text. DOCUMENT: Text can be resized without assistive technology up to 200 percent without loss of content or functionality.

1.4.5 Images of Text(AA): If the technologies being used can achieve the visual presentation, text is used to convey information rather than images of text.	HARDWARE: Does not Support PRINTER DRIVER: Supports Remote UI: Supports* Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: The visual appearance of text on display cannot be changed. PRINTER DRIVER: The printer driver uses text to convey information and does not have any images of text. Remote UI: The remote UI does not use any images of text. Canon PRINT: Canon PRINT does not use any images of text. DOCUMENT: Text format, not images of text, is used for the text.
1.4.10 Reflow(AA):Content can be presented without loss of information or functionality, and without requiring scrolling in two dimensions for: •Vertical scrolling content at a width equivalent to 320 CSS pixels; •Horizontal scrolling content at a height equivalent to 256 CSS pixels.	HARDWARE: Supports PRINTER DRIVER: Supports Remote UI: Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: Scrolling in two directions is not required. PRINTER DRIVER: The Printer Driver's windows are small and static, which basically does not require scrolling. In case of scrolling, the influence stays minute. Remote UI: The remote UI does not use two-way scrolling. Canon PRINT: Scrolling in two dimensions on the same screen does not occur in Canon PRINT. DOCUMENT: Content can be presented vertical scrolling at a width equivalent to 320CSS pixels and adjusted for the screen without loss of information or functionality.
1.4.11 Non-text Contrast(AA):The visual presentation of the following have a contrast ratio of at least 3:1 against adjacent color(s): •User Interface Components: Visual information required to identify user interface components and states, except for inactive components or where the appearance of the component is determined by the user agent and not modified by the author; •Graphical Objects: Parts of graphics required to understand the content, except when a particular presentation of graphics is essential to the information being conveyed.	HARDWARE: Supports PRINTER DRIVER: Supports Remote UI: Supports Canon PRINT: Partially Supports DOCUMENT: Supports	HARDWARE: The contrast is satisfying. PRINTER DRIVER: The visual presentation of user interface components and graphical objects have a contrast ratio of at least 3:1 against adjacent color(s) Remote UI: The visual User Interface Components and Graphical Objects meet a contrast ratio standard against adjacent colors. Canon PRINT: There are some buttons for which the contrast between the border and background is less than 3:1. DOCUMENT: The visual presentation of User Interface Components and Graphical Objects have a contrast ratio of at least 3:1 against adjacent color(s)

1.4.12 Text Spacing(AA):In content implemented using markup languages that support the following text style properties, no loss of content or functionality occurs by setting all of the following and by changing no other style property: Line height (line spacing) to at least 1.5 times the font size; Spacing following paragraphs to at least 2 times the font size; Letter spacing (tracking) to at least 0.12 times the font size; Word spacing to at least 0.16 times the font size.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports Canon PRINT: Supports DOCUMENT: Supports*	HARDWARE: Markup Language is not used. PRINTER DRIVER: Printer Driver does not use markup languages. Therefore, it does not change the following setting: Line height (line spacing); Spacing following paragraphs; Letter spacing (tracking); Word spacing. Remote UI: Remote UI uses markup language, and possible to apply style sheet. Canon PRINT: Markup language is not used in Canon PRINT. DOCUMENT: It does not provide the means to change letter spacing (tracking).
1.4.13 Content on Hover or Focus(AA): Where receiving and then removing pointer hover or keyboard focus triggers additional content to become visible and then hidden, the following are true: Dismissible: A mechanism is available to dismiss the additional content without moving pointer hover or keyboard focus, unless the additional content communicates an input error or does not obscure or replace other content; Hoverable: If pointer hover can trigger the additional content, then the pointer can be moved over the additional content without the additional content disappearing; Persistent : The additional content remains visible until the hover or focus trigger is removed, the user dismisses it, or its information is no longer valid.	HARDWARE: Supports* PRINTER DRIVER: Partially Supports Remote UI: Supports* Canon PRINT: Supports DOCUMENT: Supports*	HARDWARE: Additional content is not displayed by hover or focus. PRINTER DRIVER: It does not provide to set the additional content to become hidden in Printer Driver, but provide to keep visible. Remote UI: Remote UI have no components that become visible additional content. Canon PRINT: As a UI for mobile devices, there are no elements which are triggered upon receiving pointer hover or keyboard focus. DOCUMENT: It has no components that became visible additional content.
2.1.1 Keyboard(A): All functionality of the content is operable through a keyboard interface without requiring specific timings for individual keystrokes, except where the underlying function requires input that depends on the path of the user's movement and not just the endpoints.	HARDWARE: Does not Support PRINTER DRIVER: Supports Remote UI: Partially Supports Canon PRINT: iOS : Supports Android : Partially Supports DOCUMENT: Supports	HARDWARE: The firmware must be operated using the touch panel of the product itself. Keyboard IF operation is not available. Speech output is not provided by the product itself. PRINTER DRIVER: The printer driver runs on systems with keyboards, and all functionality can be operated solely with the keyboard. Remote UI: In some function, operation through a keyboard are not provided. Canon PRINT: Android: there are some screens which cannot receive keyboard focus. DOCUMENT: All functionality are operable with keyboard interface and does not depend on operation timing.

2.1.2 No Keyboard Trap(A): If keyboard focus can be moved to a component of the page using a keyboard interface, then focus can be moved away from that component using only a keyboard interface, and, if it requires more than unmodified arrow or tab keys or other standard exit methods, the user is advised of the method for moving focus away.	HARDWARE: Supports* PRINTER DRIVER: Supports Remote UI: Supports Canon PRINT: iOS : Supports Android : Partially Supports DOCUMENT: Supports	HARDWARE: Since the screen is operated by a touch panel, there is no keyboard-operated focus. PRINTER DRIVER: Focus can be moved away from the component using only a keyboard interface. Remote UI: The focus which moves by using keyboard moves without trapped at any particular component. Canon PRINT: Android: there are some screens which contain a keyboard trap. DOCUMENT: Keyboard focus can be moved using a keyboard interface without keyboard trap in a specific component.
2.1.4 Character Key Shortcuts(A):If a keyboard shortcut is implemented in content using only letter (including upper- and lower-case letters), punctuation, number, or symbol characters, then at least one of the following is true: Turn off: A mechanism is available to turn the shortcut off; Remap: A mechanism is available to remap the shortcut to use one or more non-printable keyboard characters (e.g. Ctrl, Alt, etc); Active only on focus: The keyboard shortcut for a user interface component is only active when that component has focus.	HARDWARE: Supports* PRINTER DRIVER: Does not Support Remote UI: Supports* Canon PRINT: Supports DOCUMENT: Supports*	HARDWARE: There is no keyboard shortcuts. PRINTER DRIVER: Keyboard shortcut is implemented in printer driver content.However, it is not available to turn the shortcut off, and to remap the shortcut. Remote UI: There is no component that implements a keyboard shortcut in Remote UI. Canon PRINT: Canon PRINT does not utilize keyboard shortcuts using character keys. DOCUMENT: There is no component that implements a keyboard shortcut.
2.2.1 Timing Adjustable(A): For each time limit that is set by the content, at least one of the following is true: • Turn off: The user is allowed to turn off the time limit before encountering it; or • Adjust: The user is allowed to adjust the time limit before encountering it over a wide range that is at least ten times the length of the default setting; or • Extend: The user is warned before time expires and given at least 20 seconds to extend the time limit with a simple action (for example, "press the space bar"), and the user is allowed to extend the time limit at least ten times; or • Real-time Exception: The time limit is a required part of a real-time event (for example, an auction), and no alternative to the time limit is possible; or • Essential Exception: The time limit is essential and extending it would invalidate the activity; or • 20 Hour Exception: The time limit is longer than 20 hours.	HARDWARE: Supports PRINTER DRIVER: Supports Remote UI: Supports* Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: There is a screen lock by timeout in the administrator password settings function. The screen lock function can be disabled. When the media type selection method is set to "Auto (Auto feed)," the operation will be executed in some places if no operation is performed for 5 seconds. The media type selection method can be changed to "manual". PRINTER DRIVER: There are no time limits applied. Remote UI: There are no time limits applied. Canon PRINT: There may be time limits set by the operating system, but there are no time limits set by the application. DOCUMENT: It has no contents that set time limit.

2.2.2 Pause, Stop, Hide(A): For moving, blinking, scrolling, or auto-updating information, all of the following are true: •Moving, blinking, scrolling: For any moving, blinking or scrolling information that (1) starts automatically, (2) lasts more than five seconds, and (3) is presented in parallel with other content, there is a mechanism for the user to pause, stop, or hide it unless the movement, blinking, or scrolling is part of an activity where it is essential; and •Auto-updating: For any auto-updating information that (1) starts automatically and (2) is presented in parallel with other content, there is a mechanism for the user to pause, stop, or hide it or to control the frequency of the update unless the auto-updating is part of an activity where it is essential.	HARDWARE: Supports PRINTER DRIVER: Supports Remote UI: Supports* Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: Although there is a progress indicator, this requirement does not apply because the absence of this indicator could lead to the misunderstanding that the operation has stopped. PRINTER DRIVER: There are no UI components in the printer driver that automatically move or update. Remote UI: The remote UI does not have any components which auto-update. Canon PRINT: Canon PRINT does not have any components which auto-update. DOCUMENT: Content with automatic movement has a mechanism to pause.
2.3.1 Three Flashes or Below Threshold(A): Web pages do not contain anything that flashes more than three times in any one second period, or the flash is below the general flash and red flash thresholds.	HARDWARE: Supports PRINTER DRIVER: Supports Remote UI: Supports* Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: The display of the product itself does not have flashing. The LED, near the display, has no flashing which may affect users. PRINTER DRIVER: There are no UI components in the printer driver that flash. Remote UI: There are no Blinking or flashing objects applied in Remote UI. Canon PRINT: There are no UI components in Canon PRINT that flash. DOCUMENT: There are no user interface components that flash.
2.4.1 Bypass Blocks(A): A mechanism is available to bypass blocks of content that are repeated on multiple Web pages.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Does not Support Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: This requirement is not applied to firmwares in accordance with EN 301 549. PRINTER DRIVER: The product does not contain a web page. Remote UI: A mechanism to bypass blocks of tab menu that are repeated is not provided in Remote UI. Canon PRINT: Canon PRINT does not contain blocks of content that are repeated on multiple pages. DOCUMENT: It is available to bypass blocks of content that are repeated on multiple Web pages.

2.4.2 Page Titled(A): Web pages have titles that describe topic or purpose.	HARDWARE: Supports* PRINTER DRIVER: Partially Supports Remote UI: Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: This requirement is not applied to firmwares in accordance with EN 301 549. PRINTER DRIVER: Each screen of the printer driver has a title that indicates the purpose of the screen. However, for the reading of the title, the use of assistive technology (e.g. JAWS) is needed. Remote UI: Each remote UI page displays a title or tab that explains the purpose of the screen on which it is displayed. Canon PRINT: Each Canon PRINT page displays a title that explains the purpose of the screen on which it is displayed. DOCUMENT: All pages have titles that describe topic.
2.4.3 Focus Order(A): If a Web page can be navigated sequentially and the navigation sequences affect meaning or operation, focusable components receive focus in an order that preserves meaning and operability.	HARDWARE: Supports* PRINTER DRIVER: Supports Remote UI: Partially Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: Since the screen is operated by a touch panel, there is no keyboard-operated focus. PRINTER DRIVER: The order of focus preserves meaning and operability. Remote UI: Users need to acknowledge that the items in lower hierarchies are read out directly after a series of upper hierarchies. Canon PRINT: The Canon PRINT UI screen has a list structure such that focus moves in a top-to-bottom order. DOCUMENT: Focusable components receive focus in an order that preserves meaning and operability.
2.4.4 Link Purpose (In Context)(A): The purpose of each link can be determined from the link text alone or from the link text together with its programmatically determined link context, except where the purpose of the link would be ambiguous to users in general.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: No link is used. PRINTER DRIVER: The product does not contain any link. Remote UI: The purpose of each link in the remote UI can be determined from the link text. Canon PRINT: The purpose of each link in Canon PRINT can be determined from the link text. DOCUMENT: Each link can be easily understood the purpose of it.

2.4.5 Multiple Ways(AA): More than one way is available to locate a Web page within a set of Web pages except where the Web Page is the result of, or a step in, a process.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Does not Support Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: This requirement is not applied to firmwares in accordance with EN 301 549. PRINTER DRIVER: The product does not contain a web page. Remote UI: When using the remote UI, it is not possible to reach a page without going through the required pages in the required order. Canon PRINT: Canon PRINT is not a Web page. DOCUMENT: "Contents" and "Search" are provided for available to locate a Web page.
2.4.6 Headings and Labels(AA): Headings and labels describe topic or purpose.	HARDWARE: Supports PRINTER DRIVER: Supports Remote UI: Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: The headings convey the intentions. PRINTER DRIVER: Headings and Labels describe the purpose. Remote UI: Each label and heading displayed in the remote UI describes purpose. Canon PRINT: Each label and heading displayed in Canon PRINT describes purpose. DOCUMENT: All headings and labels describe topic.
2.4.7 Focus Visible(AA): Any keyboard operable user interface has a mode of operation where the keyboard focus indicator is visible.	HARDWARE: Supports* PRINTER DRIVER: Supports Remote UI: Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: Since the screen is operated by a touch panel, there is no keyboard-operated focus. PRINTER DRIVER: The keyboard focus can be recognized visually in the keyboard operable user interface. Remote UI: The remote UI uses assistive technology (For example, JAWS) to allow the keyboard to recognize focus. Canon PRINT: All applicable areas of this application meet the requirements. DOCUMENT: The keyboard focus can be recognized visually in the keyboard operable user interface.
2.4.11 Focus Not Obscured (AA): When a user interface component receives keyboard focus, the component is not entirely hidden due to author-created content.	HARDWARE: Supports* PRINTER DRIVER: Supports Remote UI: Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: Focus movement is not supported. PRINTER DRIVER: The UI element that receives focus is not obscured. Remote UI: Small pop-ups don't hide much of the main screen. Canon PRINT: All applicable areas of this application meet the requirements. DOCUMENT: The keyboard focus does not become obscured by other content in the keyboard operable user interface.

2.5.1 Pointer Gestures(A):All functionality that uses multipoint or path-based gestures for operation can be operated with a single pointer without a path-based gesture, unless a multipoint or path-based gesture is essential.	HARDWARE: Supports PRINTER DRIVER: Supports Remote UI: Supports* Canon PRINT: Partially Supports DOCUMENT: Supports	HARDWARE: The display of the product does not require multipoint or path-based gestures for operation. Swiping is available, but you can also use a single pointer. PRINTER DRIVER: Functionality that uses path-based gestures for operation can be operated with a single pointer. Remote UI: No function that uses multipoint or path-based gestures for operation in Remote UI. Canon PRINT: The preview screen can only be enlarged/reduced using a pinch operation requiring two fingers. DOCUMENT: All functionality that uses multipoint gestures for operation can be operated with a single pointer.
2.5.2 Pointer Cancellation(A):For functionality that can be operated using a single pointer, at least one of the following is true: No Down-Event: The down-event of the pointer is not used to execute any part of the function; Abort or Undo: Completion of the function is on the up-event, and a mechanism is available to abort the function before completion or to undo the function after completion; Up Reversal: The up-event reverses any outcome of the preceding down-event; Essential: Completing the function on the down-event is essential.	HARDWARE: Supports PRINTER DRIVER: Supports Remote UI: Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: Scrollbars work with down events, but there are other workarounds and operation with down events is not essential. PRINTER DRIVER: For functionality that can be operated using a single pointer, it is easily available to abort or undo the function. Remote UI: The scrollbar operates in a down event, but there are other workarounds and it is not necessary to operate in a down event. Canon PRINT: All applicable areas of this application meet the requirements. DOCUMENT: Pointer Cancellation is available. User can abort the function before completion or to undo the function after completion.
2.5.3 Label in Name(A):For user interface components with labels that include text or images of text, the name contains the text that is presented visually.	HARDWARE: Does not Support PRINTER DRIVER: Supports Remote UI: Partially Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: Speech output is not provided by the product itself. The contents of display is not programmatically interpretable. PRINTER DRIVER: For user interface components with labels, the name contains the text that is presented visually. Remote UI: For user interface components with labels, the name contains the text that is presented visually. In some contents, the item name of the check box is read out one step apart. Canon PRINT: All applicable areas of this application meet the requirements. DOCUMENT: For user interface components with labels, the name contains the text that is presented visually.

2.5.4 Motion Actuation(A):Functionality that can be operated by device motion or user motion can also be operated by user interface components and responding to the motion can be disabled to prevent accidental actuation, except when: Supported Interface: The motion is used to operate functionality through an accessibility supported interface; Essential: The motion is essential for the function and doing so would invalidate the activity.	HARDWARE: Supports PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Supports DOCUMENT: Supports*	HARDWARE: There are no functions that can be operated by the device motion or user motion. PRINTER DRIVER: There is no function that can be operated by device motion or user motion in the printer driver. Remote UI: No function that can be operated by device motion or user motion is in Remote UI. Canon PRINT: There are no functions that are operated by shaking or moving the device. DOCUMENT: No function that can be operated by device motion or user motion.
2.5.7 Dragging Movements (AA): All functionality that uses a dragging movement for operation can be achieved by a single pointer without dragging, unless dragging is essential or the functionality is determined by the user agent and not modified by the author.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports* Canon PRINT: Partially Supports DOCUMENT: Supports*	HARDWARE: There are no multipoint operations or operations requiring trajectories. PRINTER DRIVER: This product does not require dragging. Remote UI: There are no multipoint operations or operations that require trajectories. Canon PRINT: The preview screen can only be enlarged/reduced using a pinch operation requiring two fingers. DOCUMENT: There are no user interface components that require dragging operations.
2.5.8 Target Size (AA): The size of the target for pointer inputs is at least 24 by 24 CSS pixels, except where: - Spacing: Undersized targets (those less than 24 by 24 CSS pixels) are positioned so that if a 24 CSS pixel diameter circle is centered on the bounding box of each, the circles do not intersect another target or the circle for another undersized target; - Equivalent: The function can be achieved through a different control on the same page that meets this criterion; - Inline: The target is in a sentence or its size is otherwise constrained by the line-height of non-target text; - User agent control: The size of the target is determined by the user agent and is not modified by the author; - Essential: A particular presentation of the target is essential or is legally required for the information being conveyed.	HARDWARE: Supports PRINTER DRIVER: Partially Supports Remote UI: Partially Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: The button and wrist pitch are larger than the reference value. PRINTER DRIVER: The target size for pointer input meets the requirements except for some controls. The size of the spin box and some list boxes is less than the requirement, but can be manipulated by up and down key operations and direct input as an alternative. Remote UI: Some sizes, such as check boxes, do not meet the standards, so they are partially supported. Canon PRINT: The theoretical physical size of 24 by 24 CSS pixels is 6.24 by 6.24 mm. However, when calculating from the actual screen size and resolution, the size is about 1.3 by 1.3 mm, and Canon PRINT has a target size larger than this. DOCUMENT: User interface components that require pointer or touch input are sufficiently sized for activation.

3.1.1 Language of Page(A): The default human language of each Web page can be programmatically determined.	HARDWARE: Does not Support PRINTER DRIVER: Supports Remote UI: Partially Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: Speech output is not provided by the product itself. The contents of display is not programmatically interpretable. PRINTER DRIVER: The default human languages are programmatically determined. Remote UI: The language used by RemoteUI is recognized by assistive technology. In some contents, the item name of the check box is read out one step apart. Canon PRINT: The language of the screen reader matches the language of the text. DOCUMENT: Human language can be recognized by using assistive technology.
3.1.2 Language of Parts(AA): The human language of each passage or phrase in the content can be programmatically determined except for proper names, technical terms, words of indeterminate language, and words or phrases that have become part of the vernacular of the immediately surrounding text.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Partially Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: This requirement is not applied to firmwares in accordance with EN 301 549. PRINTER DRIVER: There is no case in printer driver. Remote UI: The language used by RemoteUI is recognized by assistive technology. In some contents, the item name of the check box is read out one step apart. Canon PRINT: The text content does not include partial usage of other languages. DOCUMENT: Human language can be recognized by using assistive technology.
3.2.1 On Focus(A): When any user interface component receives focus, it does not initiate a change of context.	HARDWARE: Supports* PRINTER DRIVER: Supports Remote UI: Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: Since the screen is operated by a touch panel, there is no keyboard-operated focus. PRINTER DRIVER: There are no UI components in the printer driver that change context upon receiving focus. Remote UI: There is no component that initiates a change of context when receives focus in Remote UI. Canon PRINT: There are no components in Canon PRINT that initiate a change of context upon receiving focus. DOCUMENT: It has no component that initiates a change of context, when use interface receives focus.

3.2.2 On Input(A): Changing the setting of any user interface component does not automatically cause a change of context unless the user has been advised of the behavior before using the component. .	HARDWARE: Supports PRINTER DRIVER: Supports Remote UI: Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: The screen is touch-panelized, and the items do not cause serious unpredictable change of context, automatically. PRINTER DRIVER: There are no circumstances in which changing the settings in the printer driver result in other settings being changed. Remote UI: Some buttons or radio button clicks display additional settings, but additional settings are predictable. Canon PRINT: There are no operations in Canon PRINT that cause an unpredictable change of context. DOCUMENT: Changing the setting of any user interface component does not cause a change of context.
3.2.3 Consistent Navigation(AA): Navigational mechanisms that are repeated on multiple Web pages within a set of Web pages occur in the same relative order each time they are repeated, unless a change is initiated by the user.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: This requirement is not applied to firmwares in accordance with EN 301 549. PRINTER DRIVER: The product does not contain a web page. Remote UI: Navigational mechanisms that are repeated throughout the Remote UI occur in the same order each time they are repeated. Canon PRINT: Navigational mechanisms that are repeated throughout Canon PRINT occur in the same order each time they are repeated. DOCUMENT: Navigational mechanisms that are repeated on occur in the same relative order each time they are repeated.
3.2.4 Consistent Identification(AA): Components that have the same functionality within a set of Web pages are identified consistently.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: This requirement is not applied to firmwares in accordance with EN 301 549. PRINTER DRIVER: The product does not contain a web page. Remote UI: The same terminology is used for the naming/labeling of components within the Remote UI which have the same functionality. Canon PRINT: The same terminology is used for the naming/labeling of components within Canon PRINT which have the same functionality. DOCUMENT: Components that have the same functionality are identified consistently.

3.2.6 Consistent Help (A): If a Web page contains any of the following help mechanisms, and those mechanisms are repeated on multiple Web pages within a set of Web pages, they occur in the same order relative to other page content, unless a change is initiated by the user: - Human contact details; - Human contact mechanism; - Self-help option; - A fully automated contact mechanism.	HARDWARE: Supports* PRINTER DRIVER: Supports Remote UI: Supports* Canon PRINT: Supports DOCUMENT: Not Applicable	HARDWARE: Help is not repeated on multiple pages. PRINTER DRIVER: Meet the requirements for consistent help. Remote UI: There is no help display. Canon PRINT: Canon PRINT does not have any help mechanisms. DOCUMENT: There are no user interfaces that provide help content across multiple instruction screens.
3.3.1 Error Identification(A): If an input error is automatically detected, the item that is in error is identified and the error is described to the user in text.	HARDWARE: Does not Support PRINTER DRIVER: Supports Remote UI: Partially Supports Canon PRINT: Supports DOCUMENT: Supports*	HARDWARE: Speech output is not provided by the product itself. The contents of display is not programmatically interpretable. PRINTER DRIVER: In the printer driver, when errors are occurred, the error can be recognized programmatically and display the error content. Remote UI: If an input error is automatically detected, the item that is in error can be identified. However, it can not be identified by reading. Canon PRINT: In Canon PRINT, when errors are displayed, the display of the error can be recognized programmatically and the error is displayed using an item name together with the error content. DOCUMENT: There is no component that an input error occurs.
3.3.2 Labels or Instructions(A): Labels or instructions are provided when content requires user input.	HARDWARE: Supports PRINTER DRIVER: Supports Remote UI: Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: Visual label is provided for user inputs on the display of the product itself. PRINTER DRIVER: All entry fields in the user interface of the printer driver are labeled. Remote UI: Any content in the remote UI (such as text boxes), which require a user's input are appropriately labeled. Canon PRINT: Any content in Canon PRINT (such as text boxes) which require a user's input are appropriately labeled. DOCUMENT: All content requires user input is provided labels or instructions.

3.3.3 Error Suggestion(AA): If an input error is automatically detected and suggestions for correction are known, then the suggestions are provided to the user, unless it would jeopardize the security or purpose of the content.	HARDWARE: Supports PRINTER DRIVER: Partially Supports Remote UI: Does not Support Canon PRINT: Supports DOCUMENT: Supports*	HARDWARE: On the product screen, detection is performed for input errors and a notice to that effect is displayed. PRINTER DRIVER: Messages with instructions for correcting errors are displayed in the UI of the printer driver for all locations where errors can occur. However, for the reading of the range of value, the use of assistive technology (e.g. JAWS) is needed. Remote UI: Suggestions for the correction of errors are not offered in Remote UI. Canon PRINT: Messages with instructions for correcting errors are displayed in the UI of Canon PRINT for all locations where errors can occur. DOCUMENT: There is no component that an input error occurs.
3.3.4 Error Prevention (Legal, Financial, Data)(AA): For Web pages that cause legal commitments or financial transactions for the user to occur, that modify or delete user-controllable data in data storage systems, or that submit user test responses, at least one of the following is true: 1. Reversible: Submissions are reversible. 2. Checked: Data entered by the user is checked for input errors and the user is provided an opportunity to correct them. 3. Confirmed: A mechanism is available for reviewing, confirming, and correcting information before finalizing the submission.	HARDWARE: Supports PRINTER DRIVER: Supports* Remote UI: Supports Canon PRINT: Supports DOCUMENT: Supports*	HARDWARE: On the device screen, there is a web service license on arrival and a choice to consent to the license in the Web service setup. It can also be undone in subsequent operations. PRINTER DRIVER: There is no case in printer driver.. Remote UI: In the Cloud Printing Center setup, there is an option to accept the license, and user can undo it later. Canon PRINT: Canon Print does not have functions that cause legal commitments or financial transactions for the user to occur, or that modify or delete user-controllable data in data storage systems. DOCUMENT: No applicable function.
3.3.7 Redundant Entry (A): Information previously entered by or provided to the user that is required to be entered again in the same process is either: - auto-populated, or - available for the user to select. Except when: re-entering the information is essential, the information is required to ensure the security of the content, or previously entered information is no longer valid.	HARDWARE: Supports* PRINTER DRIVER: Supports Remote UI: Supports* Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: Nothing to re-enter in the same process. PRINTER DRIVER: The information previously entered by the user is retained and does not need to be reentered. Remote UI: Nothing to re-enter in the same process. Canon PRINT: Canon PRINT does not have any information that is required to be entered again in the same process. DOCUMENT: For any required input, users can proceed by selecting from available options even if re-entry would otherwise be needed.

3.3.8 Accessible Authentication (AA): A cognitive function test (such as remembering a password or solving a puzzle) is not required for any step in an authentication process unless that step provides at least one of the following: - Alternative: Another authentication method that does not rely on a cognitive function test. - Mechanism: A mechanism is available to assist the user in completing the cognitive function test. - Object Recognition: The cognitive function test is to recognize objects. - Personal Content: The cognitive function test is to identify non-text content the user provided to the Web site.	HARDWARE: Supports* PRINTER DRIVER: Supports Remote UI: Supports* Canon PRINT: Supports DOCUMENT: Supports*	HARDWARE: Identification other than text content is not used for authentication input. PRINTER DRIVER: Passwords can be copied and pasted without being memorized, guessed from diagrams, or requiring any other authentication process. Remote UI: Identification other than non-text content is not used for authentication input Canon PRINT: Canon PRINT does not use any authentication processes other than identifying non-text content. DOCUMENT: There are no user interfaces that provide authentication.
4.1.1 Parsing(A): In content implemented using markup languages, elements have complete start and end tags, elements are nested according to their specifications, elements do not contain duplicate attributes, and any IDs are unique, except where the specifications allow these features. * 4.1.1 has been deprecated in WCAG 2.2. The criteria are based on references to WCAG 2.0 or 2.1.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: This requirement is not applied to firmwares in accordance with EN 301 549. PRINTER DRIVER: No part of the printer driver is implemented using markup languages. Remote UI: The HTML used in the remote UI adheres to the appropriate standards. Canon PRINT: No part of Canon PRINT is implemented using markup languages. DOCUMENT: Markup languages used are nested according to their specifications.
4.1.2 Name, Role, Value(A): For all user interface components (including but not limited to: form elements, links and components generated by scripts), the name and role can be programmatically determined; states, properties, and values that can be set by the user can be programmatically set; and notification of changes to these items is available to user agents, including assistive technologies.	HARDWARE: Supports* PRINTER DRIVER: Supports Remote UI: Partially Supports Canon PRINT: Supports DOCUMENT: Supports	HARDWARE: This requirement is not applied to firmwares in accordance with EN 301 549. PRINTER DRIVER: In the printer driver, names and roles of UI components can be recognized and configured programmatically, and notification of changes can be made available. Remote UI: The interface elements used by RemoteUI are recognizable by assistive technology. In some contents, the item name of the check box is read out one step apart. Canon PRINT: All applicable areas of Canon PRINT meet the requirements. DOCUMENT: HTML used adheres to the appropriate standards.

4.1.3 Status Messages(AA):In content implemented using markup languages, status messages can be programmatically determined through role or properties such that they can be presented to the user by assistive technologies without receiving focus.	HARDWARE: Supports* PRINTER DRIVER: Supports* Remote UI: Does not Support Canon PRINT: Supports DOCUMENT: Supports*	HARDWARE: This requirement is not applied to firmwares in accordance with EN 301 549. PRINTER DRIVER: No part of the printer driver is implemented using markup languages. Remote UI: The status message in Remote UI can be confirmed with moving focus on the status message. Canon PRINT: Markup language is not used in Canon PRINT. DOCUMENT: It has no content to display status messages.
--	--	--

Chapter 5: Functional Performance Statements

Criteria	Conformance Level	Remarks and Explanations
5.1.2 Blindness	Partially Supports	HARDWARE: The product primarily uses a touchscreen-based visual interface and does not provide speech output, such as voice guidance or audio access to screen information. Status information and indicator lamps are primarily visual, and tactile access to controls and status information is limited. Some functions can be accessed using Canon PRINT with VoiceOver or TalkBack on a mobile device or through Remote UI with a screen reader on a PC. However, certain non-text content, error information, and accessibility-related settings may not be fully accessible without vision. Remote UI: Remote UI is generally usable with a screen reader on a PC. However, some ink-level information and non-text content lack appropriate text alternatives or are not announced correctly. On some screens, the reading order and relationships between items are not fully conveyed. Some error information is not available through speech output alone, repeated navigation blocks cannot be bypassed, and certain functions are not fully operable using a keyboard. PRINTER DRIVER: The printer driver is generally operable using a keyboard with a screen reader. However, not all functions are fully accessible without vision. DOCUMENT: Text alternatives are provided for non-text content presented to users, enabling the content to be accessed without vision. Canon PRINT: Canon PRINT is generally usable with VoiceOver or TalkBack on a mobile device. However, not all applicable functions and content are fully accessible without vision. *Access to Remote UI: To access the Remote UI, enter the IP address of your Canon device (for example, http://XXX.XXX.XXX.XXX) into a web browser. Navigation within the Remote UI can be performed primarily using the arrow keys to move between user interface elements. In this version of the Remote UI, child elements are presented immediately after their corresponding parent elements in the navigation and reading order.
5.1.3 Low vision	Partially Supports	HARDWARE: Information is visually presented on the display and indicator lamps. Information conveyed by color is also available in text, and controls can generally be distinguished through contrast. However, the on-screen text size is smaller than the minimum requirement, some areas used for paper, ink, and maintenance operations have limited contrast, and the product does not provide text enlargement or display customization features. Remote UI: Remote UI supports text resizing, sufficient contrast, and information that is not conveyed by color alone. However, some ink level information and non-text content lack appropriate text alternatives, some controls do not meet target size requirements, repeated navigation blocks cannot be bypassed, certain functions do not fully support keyboard operation, and error assistance or help functions are not provided. PRINTER DRIVER: The printer driver provides sufficient contrast between text and background, enabling use by many users with limited vision.

		DOCUMENT: Non-text content is accompanied by text alternatives, enabling information to be accessed more easily by users with limited vision and through magnification tools. Canon PRINT: Canon PRINT generally supports users with limited vision through platform accessibility features such as screen magnification and high-contrast display settings. However, not all applicable accessibility criteria are fully supported.
5.1.4 Colour blindness	Supports	HARDWARE, Remote UI, PRINTER DRIVER and DOCUMENT: Information is not conveyed by color alone. Color-coded information is supplemented with text, and controls can be distinguished through contrast with surrounding areas. Canon PRINT: Information is generally not conveyed by color alone. However, not all applicable accessibility criteria related to color-independent use are fully supported.
5.1.5 Deafness	Supports	HARDWARE: Operation of the product does not require hearing. Audible notifications, when provided, are also available through visual indicators such as the display and status lamps. Remote UI, PRINTER DRIVER, DOCUMENT and Canon PRINT: The products do not rely on auditory information and can be used without hearing.
5.1.6 Hearing impairment	Supports	HARDWARE: Operation of the product does not require hearing. Audible notifications, when provided, are also available through visual indicators such as the display and status lamps. Remote UI, PRINTER DRIVER, DOCUMENT and Canon PRINT: The products do not rely on auditory information and can be used without hearing.
5.1.7 Speech impairment	Supports	The product does not require speech input, voice commands, or speech-based user identification. All functions can be operated without vocal input.
5.1.8 Impairment that limits upper limb strength and action (limited manipulation)	Partially Supports	HARDWARE: The product does not require multipoint gestures, path-based gestures, simultaneous actions, or motion-based operation for touchscreen use. However, maintenance tasks such as paper replacement and roll paper installation require pinching, twisting, and coordinated manual actions, and no alternative method is provided. Remote UI: Most functions can be performed without fine motor control or simultaneous actions. However, some functions are not fully operable using only a keyboard. PRINTER DRIVER: All functions can be operated using a keyboard interface without requiring simultaneous manual actions. DOCUMENT: Documentation can be accessed and navigated using standard keyboard functions without requiring simultaneous manual actions. Canon PRINT: Most functions can be operated using standard touch gestures without requiring multipoint or path-based gestures. However, not all applicable accessibility criteria related to limited manipulation are fully supported.

5.1.8 Impairment that limits upper limb strength and action (limited strength)	Partially Supports	HARDWARE: Some operations, including ink tank replacement and roll paper replacement, require force exceeding 22.2 N. No alternative method is provided for these operations. Remote UI, PRINTER DRIVER, DOCUMENT and Canon PRINT: Use of the products does not require significant hand strength.
5.1.9 Impairment that limits reach ranges	Partially Supports	HARDWARE: Obstacles exceeding 865 mm are present when operating the touch screen, control panel buttons, top cover, and ink tanks. The ink replacement reach depth exceeds 610 mm. The open top cover and ink tank positions exceed 1170 mm in height. In addition, the display is difficult to view from a seated position due to its height and viewing angle. Remote UI, PRINTER DRIVER, DOCUMENT and Canon PRINT: The products can be accessed without requiring physical reach to product controls or components.
5.1.10 Photosensitive seizure	Supports	The product does not contain flashing content that may trigger photosensitive seizures. Display indicators and status lamps do not flash in a manner that may adversely affect users.
5.1.11 Cognitive, language, or learning disorders	Partially Supports	HARDWARE: The product provides labels, status indications, error notifications, and information that is not dependent on color or audio alone. Some functions can be accessed through Canon PRINT or Remote UI using assistive technologies, and certain timeout-based functions can be disabled. However, the product does not provide speech output, and some non-text content and error information may not be fully accessible. Remote UI: Remote UI supports understanding and ease of use through clear labels, consistent navigation, and predictable behavior. However, some ink level information and non-text content lack sufficient explanatory information, some content relationships are not clearly conveyed, and help or error assistance features are not provided. PRINTER DRIVER: Accessibility features support users in completing tasks with minimal interruption and consistent operation. DOCUMENT: Components with the same functionality are identified consistently, supporting understanding and learning. Canon PRINT: Canon PRINT provides features that support understanding and operation. However, not all applicable accessibility criteria related to cognition, language, and learning are fully supported.

Chapter 6: Requirements

Criteria	Conformance Level	Remarks and Explanations
6.1 General The basic requirements which shall be followed with respect to office equipment in order to ensure and improve accessibility are as specified in 6.2 to 6.13.	No response required	
6.2 Closed functionality 6.2.1 General Office equipment with closed functionality shall be operable without requiring the user to attach or install assistive technology and shall conform to the following items.	No response required	

6.2.2 Speech-output enabled 6.2.2.1 General For the operation of a screen, such as the control panel, an operation with voice guidance shall be provided.	No response required	
6.2.2.2 Information displayed on-screen Voice guidance shall be provided for all information displayed on-screen.	Partially Supports	The product itself does not provide audio output, such as voice guidance. However, some functions can be operated using Canon PRINT with VoiceOver or TalkBack. Device status and settings can also be accessed through Remote UI using screen reader software on a PC, such as JAWS.
6.2.2.3 Spoken languages Voice guidance shall be output in the same human language as the displayed language.	Partially Supports	The product itself does not provide audio output, such as voice guidance. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Text and speech output are provided in the same language.
6.2.2.4 Speech delivery type and coordination Voice guidance shall be delivered in a mechanism that can be easily used by all users. Examples include, but are not limited to, direct audio output (or bundled audio output), industry standard connectors, telephone handsets, and the like. Speech shall be recorded or digitized human or synthesized. Voice guidance shall be coordinated with information displayed on the screen.	Supports*	The product itself does not provide audio output, such as voice guidance. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Access to speech output and the method of audio delivery depend on the user's computing device and screen reader software.
6.2.2.5 User control Voice guidance for any single function shall be automatically interrupted when a transaction is selected. Voice guidance shall be capable of being repeated and paused. Where it is essential that the user hears the entire message, for example a safety instruction or warning, office equipment shall block all user action so that speech is not interrupted.	Supports*	Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Control of speech output, including functions such as stop and repeat, depends on the user's computing device and screen reader software.
6.2.2.6 Non-interfering audio output During voice guidance, another guidance (warning notification) or auditory signal that lasts three seconds or longer shall not be automatically played.	Supports*	Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Whether interfering audible output is played simultaneously with speech output depends on the user's computing device, screen reader software, and audio configuration.
6.2.2.7 Tactile indication of speech output mode Where voice guidance is provided, a tactile symbol to initiate the guidance shall be provided.	Supports*	Speech output is not provided by the product itself.
6.2.3 Volume 6.2.3.1 General Where sound such as voice guidance is delivered, volume control and output amplification conforming to 6.2.3.2 and 6.2.3.3 shall be provided. Deliver the voice guidance as the main operation means, and when the use by the hearing impairment users is assumed, a) volume shall be adjusted within a range of at least 18 dB, b) at least one intermediate step of 12 dB above the lowest volume level shall be provided.	Not applicable	
6.2.3.2 Private listening Where private listening is provided, non-visual mode of operation for controlling the volume shall be provided.	Supports*	Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Speech output controls, including volume adjustment, depend on the user's computing device, screen reader software, and listening technology.
6.2.3.3 Non-private listening Where non-private listening is provided, a) speaker volume can be amplified up to a level of at least 65 dB (both speech and auditory signals), b) the volume shall be automatically reset to the default level after every use. (only speech). For personal authentication, it may have a function not to reset.	Supports*	Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Speech output controls, including volume adjustment, depend on the user's computing device, screen reader software, and audio output device.

6.2.4 Characters on display screens At least one mode of characters displayed on the screen shall be in a sans serif font. Where a screen enlargement feature is not provided, characters shall be 4,8 mm or higher based on the uppercase letter "I" or "H".	Partially Supports	The character size displayed on the screen is approximately 3.5 mm and does not meet the minimum size requirement specified by this criterion. However, the characters provide sufficient contrast against the background, which helps maintain a degree of readability.
6.3 Biometrics Where provided, biometrics shall not be the only means for user identification or control. Exception: Where at least two biometric options that use different biological characteristics are provided, using biometrics shall be permitted as the only means for user identification or control.	Supports*	No biometric user identification is used.
6.4 Preservation of information provided for accessibility Where video and other contents with information added for accessibility are delivered to multi-function devices, non-proprietary information provided for accessibility shall not be removed or shall be restored upon delivery.	Supports*	The import/export functions are applicable to this requirement. However, no accessibility-related information is included in the imported or exported data; therefore, there is no such information to preserve.
6.5 Privacy 6.5.1 General The same degree of privacy of input and output shall be provided to all individuals.	Supports	Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. In accordance with Canon Global Privacy principles, privacy is provided equally to all users, regardless of disability. In addition, Remote UI does not provide a feature that conceals on-screen information while screen reader output is active.
6.5.2 Masked entry Where auditory output is provided as non-visual access to closed functionality, and the characters displayed are masking characters, the auditory output shall not be a spoken version of the characters entered unless the auditory output is known to be delivered only to a mechanism for private listening, or the user explicitly chooses to allow non-private auditory output.	Supports	Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on computing devices. Characters entered in masked fields, such as password fields, are not spoken by screen readers.
6.5.3 Private access to personal data Where auditory output is provided as non-visual access to a closed functionality, and the output contains data that is considered to be private according to the applicable privacy policy, the corresponding auditory output shall only be delivered through a mechanism for private listening that can be connected without requiring the use of vision, or through any other mechanism explicitly chosen by the user.	Supports	Speech output is not provided by the product itself. However, some functions are available through Canon PRINT and Remote UI and can be accessed using screen readers on a mobile device or computer. In accordance with the Canon Global Privacy Statement, the privacy of all individuals is protected equally, regardless of disability.
6.6 Standard connections Where data connections used for input and output are provided, at least one of each type of connection shall conform to industry standard non-proprietary formats.	Supports	All connection interfaces conform to industry standards.
6.7 Operable parts 6.7.1 General Operable parts used in the normal operation of office equipment shall conform to 6.7.	No response required	
6.7.2 Contrast Where operation parts such as hard keys and levers are provided, they shall ensure to contrast visually from background surfaces. Characters and symbols printed on office equipment shall ensure to contrast visually from background surfaces with either light characters or symbols on a dark background or dark characters or symbols on a light background.	Partially Supports	Some areas related to paper and ink replacement and maintenance have low contrast, making them difficult for users to visually identify during replacement.
6.7.3 Input controls 6.7.3.1 General At least one input control conforming to 6.7.3.2, 6.7.3.3, or 6.7.3.4 shall be provided for each function of office equipment.	No response required	
6.7.3.2 Tactilely discernible Where office equipment has operable parts by hand, it shall provide a means to tactilely discern each operable part. It shall also be discernible by touch without activation.	Does not support	The product uses a touchscreen interface and provides four physical input controls. Three of these controls are readily distinguishable by touch. The power button is tactilely discernible; however, its tactile features are less distinct and may not be readily identifiable by touch.

6.7.3.3 Alphabetic keys Where provided, individual alphabetic keys shall be arranged in a QWERTY-based keyboard layout and the "F" and "J" keys shall be tactilely distinct from the other keys.	Does not support	No alphabetic or numeric hard keys are provided. The device uses software keys on the touchscreen and does not meet the requirement.
6.7.3.4 Numeric keys Where provided, numeric keys shall be arranged in a 12-key ascending or descending keypad layout. The number five key shall be tactilely distinct from the other keys. Where the office equipment provides an alphabetic overlay on numeric keys, the relationships between letters and digits shall conform to ITU-T E.161.	Does not support	No alphabetic or numeric hard keys are provided. The device uses software keys on the touchscreen and does not meet the requirement.
6.7.4 Key repeat Where a keyboard with key repeat is provided and the key repeat cannot be turned off, the time before the key repeat is activated shall be fixed at 2 s, or adjustable to 2 or more seconds. The key repeat rate shall be adjustable to 2 or more seconds per character.	Does not support	The key repeat function is provided and cannot be disabled by the user. For manual roll paper operation, paper feeding begins less than 2 seconds after a button is pressed and held.
6.7.5 Double-strike key Where a keyboard or keypad is provided and the same operation as the previous keystroke was performed, the time during which the next keystroke will not be accepted shall be adjustable 0,5 s or more.	Does not support	The product does not provide a configurable bounce key function.
6.7.6 Timed response Where a timed response is required, and the timed response function cannot be turned off, the user shall be alerted visually, as well as by touch or sound, and shall be given the opportunity to indicate that more time is needed.	Supports	In certain settings screens, the display may be locked after a timeout period. The screen lock function can be disabled. When the paper type selection method is set to "Automatic", the operation is automatically executed after 5 seconds of inactivity. This behavior can also be disabled through configuration.
6.7.7 Simultaneous user actions Where office equipment requires simultaneous user actions for the user, office equipment shall provide at least one action that does not require simultaneous user actions.	Partially Supports	Paper replacement requires coordinated actions, and no alternative method is provided.
6.7.8 Physical operation At least one mode of operation shall be operable with one hand and the operation shall not require tight grasping, pinching, or twisting of the wrist. The operation shall require a maximum force of 22,2 N.	Partially Supports	Ink tank and roll paper replacement may require the use of both hands or forces exceeding 22.2 N in some situations, and no alternative means of operation is provided.
6.7.9 Fare cards and key cards Where operation of office equipment requires fare cards or key cards and orientation is important to use, orientation shall be tactilely discernible.	Supports*	No cards are used.
6.7.10 Reach height and depth 6.7.10.1 General At least one of each type of operable part of floor type office equipment shall be at a height conforming to 6.7.10.3 or 6.7.10.4 according to its position established by the vertical reference plane specified in 6.7.10.2 for a side reach or a forward reach. Operable parts used with speech output required by 6.2.2 shall not be the only type of operable part complying with 6.7.10 unless that part is the only operable part of its type.	No response required	
6.7.10.2 Vertical reference plane 6.7.10.2.1 General Operable parts shall be positioned for a side reach or a forward reach determined with respect to a vertical reference plane. The vertical reference plane shall be located in conformance to 6.7.10.2.2 or 6.7.10.2.3.	No response required	
6.7.10.2.2 Vertical plane for side reach Where a side reach is provided, the vertical reference plane shall be 1 220 mm (48 inches) long minimum.	Supports	A vertical reference plane for side approach can be provided. The product is designed for side approach by seated users.
6.7.10.2.3 Vertical plane for forward reach Where a forward reach is provided, the vertical reference plane shall be 760 mm (30 inches) long minimum.	Not Applicable	A vertical reference plane for side approach can be provided. The product is designed for side approach by seated users.

6.7.10.3 Side reach 6.7.10.3.1 General Operable parts of office equipment providing a side reach shall conform to 6.7.10.3.2 or 6.7.10.3.3. The vertical reference plane shall be centred on the operable part and placed at the leading edge of the maximum protrusion of the office equipment within the length of the vertical reference plane. Where a side reach requires a reach over a portion of the office equipment, the height of that portion of the office equipment shall be 865 mm (34 inches) maximum.	Does not support	When replacing ink or configuring the display, the main unit itself becomes an obstruction, as its height exceeds 865 mm.
6.7.10.3.2 Unobstructed side reach Where the operable part is located 255 mm (10 inches) or less beyond the vertical reference plane, the operable part shall be 1 220 mm (48 inches) high maximum and 380 mm (15 inches) high minimum above the floor.	Partially Supports	Some parts of the paper output basket and the stand lock are positioned less than 380 mm above the floor.
6.7.10.3.3 Obstructed side reach Where the operable part is located more than 255 mm (10 inches), but not more than 610 mm (24 inches), beyond the vertical reference plane, the height of the operable part shall be 1 170 mm (46 inches) high maximum and 380 mm (15 inches) high minimum above the floor. The operable part shall not be located more than 610 mm (24 inches) beyond the vertical reference plane.	Partially Supports	Ink replacement requires a reach depth exceeding 610 mm.
6.7.10.4 Forward reach 6.7.10.4.1 General Operable parts of office equipment providing a forward reach shall conform to 6.7.10.4.2 or 6.7.10.4.3. The vertical reference plane shall be centred, and intersect with, the operable part. Where a forward reach allows a reach over a portion of the office equipment, the height of that portion of the office equipment shall be 865 mm (34 inches) maximum.	Not Applicable	This product is intended for side access; therefore, no issues arise that require resolution.
6.7.10.4.2 Unobstructed forward reach Where the operable part is located at the leading edge of the maximum protrusion within the length of the vertical reference plane of the office equipment, the operable part shall be 1 220 mm (48 inches) high maximum and more than 380 mm (15 inches) high minimum above the floor.	Not Applicable	This product is intended for side access; therefore, no issues arise that require resolution.
6.7.10.4.3 Obstructed forward reach 6.7.10.4.3.1 General Where the operable part is located beyond the leading edge of the maximum protrusion within the length of the vertical reference plane, the operable part shall conform to 6.7.10.4.3.2 and 6.7.10.4.3.3. The maximum allowable forward reach to an operable part shall be 635 mm (25 inches).	Not Applicable	This product is intended for side access by a wheelchair user.
6.7.10.4.3.2 Operable part height for office equipment with obstructed forward reach Reach depth: 510 mm (20 inches) or less, Operable part height: 1 220 mm (48 inches) maximum Reach depth: More than 510 mm (20 inches) to 635 mm (25 inches) or less, Operable part height: 1 120 mm (44 inches) maximum	Not Applicable	This product is intended for side access by a wheelchair user.
6.7.10.4.3.3 Knee and toe space under office equipment with obstructed forward reach Knee and toe space under the office equipment shall be 685 mm (27 inches) high minimum, 635 mm (25 inches) deep maximum, and 760 mm (30 inches) wide minimum and shall be clear of obstructions.	Not Applicable	This product is intended for side access; therefore, no issues arise that require resolution.
6.8 Visibility of display screens Where office equipment provides one or more display screens, at least one of each type of display screen shall be visible from a point located 1 015 mm (40 inches) above the floor.	Does not support	The display is positioned 1015 mm above the floor and may be difficult to view due to its height and viewing angle.
6.9 Flashing Where office equipment emits lights in flashes, there shall be no more than three flashes in any one-second period.	Supports	Lights emitted by the product do not flash more than three times within a one-second period.

6.10 Status indicators Where provided, status indicators shall be discernible visually and by touch or sound.	Supports through Equivalent Facilitation	Status information presented on the operation panel and the illuminated state of indicator lamps are visually discernible. The product does not provide tactile or auditory indication of these states on the device itself. However, many status monitoring and configuration functions are available through Remote UI, which can be accessed using screen reader software on a PC.
6.11 Colour coding Where provided, colour coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	Supports	Information conveyed through the use of color is also conveyed through text. In addition, controls and visual elements that use color can be distinguished from surrounding elements by contrast.
6.12 Audible signals Where provided, audible signals or cues shall not be used as the only means of conveying information, indicating an action, or prompting a response.	Supports	All the information of audible signals or cues during operation are also given by the LED lights and other components visually.
6.13 Software requirements for closed functionality 6.13.1 General Office equipment with software closed to assistive technologies shall conform to 6.13.2 to 6.13.12. NOTE The following requirements are premised the use of office equipment, harmonizing with the related requirements of WCAG 2.1, as EN 301 549 requires to satisfy WCAG 2.1.	No response required	
6.13.2 Sensory characteristics Instructions provided for understanding and operating content do not rely solely on sensory characteristic of components such as shape, colour, size, visual location, orientation, or sound (WCAG 2.1:2018, 1.3.3).	Does not Support	Speech output is not provided by the product itself.
6.13.3 Audio control If any audio on an office equipment plays automatically for more than 3 s, either a mechanism is available to pause or stop the audio, or a mechanism is available to control audio volume independently from the overall system volume level (WCAG 2.1:2018, 1.4.2).	Supports	The product has no audio content.
6.13.4 Text contrast The visual presentation of text and images of text has a contrast ratio of at least 4.5:1, except for the following (WCAG 2.1:2018, 1.4.3):	Supports	The contrast is satisfying.
6.13.5 Non-text contrast The visual presentation of the following has a contrast ratio of at least 3:1 against adjacent colour(s) (WCAG 2.1:2018, 1.4.11):	Supports	The contrast is satisfying.
6.13.6 No-key trap If focus can be moved between components using a key interface, then focus can be moved away from that component using only a key interface, and, if it requires more than usual methods, the user is advised of the method for moving focus away (WCAG 2.1:2018, 2.1.2).	Supports*	Since the screen is operated by a touch panel, there is no keyboard-operated focus.
6.13.7 Pause, stop, hide For moving, blinking, scrolling, or auto-updating information, all of the following are true (WCAG 2.1:2018, 2.2.2):	Supports	Although there is a progress indicator, this requirement does not apply because the absence of this indicator could lead to the misunderstanding that the operation has stopped.
6.13.8 Focus order If a display can be navigated sequentially and the navigation sequences affect meaning or operation, focusable components receive focus in an order that preserves meaning and operability (WCAG 2.1:2018, 2.4.3)	Supports*	Since the screen is operated by a touch panel, there is no keyboard-operated focus.
6.13.9 Focus visible Any key-operable user interface has a mode of operation where the focus indicator is visible (WCAG 2.1:2018, 2.4.7).	Supports*	Since the screen is operated by a touch panel, there is no keyboard-operated focus.
6.13.10 Pointer gestures All functionality that uses multipoint or path-based gestures for operation can be operated with a single pointer without a path-based gesture, unless a multipoint or path-based gesture is essential (WCAG 2.1:2018, 2.5.1)	Supports	The display of the product does not require multipoint or path-based gestures for operation. Swiping is available, but you can also use a single pointer.

6.13.11 Label in name For user interface of speech input, which have labels that include text or image of text, the name contains the text that is presented visually (WCAG 2.1:2018, 2.5.3).	Does not Support	Speech output is not provided by the product itself. The contents of display is not programmatically interpretable.
6.13.12 On focus When any user interface component receives focus, it does not initiate a change of context (WCAG 2.1:2018, 3.2.1).	Supports*	Since the screen is operated by a touch panel, there is no keyboard-operated focus.

Chapter 7: Support Documentation and Services

Criteria	Conformance Level	Remarks and Explanations
7.1 Disclosure of information related to accessibility When users purchase and use office equipment, the provider of office equipment shall provide the user with information related to the accessibility of the office equipment, so that the user can easily select an office equipment with the appropriate accessibility features to match the user needs.	Supports	This VPAT lists and explains the features required by EN 301 549 requirements.
7.2 Requirements for user documentation and support services Customer service representatives or equivalent services shall be provided to users, and multiple access methods shall be available to users to communicate with these services.	Supports	The WCAG, which is clause9, is applied to the documentation. See WCAG section for the results. Support services will provide information about functions related to accessibility by means according to user's requests. You can reach contact support from below URL. https://www.canon-europe.com/support/consumer_products/contact_support/ Please choose proper country. Phone number and e-mail address are described. If there is not proper country, please access below and contact each office in your country. https://www.canon-europe.com/contact_us/canon_europe_middle_east_and_africa_offices/

Note1: This document was prepared based on normal walk-up functionality. It does not include maintenance and troubleshooting procedures. The information contained in this document is proprietary information and is not for reproduction, publication or manipulation in any way or form. This document addresses a multitude of the product's features; however, any specific inquiries should be made to the Canon Marketing Representative.

Note2: Comments in the "Conformance Level" column are based on the Information Technology Industry Council's suggested language for use when filling out the Voluntary Product Accessibility Template. The Remarks and Explanations column provides additional information on the evaluation results, and explains the standard functions of the product that can accommodate users with disabilities.

Note3: This document is for informational purposes only. This information is based on Canon's current understanding of the standards. It is not intended to address applicability of these laws to a particular end-user, customer, application or procurement.

Note4: All product design and specifications are subject to change. Some of the information may be based upon data collected or tests conducted on similar product modules.

Note5: The information in this Report should not be considered a contractual agreement by Canon. FURTHER, THE INFORMATION AND MATERIALS PROVIDED IN THIS REPORT ARE "AS IS" WITHOUT WARRANTIES OF ANY KIND, INCLUDING WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF INTELLECTUAL PROPERTY. Canon does not warrant the accuracy and completeness of the information or materials in this Report. Canon may make changes to the information in this Report, or to the products described in this Report at any time, without notice.