

EOS M SERIES COMPARISON CHART

		EOS M5	EOS M6	EOS M50	EOS M100
Image Sensor	Size	Effective pixels: Approx. 24.2 megapixels		Effective pixels: Approx. 24.1 megapixels	Effective pixels: Approx. 24.2 megapixels
	Туре	APS-C CMOS Sensor			I
ISO Range	Stills	ISO 100-25600		ISO 100-25600, H: 51200	ISO 100-25600
	Videos	ISO 100-25600	ISO 100-6400, H: 12800	4K: ISO 100–6400 Full HD, HD: ISO 100–12800, H: 25600	ISO 100–6400, H: 12800
Image Processor		D igit		DiGrC	Digic
Recording Media		SD / SDHC / SDXC Memory Cards (UHS-I compatible)			
Built-in Wireless Connectivity					
	MP4 Recording	Yes			
Video Recording	Video Recording Size	1920 x 1080 (Full HD): 60p (55 1280 x 720 (HI 640 x 480 (SE	D): 60p (59.94)	3840 x 2160 (4K): 24p (23.98) 1920 x 1080 (Full HD): 60p (59.94), 30p (29.97), 24p (23.98) 1280 x 720 (HD): 120p (119.9), 60p (59.94)	1920 x 1080 (Full HD): 60p (59.94), 30p (29.97), 24p (23.98) 1280 x 720 (HD): 60p (59.94) 640 x 480 (SD): 30p (29.97)
	External Microphone Jack	Yes		N/A	
Autofocus	Туре			Dual Pixel AF CMOS AF (4K videos)	Dual Pixel AF
	AF Points	49 points		143/99 points^	49 points
Continuous Shooting Speed		One-Shot AF (all lenses): Max. approx. 9.0 fps Servo AF: Max. approx. 7.0 fps		One-Shot AF (all lenses): Max. approx. 10.0 fps Servo AF: Max. approx. 7.4 fps	One-Shot AF (all lenses): Max. approx. 6.1 fps Servo AF: Max. approx. 4.0 fps
Maximum Shutter Speed Range		1/4000 to 30 sec., bulb			
LCD Size/Type		3.2" Tilt			
2000	ize/Type	(Up 85° / Down 180°), Capacitive Touch Panel LCD	3.0" Tilt (Up 180° / Down 45°), Capacitive Touch Panel LCD	3.0" Vari-angle, Capacitive Touch Panel LCD	3.0" Tilt (Up 180°), Capacitive Touch Panel LCD
	ize/Type vfinder	(Up 85° / Down 180°),	(Up 180° / Down 45°),		(Up 180°),
Viev		(Up 85° / Down 180°), Capacitive Touch Panel LCD	(Up 180° / Down 45°), Capacitive Touch Panel LCD Compatible with Electronic Viewfinders	Capacitive Touch Panel LCD	(Up 180°), Capacitive Touch Panel LCD
Viev Dials &	vfinder	(Up 85° / Down 180°), Capacitive Touch Panel LCD Built-in Electronic Viewfinder Main Dial (Customizable) Quick Control Dial (Customizable) Dial Function Button (Customizable) Exposure Compensation Dial (Customizable) Power Lever	(Up 180° / Down 45°), Capacitive Touch Panel LCD Compatible with Electronic Viewfinders EVF-DC2^ and EVF-DC1^^ Main Dial (Customizable) Mode Dial Quick Control Dial (Customizable) Exposure Compensation Dial	Capacitive Touch Panel LCD Built-in Electronic Viewfinder Main Dial Mode Dial Ie);	(Up 180°), Capacitive Touch Panel LCD
Viev Dials & Conn	vfinder & Buttons	(Up 85° / Down 180°), Capacitive Touch Panel LCD Built-in Electronic Viewfinder Main Dial (Customizable) Quick Control Dial (Customizable) Dial Function Button (Customizable) Exposure Compensation Dial (Customizable) Power Lever	(Up 180° / Down 45°), Capacitive Touch Panel LCD Compatible with Electronic Viewfinders EVF-DC2^^ and EVF-DC1^^ Main Dial (Customizable) Mode Dial Quick Control Dial (Customizable) Exposure Compensation Dial Power Lever B 2.0 Hi-Speed (PictBridge compatib AV Output (NTSC, MP4, Stereo Audio o-HDMI Connector, SD Memory Card	Capacitive Touch Panel LCD Built-in Electronic Viewfinder Main Dial Mode Dial Ie);	(Up 180°), Capacitive Touch Panel LCD N/A USB 2.0 Hi-Speed (PictBridge compatible); AV Output (NTSC, MP4, Stereo Audio); Micro-HDMI Connector,
Viev Dials & Conn Addition	vfinder & Buttons	(Up 85° / Down 180°), Capacitive Touch Panel LCD Built-in Electronic Viewfinder Main Dial (Customizable) Quick Control Dial (Customizable) Dial Function Button (Customizable) Exposure Compensation Dial (Customizable) Power Lever	(Up 180° / Down 45°), Capacitive Touch Panel LCD Compatible with Electronic Viewfinders EVF-DC2^^ and EVF-DC1^^ Main Dial (Customizable) Mode Dial Quick Control Dial (Customizable) Exposure Compensation Dial Power Lever B 2.0 Hi-Speed (PictBridge compatib AV Output (NTSC, MP4, Stereo Audio o-HDMI Connector, SD Memory Card Remote Switch Terminal	Capacitive Touch Panel LCD Built-in Electronic Viewfinder Main Dial Mode Dial Ie);	(Up 180°), Capacitive Touch Panel LCD N/A USB 2.0 Hi-Speed (PictBridge compatible); AV Output (NTSC, MP4, Stereo Audio); Micro-HDMI Connector, SD Memory Card Slot

Not responsible for typographical errors. Products not shown to scale. * Compatible with iOS* versions 9.3/10.3/11.0, Android" smartphone and tablet versions 4.4/5.0/5.1/6.0/7.0/7.1/8.0. Data charges may apply with the download of the free Canon Camera Connect app. This app helps enable you to upload images to social media services. Please note that image files may contain personally identifiable information that may implicate privacy laws. Canon disclaims and has no responsibility for your use of such images. Canon does not obtain, collect or use such images or any information included in such images through this app. ** Compatible with Android" smartphone and tablet versions 4.4/5.0/5.1/6.0/7.0/7.1/8.0. *** Compatible with select services (Android" version 5.0 or later and the following iOS* devices: iPhone 4s or later, iPad 3rd gen. or later, iPad Touch 5th gen. or later) equipped with Bluetooth* version 4.1 or later and the Camera Connect App Ver. 21.20. This application is not guaranteed to operate on all listed devices, even if minimum requirements are met. ^ Switches automatically depending on the lens type. ^* Othoral accessory. ^* CIPA Standard-including the battery and memory card. © 2018 Canon U.S.A., Inc. Canon, DIGIC, the DIGIC logo and EOS are trademarks of Canon Inc. in the United States, and may be registered trademarks in other countries. All third-party logos are trademarks of their respective owners.