

Environmental Profile Sheet

The imageRUNNER ADVANCE DX 6870i/6860i/6855i models incorporate Canon technologies, each with a strong environmental focus at every stage of the product lifecycle—Produce, Use, and Recycle. These technologies, which focus on Energy Conservation, Resource Conservation, and Pollution Prevention, form the foundation of Canon's Environmental Management System.

| | Energy Conservation | Resource Conservation | Pollution Prevention |
|---|------------------------|--------------------------|-------------------------|
| In order to help reduce dependence on petroleum-based materials, Canon uses 100% recycled plastics.* | | Á | |
| A variety of sleep recovery triggers, including motion sensing, help encourage the use of Sleep Mode , which minimizes power consumption. | 1 | | |
| Power consumption in Sleep Mode is as low as 0.80 W! | 1 | | |
| Low Typical Electricity Consumption (TEC) values, which measure power consumption during a one-week period. | Ŋ | | |
| Power consumption is reduced by utilizing White LED array technology in its Color Image Reader versus using a traditional Xenon tube! | A) | | |
| Rapid Fusing technologies help reduce power consumption and limit the warm-up period . | B | | |
| CS2 Toner, with its low melting point, helps reduce fusing temperature requirements . | 1 | | |
| All suppliers are required to meet Canon's stringent Green Procurement policy and environmental terms. This helps Canon exceed the tough European Union's RoHS Directive, which controls/restricts the use of certain hazardous substances . | | | A |
| Each system is equipped with paper-, toner-, and energy-saving features that help to cut costs and conserve resources . | Ŋ | 1 | |
| Long-life parts and high-yield supplies help maximize uptime and help reduce the amount of materials consumed during the product life cycle. | | Á | B |
| imageRUNNER ADVANCE DX 6800 series, registered as EPEAT Gold , also attained EPEAT Climate+ , demonstrating criteria adherence for limited climate impact. | Ą | <u> </u> | A |

Canon. The Natural Partner for Business.





^{*} Excluding a small amount of additives to improve physical properties.

Environment-Related Specifications

| System Type | | |
|----------------------------------|---|--|
| Monochrome Laser Multifunctional | | |
| Functions | | |
| Standard: | Print (UFR III, PCL® 6, Adobe® PostScript® 3™), Copy, Scan, Send, Store | |
| Optional: | Fax (Up to 4 lines) | |
| Operation Panel | | |
| Standard: | 10.1" TFT LCD WSVGA Color Flat-panel | |
| Warm-up Time | | |
| From Power On: | Approx. 6 Seconds | |
| From Sleep Mode: | | |
| 6870i: | Approx. 7 Seconds | |
| 6860i: | Approx. 6 Seconds | |
| 6855i: | Approx. 6 Seconds | |
| Quick Startup Mode: | Approx. 4 Seconds | |
| Power Requirements | 110-127 V AC, 60 Hz, 12 A | |
| Power Consumption | | |
| Maximum: | 1,800 W | |
| Sleep Mode: | 0.80 W | |
| Copying/Printing: | 854 W | |
| Copy Ready (Standby): | 48.4 W | |
| Plug-in | | |
| Quick Startup Mode "OFF": | 0.19 W | |
| Quick Startup Mode "ON": | 0.4 W | |
| One Week TEC: | | |
| 6870i: | 0.89 kWh | |
| 6860i: | 0.74 kWh | |
| 6855i: | 0.68 kWh | |
| One Year TEC: | | |
| 6870i: | 46.3 kWh | |
| 6860i: | 38.5 kWh | |
| 6855i: | 35.4 kWh | |
| British Thermal Units (BTU) | | |
| Maximum (BTU/Hr.): | 6,142 | |
| Copying/Printing (BTU/Hr.): | 2,914 | |
| Copy-Ready (Standby) (BTU/Hr.): | 165 | |

| * | Including consumables. | |
|---|------------------------|--|
| * | 1[D] =10[dD] | |

- *** Measured in accordance with ISO7796. Presented in accordance with ISO9296.
- Percentage based on weight of recycled content.
- ENERGY STAR, TEC Values, and EPEAT is based off of ENERGY STAR version 3.0.

| NEMA 5-15P |
|------------|
| |

Dimensions (W x D x H)

Standard (including 1-Pass DADF): 24-3/8" x 28-1/2" x 36-7/8" (620 mm x 722 mm x 937 mm)

Installation Space (W x D)

Basic: 44-7/8" x 45-3/4" (1,138 x 1,162 mm) (Right Cover Open with Multipurpose tray extended + Cassette Drawers Open)

Fully Configured: 73-1/2" x 45-3/4" (1,866 x 1,162 mm) (Staple Finisher-AB2 or Paper Folding/Booklet Finisher-A1 with the extension tray extended + Paper Deck Unit-F2 + Cassette Drawers open)

| · | • • |
|-------------------------------|-------------------|
| Weight | |
| 6870i: | 205.0 lb. (93 kg) |
| 6860i: | 200.6 lb. (91 kg) |
| 6855i: | 200.6 lb. (91kg) |
| Noise Levels (LwA,m [B])** | |
| Standby:*** | |
| 6870i: | 4.0 B |
| 6860i: | 4.0 B |
| 6855i: | 3.6 B |
| Copying/Printing*** | |
| 6870i: | 6.7 B |
| 6860i: | 6.6 B |
| 6855i: | 6.7 B |
| Recycled Content | |
| Recycled Primary Package (%): | Approx. 24% |
| Recycled Paper Support | |
| 100% Post-consumer Content: | Yes |
| Environmental Standards Con | npliance |
| ENERGY STAR® Certified* | |
| EPEAT Gold with Climate+* | |
| | |

Environment-conscious Features

Two-sided, Copy Sample, Confirmation/Cancel, Image Combination, ID Card Copy, Secured Print, Job Forwarding, Department ID Management, Access Management System, Authentication (Universal Login Manager), Standard Duplex Driver, Auto/Weekly Sleep Timer, Auto/Weekly Shutdown Timer, Staple-Free Stapling



















1-844-50-CANON | usa.canon.com/business