
*** Network Configuration Page ***

Wireless LAN Enable
Connection Active
MAC Address AA:BB:CC:DD:EE:FF
SSID Home
Communication Mode Infrastructure
Channel 9
Encryption AES
WEP Key Length Inactive
Authentication WPA2-PSK
Signal Strength 100[%]
TCP/IP Version IPv4
IPv4 IP Address 192.168.0.103
IPv4 Default Gateway 192.168.0.1
Subnet Mask 255.255.255.0
IPv6 IP Address
IPv6 Default Gateway
Subnet Prefix Length
IPsec
Security Protocol
WPS PIN CODE 12345678
Wireless LAN DRX Enable

Wired LAN Disable
Connection Inactive
MAC Address AA:BB:CC:DD:EE:FF
TCP/IP Version IPv4
IPv4 IP Address
IPv4 Default Gateway
Subnet Mask
IPv6 IP Address
IPv6 Default Gateway
Subnet Prefix Length
IPsec
Security Protocol
Wired LAN DRX

Other Settings
Printer Name 000000000000
WSD Enable
WSD Timeout 1 [min]
LPR Protocol Enable
Bonjour Enable
Bonjour Service Name Canon iX6800 series
DNS Server Auto
Primary Server 192.168.0.1
Secondary Server
Proxy Server Disable
Proxy Port
Proxy Address
IP Address Filtering Disable
Default Password AaBbCcDd