



THE POWER OF
NEXT



imageFORCE C1935P

imageFORCE C1935P
shown with optional
accessories

SPECIFICATIONS

Main Unit

| | |
|---------------------------------------|--|
| Technology/Type | Laser/A3 Color Printer |
| Core Functions | Print |
| Print Speed (BW and Color) | Up to 35 ppm (1-Sided Letter) ¹ Up to 32.5 ppm (2-Sided Letter) ¹ |
| Control Panel | 5 Line LCD |
| Memory | 2.0 GB RAM |
| Processor | 1.6GHz dual core, 800MHz Single core |
| Storage | 32 GB eMMC (available space 15 GB) |
| Interface Connections | NETWORK Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n) OTHERS Standard: USB 2.0 (Host) x1, USB 2.0 (Device) x1 |
| Paper Sources (Letter, 20 lb. Bond) | Standard: 250-Sheet Paper Cassette, 100-Sheet Multi-Purpose Tray Optional: 550-Sheet Paper Cassettes (Paper Feeder PF-L1) |
| Paper Capacity (Letter, 20 lb. Bond) | Standard: 350 Sheets Maximum: 2,550 Sheets |
| Output Capacity (Letter, 20 lb. Bond) | Standard/Maximum: 250 Sheets |
| Finishing Capabilities | Collate, Group |
| Supported Media Types | Cassettes: Thin, Plain, Recycled, Color, Heavy, Coated, Bond, Letterhead, Label Paper Multi-Purpose Tray: Thin, Plain, Recycled, Color, Heavy, Coated, Bond, Label Paper, Envelope, Postcard, Letterhead |
| Supported Media Sizes | Cassettes: 11" x 17", Legal, Letter, Letter-R, Executive, Statement Custom Size: 3-3/8" x 5-8/7" to 11-3/4" x 17" Multi-Purpose Tray: 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R, Index Cards (3" x 5") Envelopes: No.10 (COM10), Monarch, DL, ISO-C5, Long Sheets: 11.69" x 35.43" / 11.69" x 47.24" |

| | |
|--|--|
| Supported Media Weights | Cassettes: 16 lb. Bond to 60 lb. Cover (60 to 163 gsm) |
| | Multi-Purpose Tray: 16 lb. Bond to 92.5 lb. Cover (60 to 250 gsm) |
| | Duplex: 16 lb. Bond to 60 lb. Cover (60-163 gsm) Excluding Gloss Paper 27 lb. Bond to 80 lb. Cover (100-220 gsm) Gloss Paper |
| Warm-up Time | Quick Startup Mode: Approx. 2 Seconds ² |
| | From Sleep Mode: Approx. 7 Seconds |
| Dimensions (W x D x H) | 19-5/8" x 20-5/8" x 14" (499 x 525 x 354 mm) |
| Installation Space (W x D) | 19-5/8" x 38-1/8" (499 x 968.2 mm) (Cassette Drawer Open) |
| Weight | Approx. 83.3 lb (37.8 kg) ³ |
| Print Specifications | |
| Print Resolution (dpi) | Up to 1200 x 1200 Default: 600 x 600 |
| Standard Page Description Languages | Standard: UFR II, PCL6/PCL5, Adobe® PostScript®3™ |
| Direct Print Supported File Types | PDF, EPS, TIFF/JPEG, and XPS |
| Printing from Mobile and Cloud | A range of software and MEAP-based solutions (AirPrint, Mopria, IPP Everywhere, Canon PRINT, uniFLOW Online and Universal Print) are available to provide printing from mobile devices or internet-connected devices and cloud-based services ⁴ depending on your requirements. Please contact your sales representative for further information. |
| Operating System Standard Printing Fonts | Android®/ Windows® 10®/ Windows® 11®/ Chrome OS®/ macOS (11.2.2 or later)®/ iOS(15.2 or later)®/ iPadOS® |

SPECIFICATIONS CONTINUED

imageFORCE C1935P

| | |
|--|---|
| Print Features | Secure Print, Secure Watermark, Header/Footer, Page Layout, Two-sided Printing, Mixed Paper Sizes/Orientations, Toner Reduction, Poster Printing, Forced Hold Printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer |
| Fonts | PS: 136 Roman PCL: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T ⁷ (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts ⁸ |
| Operating System | UFRIL: Windows® 10/11/Server2016/Server2019/Server2022/Server2025, macOS (10.15 or later) PCL: Windows® 10/11/Server2016/Server2019/Server2022/Server2025 PS: Windows® 10/11/Server2016/Server2019/Server2022/Server2025, macOS (10.15 or later) PPD: Windows® 10/11, macOS (10.15 or later) |
| Security Specifications | |
| Authentication and Access Control | User Authentication (Card Login, Username and Password Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online/uniFLOW ⁹ (PIN Login, Card Login, Card and PIN Login), Microsoft Entra ID Authentication (Card Login), Two-Factor Authentication at RUI, Access Management System (Access Control) |
| Document Security | Print Security (Secure Print, Encrypted SecurePrint, Forced Hold Printing, uniFLOW Secure Print ⁹) |
| Network Security | TLS 1.3 (FIPS 140-3), IPsec (FIPS 140-3), IEEE802.1X authentication, SNMPv3, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/ Wireless LAN, Wired LAN/Wired LAN), WPA3 support (Wi-Fi), Enabling/Disabling (Network Applications, Remote UI, USB Interface), USB Port separation from LAN, Scan and Send-Virus Concerns for E-mail Reception |
| Device Security | Standard Storage Initialize, Job Log Conceal Function, Protecting MFP Software Integrity: Verify System at Startup (NIST SP800-193: Protection) ¹⁰ , Checking MFP Software Integrity & Platform Firmware Resiliency: Automatic System Recovery (NIST SP800-193: Recovery), Runtime Intrusion Detection: Trellix Embedded Control ¹⁰ |
| Device Management and Auditing | Administrator Password, Digital Certificate and Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Security Policy Setting |

| | |
|--|---|
| Environmental Specifications | |
| Operating Environment | Temperature: 10 to 30 °C Humidity: 20 to 80 % RH (Relative Humidity) |
| Power Requirements | 110-127V, 60 Hz, 6.0A |
| Power Consumption | Maximum: Approx. 1,905 W Sleep mode: Approx. 1.0 W ¹¹ Typical Electricity Consumption (TEC) rating: 0.39 kWh ¹² |
| Environmental Standards | ENERGY STAR® certified EPEAT Bronze |
| Consumables | |
| Toner Cartridges (All in One Toner Cartridge) | Toner T16 Yellow ¹³ Toner T16 Magenta ¹³ Toner T16 Cyan ¹³ Toner T16 Black ¹³ |
| Toner Yield (Estimated @ 5.0% Coverage) | Yellow/Magenta/Cyan: 14,000 impressions Black: 21,000 impressions |
| Paper Source Options¹⁴ | |
| Feeder Options | PAPER FEEDER PF-L1 Paper Capacity: 550 Sheets (Letter, 20 lb. Bond) Paper Type: Plain, Recycled, Color, Heavy, Bond, Letterhead, Rough Paper, Label Paper Paper Size: 11" x 17", Legal, Letter, Letter-R, Executive Custom Size: 5-8/7" x 5-8/7" to 11-3/4" x 17" |

¹ Print speed is based on internal testing. Print speed may vary, depending on the number of copies selected as well as the settings for size, type, and orientation of paper.
² Time from device power-on until print ready (not print reservation).
³ Includes consumables.
⁴ Subscription to a third-party cloud service required. Subject to third-party cloud service provider's Terms and Conditions.
⁵ Need to select the [Use Mopria] check box [OK].
⁶ Need to select the [Use AirPrint] check box [OK].
⁷ Optional PCL International Font Set-A1 is required.
⁸ Optional Barcode Printing Kit-D1 is required.
⁹ Requires optional uniFLOW Online/uniFLOW.
¹⁰ This feature is off by default and must be turned on by the administrator. Times are affected once turned on.
¹¹ Sleep mode is not available in all circumstances due to certain settings.
¹² ENERGY STAR® Product Specification for Imaging Equipment Version 3.2.
¹³ Includes toner, drum, and developer.
¹⁴ Paper capacity may vary with different paper types/sizes.



usa.canon.com/business

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified this model as meeting the ENERGY STAR® energy efficiency criteria through an EPA recognized certification body. ENERGY STAR® and the ENERGY STAR® mark are registered U.S. marks. Canon, imageFORCE and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Some security features may impact functionality/performance; you may want to test these settings in your environment. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. Trellix and the Trellix logo are trademarks or registered trademarks of Musarubra US LLC or its subsidiaries in the U.S. and other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Representative for details. Products shown with optional accessories. Subscription to a third-party cloud service required. Subject to third-party cloud service providers terms and conditions. uniFLOW is a registered trademark of NT-ware Systemprogrammierung GmbH. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21, or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.
 ©2026 Canon U.S.A., Inc. All rights reserved. 03/26-0022-14926