



THE POWER OF NEXT

imageFORCE C5170/C5160 C5150/C5140



Device shown with optional accessories.

SPECIFICATIONS

Main Unit

Technology/Type	OLED/A3 Color Multifunction
Core Functions	Standard: Print, Copy, Scan, Send, Store Optional: Fax, Up to 4 lines
Print/Copy Speed (BW and Color)	imageFORCE C5170 Up to 70 ppm ¹ (Letter) Up to 42 ppm (Letter-R) Up to 40 ppm (Legal) Up to 35 ppm (11" x 17") imageFORCE C5160 Up to 60 ppm ¹ (Letter) Up to 36 ppm (Letter-R) Up to 34 ppm (Legal) Up to 32 ppm (11" x 17") imageFORCE C5150 Up to 50 ppm ¹ (Letter) Up to 30 ppm (Letter-R) Up to 29 ppm (Legal) Up to 27 ppm (11" x 17") imageFORCE C5140 Up to 40 ppm ¹ (Letter) Up to 24 ppm (Letter-R) Up to 23 ppm (Legal) Up to 20 ppm (11" x 17")
Control Panel	10.1" TFT LCD WSVGA Color Touch panel
Memory	6.0 GB RAM
Solid-State Drive	Standard: 256GB Optional: 1TB
Interface Connection	NETWORK Standard: 1000Base-T/100Base-TX/10Base-T Optional: Wireless LAN (IEEE 802.11a/b/g/n/ac/ax) OTHERS Standard: USB 2.0 (Host) x1, USB 3.0 (Host) x1, USB 2.0 (Device) x1 Optional: Serial Interface, Copy Control Interface
Paper Sources (Letter, 20 lb. Bond)	Standard: Dual 550-sheet Paper Cassettes, 100-sheet Multi-Purpose Tray Optional: Dual 550-Sheet Paper Cassettes (Cassette Feeding Unit-AY1), 2,450-Sheet High Capacity Cassette (High Capacity Cassette Feeding Unit-F1), 2,700-Sheet Paper Deck (Paper Deck Unit-F2)
Paper Capacity (Letter, 20 lb Bond)	Standard: 1,200 Sheets Maximum: 6,350 Sheets

Output Options	1st Copy Tray Kit-B1, Inner 2way Tray-M1, 3rd Copy Tray Kit-A1, Inner Finisher-N1, Staple Finisher-AB3, Staple Finisher Lite-A1, Paper Folding/Booklet Finisher-A2, Paper Folding Unit-L1, Inner 2/3 Hole Puncher-D1, 2/3 Hole Puncher Unit-A1
Output Capacity (Letter, 20 lb. Bond)	Standard 250 Sheets Maximum: 3,450 Sheets
Finishing Capabilities	Collate, Group, Offset, Staple, Saddle Stitch, Hole Punch, Eco Staple, Staple On Demand, V-fold, C-fold, Z-fold (Capabilities vary depending on the options installed)
Supported Media Types	Paper Cassettes: Thin, Plain, Recycled, Eco, Color, Heavy, Bond, Transparency, Pre-punched, Letterhead, Envelope (Requires standard envelope feeder attachment) Multi-Purpose Tray: Thin, Plain, Recycled, Eco, Color, Heavy, Coated, Tracing, Bond, Transparency, Label, Pre-punched, Letterhead, Tab, Envelope
Supported Media Sizes	Upper Cassette: Letter, Executive, Statement-R, Envelopes [COM10 (No.10), Monarch, DL, ISO-C5], Custom Size (3-7/8" x 5-7/8" to 11-3/4" x 8-1/2") Lower Cassette: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Envelopes [COM10 (No.10), Monarch, DL, ISO-C5], Custom size (3-7/8" x 5-7/8" to 12" x 18") Multi-Purpose Tray: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R, Envelopes[COM 10 (No.10), Monarch, DL, ISO-C5], Custom size/Free Size (3-7/8" x 5-1/2" to 12-5/8" x 18"), Long sheet ² (3-7/8" x 18" to 12-5/8" x 51-1/4")
Supported Media Weights	Upper Cassette: 14 lb bond to 140 lb index (52 to 256 gsm) Lower Cassette: 14 lb bond to 110 lb cover (52 to 300 gsm) Multi-Purpose Tray: 14 lb bond to 110 lb cover (52 to 300 gsm) Duplexing: 14 lb bond to 140 lb index (52 to 256 gsm)
Warm-up Time	Quick Startup Mode: Approx. 4 Seconds ³ From Sleep Mode: Approx. 7 Seconds ⁴ (imageFORCE C5170) Approx. 6 Seconds ⁴ (imageFORCE C5160/ C5150/C5140) From Power On: Approx. 6 Seconds ⁵

SPECIFICATIONS CONTINUED

imageFORCE C5170/C5160 C5150/C5140

Dimensions (W x D x H)	24-3/8" x 28-1/2" x 36-7/8" (620 x 722 x 937 mm)*
Installation Space (W x D)	Basic: 41-3/8" x 45-3/4" (1,050 x 1,162 mm) (Right Cover Open with Multi-purpose tray extended + Cassette Drawers Open) Fully Configured: 80-1/2" x 45-3/4" (2,044 x 1,162 mm) (Staple Finisher-AB3/Paper Folding/Booklet Finisher-A2 with the extension tray extended + Paper Folding Unit-L1 + Paper Deck Unit-F2 + Cassette Drawers open)
Weight	Approx. 231.5 lb (105 kg) ⁷
Print Specifications	
Print Resolution (dpi)	Up to 4,800 x 2,400*
Standard Page Description Languages	Standard: UFR II, PCL6/PCL5, Adobe® PostScript®3™
Direct Print Supported File Types	PDF, EPS®, TIFF/JPEG, and XPS
Printing from Mobile and Cloud	A range of standard and optional software and MEAP based solutions (including AirPrint, Mopria, IPP Everywhere, Canon PRINT, optional uniFLOW Online, Universal Print by Microsoft®, and optional Cloud Connector) are available to provide printing from mobile devices or compatible internet-connected devices and cloud-based services ¹⁰ depending on your requirements. Please contact your sales representative for further information.
Operating System Standard Printing	Android/Windows® 10/Windows® 11/Chrome OS/macOS (11.2.2 or later) /iOS (15.2 or later)/iPadOS
Fonts	PCL: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT (Japanese, Korean, Simplified and Traditional Chinese) ¹¹ , Barcode fonts ¹² PS: 136 Roman
Operating System¹³	UFR II: Windows® 10/11/Server 2016/Server2019/Server2022/Server 2025, macOS (10.14 or later) PCL: Windows® 10/11/Server 2016/Server2019/Server2022/Server 2025 PS: Windows® 10/11/Server 2016/Server2019/Server2022/Server 2025, macOS (10.14 or later) PPD: Windows® 10/11/Server 2016/Server2019/Server2022/Server 2025, macOS (10.14 or later)
Copy Specifications	
First-Copy-Out Time (Letter)	imageFORCE C5170: As fast as 2.7 seconds (BW) / 3.7 seconds (Color)
	imageFORCE C5160: As fast as 2.9 seconds (BW) / 4.2 seconds (Color)
	imageFORCE C5150: As fast as 3.4 seconds (BW) / 4.9 seconds (Color)
	imageFORCE C5140: As fast as 4.1 seconds (BW) / 6.1 seconds (Color)
Copy resolution (dpi)	600 x 600
Multiple Copies	Up to 999 copies
Magnification	Variable zoom: 25% to 400% (1% increments)
Scan Specifications	
Type	Single-pass Duplexing Automatic Document Feeder (Multi-Sheet Feed Detection is supported)
Document Feeder Paper Capacity	Up to 200 Sheets (20 lb bond)
Document Feeder Supported Media Sizes	Document Feeder media size: 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Custom size (2-3/4" x 5-1/2" to 12" x 17")
Document Feeder Supported Media Weights	50 to 220 gsm
Platen Scanning Size	Up to 11-3/4" x 17"
Pull Scan Specifications	Color Network ScanGear2 for both TWAIN and WIA Supported OS: Windows® 10/11/Server 2016/Server 2019/Server 2022/Server 2025
Scan Resolution (dpi)	600 x 600

Scan Method	Push Scan, Pull Scan, Scan to Box, Scan to Advanced Box, Scan to Network, Scan to USB Memory Key, Scan to Mobile devices, Scan to Cloud (Optional uniFLOW Online or Cloud Connector)
Scan Speed (ipm, BW and Color, Letter)	Single-Scanning: 135/135 (300 x 300 dpi, Send), 80/80 (600 x 600 dpi, Copy), Double-sided Scanning: 270/270 (300 x 300 dpi, Send), 160/90 (600 x 600 dpi, Copy)
Send Specifications	
Destination	Standard: Email/Internet FAX (SMTP*4), SMB, FTP, WebDAV, Mail Box Optional: Super G3 FAX, IP Fax
Address Book	LDAP (2,000)/Local (1,600)/Speed dial (200)
Communication Protocol	File: FTP (TCP/IP), SMB3.1.1 (TCP/IP), WebDAV Email/I-Fax: SMTP, POP3
File Format	TIFF (MMR), JPEG (Single Page Only), PDF (Compact, Searchable, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Device Signature, User Signature), Office Open XML (PowerPoint, Word)
Send Features	Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, Email Priority, TX Report, Original Content Orientation, Skip Blank Pages
Fax Specifications	
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400 x 400 (Ultra Fine), 200 x 400 (Super Fine), 200 x 200 (Fine), 200 x 100 (Normal)
Sending/Receiving Size	11" x 17", Legal, Letter, Letter-R, Statement-R
FAX Memory	Up to 30,000 pages (2,000 Jobs)
Speed Dials	Max. 200
Group Dials/Destinations	Max. 199 Dials
Sequential Broadcast	Max. 256 Addresses
Memory Backup	Yes
Store Specifications	
Mail Box (Number Supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes Maximum 10,000 Pages (2,000 jobs) Stored
Advanced Box	Communication Protocol: SMB or WebDAV Supported Client PC: Windows® 10/11 Concurrent Connections (Max.): SMB:64, WebDAV:3
Advanced Box Available Disc Space	Approx. 16 GB (Standard SSD) Approx. 480 GB (With Optional 1 TB SSD)
Security Specifications	
Authentication and Access Control	User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), optional uniFLOW Online/uniFLOW ¹⁵ (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), optional Cloud Connector (PIN Login), Microsoft Entra ID (PIN Login, Card Login), Two-Factor Authentication at LUI/ RUI, Access Management System (Access Control)

SPECIFICATIONS CONTINUED

imageFORCE C5170/C5160 C5150/C5140

Document Security	Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print ¹⁵), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS), BOX Security (Mail Box Password Protected, Advanced Box Access Control), Send Data Security (Setting for requesting password input per transmission, Restricted Email/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Secure Watermark
Network Security	TLS 1.3, IPSec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), WPA3 (Wi-Fi), Enabling/Disabling (Network Applications, Remote UI, USB Interface), G3 FAX separation from LAN, USB Port separation from LAN, Prohibit the execution of files stored in Advanced Box in the MFP, Scan and Send -Virus Concerns for Email Reception
Device Security	Protecting SSD Data [SSD Data Encryption (FIPS140-3), SSD Lock], Standard SSD Initialize, Initialize (NIST 800-88 Purge Level), Trusted Platform Module (TPM 2.0), Job Log Conceal Function, Protecting MFP Software Integrity: Verify System at Startup (NIST SP800-193: Protection), Checking MFP Software Integrity & Platform Firmware Resiliency: Automatic System Recovery (NIST SP800-193: Recovery), Runtime Intrusion Detection: Trellix Embedded Control ¹⁶ , HCD-PP Common Criteria Certification (Validation pending)
Device Management and Auditing	Administrator Password, Digital Certificate and Key Management, SAN certificates, Audit Log, Cooperating with External Security Audit System (SIEM: Security Information and Event Management) ¹⁷ , Image Data Logging, Security Policy Setting
Environmental Specifications	
Operating Environment	Temperature: 50 to 86 °F Humidity: 20 to 80% RH (Relative Humidity)
Power Source	imageFORCE C5170/C5160/C5150: 110-127V, 60Hz, 12A imageFORCE C5140: 110-127V, 60Hz, 10A
Power Consumption	Maximum: Approx. 1,800 W Sleep mode: Approx. 0.5 W ¹⁸ Typical Electricity Consumption (TEC) ¹⁹ : imageFORCE C5170 : 0.78 kWh imageFORCE C5160 : 0.64 kWh imageFORCE C5150 : 0.51 kWh imageFORCE C5140 : 0.40 kWh
Environmental Standards	ENERGY STAR® certified EPEAT-Gold EPEAT Climate+
Consumables	
Toner Cartridges	GPR-1001 Toner BK/C/M/Y GPR-1001L Toner C/M/Y
Toner Yield (Estimated @5% Coverage)	GPR-1001 BK: Approx. 63,000 Pages GPR-1001 C/M/Y: Approx. 54,500 Pages GPR-1001L C/M/Y: Approx. 24,000 Pages
Paper Source Options	
Cassette Feeding Unit-A1	Paper Capacity: Dual 550-Sheet Paper Cassettes (20 lb bond) Paper Type: Thin, Plain, Recycled, Eco, Color, Heavy, Bond, Transparency, Pre-punched, Letterhead Paper Size: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size (3-7/8" x 5-7/8" to 12" x 18") Paper Weight: 14 lb bond to 110 lb cover (52 to 300 gsm)
High Capacity Cassette Feeding Unit-F1	Paper Capacity: Up to 2,450 Sheets Paper Type: Thin, Plain, Recycled, Eco, Color, Heavy, Bond, Pre-punched, Letterhead Paper Size: Letter Paper Weight: 14 lb bond to 110 lb cover (52 to 300 gsm)
Paper Deck Unit-F2	Paper Capacity: Up to 2,700 Sheets Paper Type: Thin, Plain, Color, Recycled, Heavy, Pre-punched Paper Size: Letter Paper Weight: 14 lb bond to 140 lb index (52 to 256 gsm)

Paper Output Options²⁰

1st Copy Tray Kit-B1	Tray Capacity: Letter, Statement, Statement-R: Up to 250 Sheets 12" x 18", 11" x 17", Legal, Letter-R, Executive: Up to 100 Sheets Long Sheet ²¹ : Length up to 35-1/2": Up to 20 Sheets [56 lb cover to 60 lb cover (151 to 163 gsm)] Length up to 47-1/4": 1 Sheet [56 lb cover to 60 lb cover (151 to 163 gsm)] Paper Weight: 14 lb bond to 110 lb cover (52 to 300 gsm)
Inner 2way Tray-M1	(Requires 1st Copy Tray Kit-B1) Tray Capacity: Letter, Statement, Statement-R: Up to 100 Sheets 12" x 18", 11" x 17", Legal, Letter-R, Executive: Up to 50 Sheets Paper Weight: 14 lb bond to 110 lb cover (52 to 300 gsm)
3rd Copy Tray Kit-A1	Tray Capacity: Letter, Statement-R: Up to 100 Sheets 12" x 18", 11" x 17", Legal, Letter-R, Executive: Up to 75 Sheets Paper Weight: 14 lb bond to 110 lb cover (52 to 300 gsm)
Inner Finisher-N1	Tray Capacity: Upper Tray: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R: Up to 50 Sheets Long sheet length of Up to 35-1/2": 1 Sheet Lower Tray: Letter, Statement, Statement-R, Executive: Up to 500 Sheets 11" x 17", Legal, Letter-R: Up to 250 Sheets 12" x 18", Envelope: Up to 10 Sheets Paper Weight: 14 lb bond to 110 lb cover (52 to 300 gsm) Staple Position: Corner, Double Staple Capacity [14 lb bond to 24 lb bond (52 to 90 gsm)]: Letter, Executive: Up to 50 Sheets Letter-R: Up to 40 Sheets 11" x 17", Legal: Up to 30 Sheets Eco Staple: 11" x 17", Letter: Up to 10 Sheets [14 lb bond to 17 lb bond (52 to 64 gsm)] Up to 8 Sheets [18 lb bond to 21 lb bond (65 to 81.4 gsm)] Up to 6 Sheets [22 lb bond to 28 lb bond (82 to 105 gsm)] Staple On Demand: Up to 40 Sheets [20 lb bond (75 gsm)]
Staple Finisher-AB3	(Requires Buffer Pass Unit-R1) Tray Capacity: Upper Tray: Letter, Executive, Statement, Statement-R: Up to 250 Sheets 12" x 18", 11" x 17", Legal, Letter-R: Up to 125 Sheets Lower Tray: Letter, Executive, Statement, Statement-R: Up to 3,000 Sheets 12" x 18", 11" x 17", Legal, Letter-R: Up to 1,500 Sheets 11" x 17" (Z-fold ²²): Up to 30 Sheets Legal, Letter-R (Z-fold ²²): Up to 10 Sheets Envelopes: Monarch: Up to 30 Sheets, COM10 No.10, DL, ISO-C5: Up to 100 Sheets Long sheet length of up to 51-1/4": Up to 20 Sheets ejected to the top of the Buffer Pass Unit-R1 and Staple Finisher-AB3 Paper Weight: Upper Tray: 14 lb bond to 140 lb index (52 to 256 gsm) Lower Tray: 14 lb bond to 110 lb cover (52 to 300 gsm) Staple Position: Corner, Double Staple Capacity: Letter, Executive: Up to 65 Sheets [14 lb bond to 24 lb bond (52 to 90 gsm)] Letter-R: Up to 40 Sheets [14 lb bond to 24 lb bond (52 to 90 gsm)] 11" x 17", Legal: Up to 30 Sheets [14 lb bond to 24 lb bond (52 to 90 gsm)] Eco Staple: 11" x 17", Letter: Up to 10 Sheets [14 to 17 lb bond (52 to 64 gsm)] Up to 8 Sheets [18 lb bond to 21 lb bond (65 to 81.4 gsm)] Up to 6 Sheets [22 lb bond to 28 lb bond (82 to 105 gsm)] Staple On Demand: Up to 65 Sheets [14 lb bond to 24 lb bond (52 to 90 gsm)]

SPECIFICATIONS CONTINUED

imageFORCE C5170/C5160 C5150/C5140

Staple Finisher Lite-A1	(Requires Buffer Pass Unit-R1) Tray Capacity: Upper Tray: Letter, Executive, Statement, Statement-R: Up to 250 Sheets 12" x 18", 11" x 17", Legal, Letter-R: Up to 125 Sheets Lower Tray: Letter, Executive, Statement, Statement-R: Up to 1,500 Sheets 12" x 18", 11" x 17", Legal, Letter-R: Up to 1,500 Sheets 11" x 17" (Z-fold ²²): Up to 30 Sheets Legal, Letter-R (Z-fold ²²): Up to 10 Sheets Envelopes: Monarch: Up to 30 Sheets, COM10 No.10, DL, ISO-C5: Up to 100 Sheets Long sheet length of up to 51-1/4" (1,300 mm): Up to 20 Sheets ejected to the top of the Buffer Pass Unit-R1 and Staple Finisher Lite-A1 Paper Weight: Upper Tray: 14 lb bond to 140 lb index (52 to 256 gsm) Lower Tray: 14 lb bond to 110 lb cover (52 to 300 gsm) Staple Position: Corner, Double Staple Capacity: Letter, Executive: Up to 65 Sheets [14 lb bond to 24 lb bond (52 to 90 gsm)] Letter-R: Up to 40 Sheets [14 lb bond to 24 lb bond (52 to 90 gsm)] 11" x 17", Legal: Up to 30 Sheets [14 lb bond to 24 lb bond (52 to 90 gsm)] Staple On Demand: Up to 65 Sheets [14 lb bond to 24 lb bond (52 to 90 gsm)]
Booklet Finisher-A2 with Tri-Fold	(Requires Buffer Pass Unit-R1) (Includes the above Staple Finisher-AB3 basic staple specifications.) Saddle Stitch/V-fold paper size: 12" x 18", 11" x 17", Legal, Letter-R C-fold paper size: Legal, Letter-R Saddle Stitch Staple Capacity: Up to 20 Sheets x 10 sets [14 to 21 lb bond (52 to 81.4 gsm)] (including 1 cover sheet [14 lb bond to 140 lb index (52 to 256 gsm)]) V-fold Capacity: Up to 5 Sheets [14 lb bond to 28 lb bond (52 to 105 gsm)] C-fold Capacity: Letter-R: up to 6 Sheets [14 lb bond to 24 lb bond (52 to 90 gsm)] up to 5 Sheets [25 lb bond to 34 lb bond (91 to 128 gsm)] Legal: up to 5 Sheets [17 lb bond to 34 lb bond (64 to 128 gsm)]
Paper Folding Unit-L1	(Requires an external Staple Finisher or Booklet Finisher) Paper size: 11" x 17", Legal, Letter-R
Inner 2/3 Hole Puncher-D1	(Requires the Inner Finisher-N1) Two or Three Holes Acceptable Punch Paper Weight: 14 lb bond to 110 lb cover (52 to 300 gsm) Acceptable Punch Paper Size: Two holes: 11" x 17", Legal, Letter, Letter-R, Executive Three holes: 11" x 17", Letter, Executive
2/3 Hole Puncher Unit-A1	(Requires Buffer Pass and an external Staple Finisher or Booklet Finisher) Two or Three Holes Acceptable Punch Paper Weight: 14 lb bond to 110 lb cover (52 to 300 gsm) Acceptable Punch Paper Size: Two holes: 11" x 17", Legal, Letter, Letter-R, Executive Three holes: 11" x 17", Letter, Executive

imagePASS Controller Specifications (Optional)	
Name	imagePASS-T1
Page Description Languages	Adobe PS3, PCL6, Adobe PDF Print Engine (Optional)
Memory	8GB (4GBx2)
Hard Disk Drive	500 GB SATA
CPU	Intel Pentium Gold 5400 (3.7GHz)
System Software	FS500
OS	Debian or Linux
imagePASS Controller Standard Features	Fiery Command WorkStation 7/Paper Catalog/Fiery Spot-On/Fiery Remote Scan
imagePASS Controller Options	Fiery Impose/Fiery Compose/Fiery Impose and Compose/Fiery Automation package/Fiery ColorRight package/Fiery JobExpert and PDF Processing Kit

- ¹ When paper is fed from Upper Cassette, High Capacity Cassette, Feeding Unit-F1, or Paper Deck Unit-F2.
- ² Long Sheet Feeding Tray-A1 is required.
- ³ Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display.
- ⁴ Time from exiting Sleep mode to when printing is operational.
- ⁵ Time from device power-on until copy ready (not print reservation).
- ⁶ Includes main unit and standard ADF.
- ⁷ Includes consumables.
- ⁸ Data processing is 4,800 equivalent x 2,400 equivalent.
- ⁹ EPS can be printed directly only from the Remote User Interface.
- ¹⁰ Subscription to a third-party cloud service required. Subject to third-party cloud service provider's Terms and Conditions.
- ¹¹ Requires optional PCL International Font Set-A1.
- ¹² Requires optional Barcode Printing Kit-D1.
- ¹³ Other operating systems and environments, including AS/400, UNIX, Linux, and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.
- ¹⁴ Available OAuth 2.0 authentication method on Microsoft 365 and Google Workspace.
- ¹⁵ Requires optional uniFLOW Online/uniFLOW.
- ¹⁶ This feature is off by default and must be turned on by the user. Warm-up times are affected once turned on. Note: See Product Specifications Sheet for a complete list of standard and optional security features.
- ¹⁷ Third-party SIEM system required. Subject to third-party SIEM system's Terms and Conditions. Canon cannot ensure compatibility with all third-party SIEM systems.
- ¹⁸ 0.5 W is not available in all circumstances due to certain settings.
- ¹⁹ Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.2.
- ²⁰ Paper capacity may vary with different paper types/sizes.
- ²¹ Long Sheet Catch Tray-D1 is required.
- ²² Paper Folding Unit-L1 is required.



1-844-50-CANON | usa.canon.com/business

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified this model as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon, imageFORCE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Some security features may impact functionality/performance; you may want to test these settings in your environment. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. Trellix and the Trellix logo are trademarks or registered trademarks of Musarubra US LLC or its subsidiaries in the U.S. and other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Subscription to a third-party cloud service required. Subject to third-party cloud service provider's terms and conditions. uniFLOW is a registered trademark of NT-ware Systemprogrammierung GmbH. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21, or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.