



imagePRESS V1000

COLOR PRODUCTION DIGITAL PRESS



imagePRESS V1000 shown with optional accessories.

Product Specifications

Marking Engine

Technology	Electrophotography	
Print Speed	8.5" x 11":	Up to 101 ipm
	11" x 17":	Up to 52 ipm
	12" x 18":	Up to 50 ipm
	13" x 19":	Up to 48 ipm
	13" x 30":	Up to 28 ipm
Paper Size	Standard:	3.9" x 5.8" to 13" x 19.2"
	Optional:	5.5" x 7.2" to 13" x 51.2"
Paper Capacity¹	Standard:	Up to 1,100 Sheets
	Optional:	Up to 11,100 Sheets
Paper Weight	Standard:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Optional:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Envelopes: ²	No. 10, ISO-C5, DL, Monarch, 6" x 9", 9" x 12", 10" x 13"
Automatic Duplexing	Paper Size:	Up to 13" x 51.2" ³
	Paper Weight:	Up to 150 lb. Cover (400 gsm) ⁴
Power Source	(2) Single-Phase 200 -240 V, 50/60 Hz, 20 A	
Weight	904 lb.	
Dimensions	62.3" x 34.3" x 40.9" (WxDxH)	

Input Accessories

Duplex Color Image Reader-P1	Image Sensor:	CCD
	Scan Speed:	Up to 270 opm (Letter, 300 dpi)
	Document Size:	2.8" x 5.5" to 12" x 24.8"
	Resolution:	Up to 600 x 600 dpi, 256 Gradations
	Tray Capacity:¹	Up to 200 Sheets
	Weight:	51 lb.
POD Deck-F1	Dimensions:	25.7" x 23.3" x 8.6" (WxDxH)
	Paper Capacity:¹	Up to 5,000 Sheets
	Paper Size:	5.5" x 7.2" to 13" x 19.2"
	Paper Weight:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Power Source:	110 - 127 V, 60 Hz, 7 A
	Weight:	392 lb.
Multi-Drawer Paper Deck-E1	Dimensions:	38" x 31.5" x 42.5" (WxDxH)
	Paper Capacity:¹	Up to 5,000 Sheets
	Paper Size:	5.5" x 7.2" to 13" x 19.2"
	Paper Weight	
	Top/Middle:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Bottom:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
POD Deck Lite-C1	Power Source:	110 - 127 V, 60 Hz, 7 A
	Weight:	392 lb.
	Dimensions:	38" x 31.5" x 42.5" (WxDxH)
	Paper Capacity:¹	Up to 3,500 Sheets
	Paper Size:	5.5" x 5.8" to 13" x 19.2"
	Paper Weight:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Power Source:	120 - 127 V, 60 Hz, 2.2 A
	Weight:	168 lb.
	Dimensions:	28.2" x 27" x 22.6" (WxDxH)

Input Accessories (Continued):

Plockmatic LCT XL	Paper Capacity: ¹	Up to 3,500 Sheets
	Required Infeed:	POD Deck-F1
	Paper Size:	7.2" x 8.3" to 13" x 27.5"
	Paper Weight:	18 lb. Bond to 150 lb. Cover (65 gsm to 400 gsm)
	Weight:	551 lb.
	Dimensions:	54" x 32" x 42.9" (WxDxH)
Plockmatic LSM XL	Paper Capacity: ¹	Up to 700 Sheets
	Required Infeed:	Plockmatic LCT XL
	Paper Size:	7.2" x 8.3" to 13" x 51.2"
	Paper Weight:	21 lb. Bond to 150 lb. Cover (80 gsm to 400 gsm)
POD Deck Lite XL-A2	Paper Capacity ¹	
	Up to 13" x 19.2":	Up to 3,500 Sheets
	Up to 13" x 30":	Up to 1,000 Sheets
	Paper Size:	5.5" x 5.83" to 13" x 30"
	Paper Weight:	
	Up to 13" x 19.2":	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Up to 13" x 30":	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Power Source:	120 – 127 V, 60 Hz, 2.2 A
	Weight:	249 lb.
	Dimensions:	43.5" x 27" x 22.6" (WxDxH)
Stack Bypass-D1	Paper Capacity: ¹	Up to 250 Sheets
	Paper Size:	3.9" x 5.83" to 13" x 19.2"
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Weight:	3 lb.
	Dimensions:	18" x 15.1" x 2.9" (WxDxH)
Stack Bypass Alignment Tray-D1	Paper Capacity:	Up to 1 Sheet
	Paper Size:	8.3" x 19.2" to 13" x 51.2"
	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Infeed:	Stack Bypass-D1
	Weight:	2 lb.
	Dimensions:	85.6" x 56.1" x 56.1" (WxDxH)

Finishing Accessories

Sensing Unit-B1 ⁵	Tasks:	Front-to-Back Alignment, Color Accuracy Check, Cross Shade Adjustment, Secondary Transfer Adjustment
	DFE:	PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 V1.0 or Later
	Paper Weight:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Paper Size:	5.5" x 5.83" to 13" x 51.2"
	Power Supply:	100 – 240 V, 50/60 Hz, 2.5 A
	Weight:	222 lb.
	Dimensions:	20.3" x 29.5" x 48.3" (WxDxH)

Inspection Unit-A1 ⁵	Paper Type:	Plain Paper, Coated Paper
	Paper Weight:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Paper Size:	3.9" x 7.2" to 11.9" x 19.2"
	Detection Size:	0.2 mm x 0.2 mm to 1.4 mm x 1.4 mm
	Scanning Width:	Up to 11.9"
	Inspection Workstation	
	Inspection Tool OS:	Windows® 10 Pro
	Mode:	Log Only Mode, Purge and Recovery Mode
	Inspection Location:	Up to 64
	Intensity Level:	9 Levels
	Objects:	Position Gap, Dot of Dirt, Streak of Dirt
	Auto Recovery:	Yes (Purge and Recovery Mode Only)
	Purge Unit:	High Capacity Stacker-J1
	Power Supply:	120 – 240 V, 50/60 Hz, 1.4 A
	Weight:	109 lb.
	Dimensions:	9.8" x 31.2" x 40.9" (WxDxH)

Document Insertion Unit-R1 ⁵	Tray Capacity ¹	
	Upper Tray:	Up to 200 Sheets
	Lower Tray:	Up to 200 Sheets
	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Paper Size:	7.2" x 7.2" to 13" x 19.2"
	Power Supply:	100 – 240 V, 50/60 Hz, 1.4 A
Static Eliminator-A1 ⁵	Weight:	135 lb.
	Dimensions:	29.4" x 31.2" x 55.4" (WxDxH)
	Paper Sizes:	3.9" x 5.8" to 13" x 51.2"
	Paper Weight:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Power Supply:	100 – 240 V, 50/60 Hz, 1 A
	Weight:	110 lb.
	Dimensions:	9.8" x 31.2" x 41" (WxDxH)

Multi Function Professional Puncher-C1 ⁵	Paper Weight	
	Punching:	20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm)
	Creasing:	110 lb. Text to 110 lb. Cover (157 gsm to 300 gsm)
	Paper Size	
	Punching:	12" x 18", 11" x 17", Letter, Legal, Letter-R, Statement
	Creasing:	Letter-R, 11" x 17", 12" x 18", 13" x 19"
Die Set	Patterns:	Loose-Leaf 3-Hole/5-Hole, Velo Bind 11-Hole, Plastic Comb 19-Hole, Twin Loop 21-Hole/32-Hole, Color Coil 44-Hole, Crease
	Power Supply:	115 V, 60 Hz, 3.8 A
	Weight:	225 lb.
	Dimensions:	17.5" x 31.3" x 40.9" (WxDxH)

GBC eWire Pro ⁶	Bound Book Size: ¹	7 to 100 Sheets
	Paper Size:	Letter, 5.5" x 8.5", Tab Stock
	Paper Weight:	20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm)
	Wire Choices:	1/4", 5/16", 3/8", 7/16", 1/2", 9/16"
	Stack Capacity:	Up to 35 Books
	Power Supply:	115 V, 60 Hz, 2.8 A
Weight:		500 lb.
	Dimensions:	42.5" x 35.9" x 31.7" (WxDxH)

Finishing Accessories (Continued):

Perfect Binder-F1⁵	Finished Book Size:	5.4" x 8" to 8.5" x 11.7"
	Book Thickness: ¹	10 to 200 Sheets (Up to 0.98")
	Body Paper Weight:	14 lb. Bond to 43 lb. Bond (52 gsm to 163 gsm)
	Cover Paper Weight:	24 lb. Bond to 110 lb. Cover (90 gsm to 300 gsm)
	Trimming Method:	3-Side Cut/1-Side Cut/No Cut
	Trim Range	
	Top/Bottom:	0.26" to 1.6"
	Side:	0.26" to 1.95"
	Options:	Perfect Binder Continuous Kit-B1
	Power Source:	208 V, 60 Hz, 3 A
High Capacity Stacker-J1	Weight:	679 lb.
	Dimensions:	36.3" x 31.1" x 51.2" (WxDxH)
	Stack Capacity: ¹	Up to 6,000 Sheets
	Top Tray Capacity: ¹	Up to 200 Sheets
	Paper Size:	5.5" x 7.2" to 13" x 19.2"
	Paper Weight:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Options:	PowerLift
Plockmatic Multi Purpose Stacker XL⁷	Power Source:	100 – 240 V, 50/60 Hz, 2.5 A
	Weight:	265 lb.
	Dimensions:	35.4" x 29.3" x 44.9" (WxDxH)
	Stack Height	
	Sheets < 28.1":	Up to 11.8"
	Sheets > 28.1":	Up to 5.5"
	Paper Size:	8.3" x 8.3" to 13" x 30"
Paper Folding Unit-K1⁸	Paper Weight:	
	Up to 18":	21 lb. Bond to 150 lb. Cover (80 gsm to 400 gsm)
	Up to 27.5":	80 lb. Text to 110 lb. Cover (120 gsm to 300 gsm)
	Up to 30":	100 lb. Text to 110 lb. Cover (150 gsm to 300 gsm)
	Power Source:	100 – 240 V, 50/60 Hz, 2 A
	Weight:	168 lb.
	Dimensions:	35.4" x 29.5" x 41.7" (WxDxH)
Paper Folding Unit-K1⁸	Double Parallel Fold:	Legal, Letter-R
	C/Accordion Fold:	Letter-R
	Z-Fold:	Letter-R, 11" x 17"
	Paper Weight:	14 lb. Bond to 28 lb. Bond (52 gsm to 105 gsm)
	Power Source:	From Finisher
	Weight:	157 lb.
	Dimensions:	13.2" x 31.2" x 46.9" (WxDxH)

Staple Finisher-AF1/Booklet Finisher-AF1	Tray Capacity ¹	
	Top Tray:	Up to 1,000 Sheets
	Lower Tray:	Up to 4,000 Sheets
	Paper Weight	
	Stacking:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Corner Stapling:	14 lb. Bond to 120 lb. Cover (52 gsm to 325 gsm)
	Booklet-Making:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Staple Positions:	Corner, Double-Side
	Paper Size	
	Stapling:	7.2" x 8.3" to 11.7" x 17"
Long Sheet Feeding and Catch Tray-D1⁸	Saddle Finisher:	8.3" x 11" to 13" x 19.2"
	Stapling Capacity ¹	
	Corner/Double Side:	Up to 100 Sheets
	Saddle-Stitch:	Up to 25 Sheets
	V-Fold:	Up to 5 Sheets without Stitch
	Power Source:	120 – 240 V, 50/60 Hz, 8 A
	Weight	
	Staple Finisher:	287 lb.
	Booklet Finisher:	397 lb.
	Dimensions:	31.5" x 31.2" x 48.8" (WxDxH)
Long Sheet Catch Tray XL-B1⁸	Stack Capacity: ¹	100 Sheets
	Paper Size:	4" x 5.83" to 13" x 30"
	Stack Capacity ¹	
Puncher Unit-BS1⁸	Up to 30":	Up to 300 Sheets
	Up to 51.2":	Up to 10 Sheets
	Paper Size:	4" x 5.83" to 13" x 51.2"
	Paper Sizes	
	2-Hole:	Legal, Letter-R, Custom Size (7.2" x 7.2" to 11.7" x 17")
DFD Adapter and Finisher Bridge-B1⁸	3-Hole:	11" x 17", Letter, Executive-R, Custom Size (9.5" x 7.2" to 11.7" x 17")
	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Punch Waste Capacity:	Up to 6,000 Sheets
	Power Supply:	From the Finisher
	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
Booklet Trimmer-G1⁸	Supported Finishing:	Plockmatic BLM50/35 Plockmatic BLM5000 Series Plockmatic Multi Purpose Stacker
	Weight:	168 lb.
	Dimensions:	35.8" x 29.3" x 46.9" (WxDxH)
	Margin Trimming:	Front-edge Trim
	Trim Amount:	2 mm to 28 mm
Booklet Trimmer-G1⁸	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Power Supply:	From the Finisher
	Weight:	392 lb.
	Dimensions:	82.5" x 31.1" x 41" (WxDxH)

Finishing Accessories (Continued):

Two-Knife Trimmer and Conveyor Set⁹	Margin Trimming:	Top and Bottom
	Trim Amount:	2 mm to 15 mm
	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Power Supply:	120 V, 50/60 Hz, 2.5 A
	Weight:	320 lb.
	Dimensions:	21.1" x 30.3" D x 41" (WxDxH)
SDD Square-Fold Booklet-Maker⁹	Booklet Capacity:¹	Up to 25 Sheets
	Booklet Input Size:	5.5"x 8.27" to 9.6" x 12.6"
	Paper Weight:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	Power Supply:	120 V, 60 Hz, 15 A
	Weight:	154 lb.
	Dimensions:	37.6" x 23.4" x 47" (WxDxH)
SDD SFM7804 Two-Knife Trim Set⁹	Booklet Capacity:¹	Up to 25 Sheets
	Booklet Input Size:	5.5"x 8.27" to 9.6" x 12.6"
	Paper Weight:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	Trim Amount:	0.08" to 2"
	Power Supply:	120 V, 60 Hz, 15 A
	Weight:	545 lb.
	Dimensions:	65.2" x 27.6" x 52.5" (WxDxH)
Plockmatic BLM50/35 Professional Booklet-Maker⁷	Booklet Size:¹	Up to 35/50 Sheets
	Paper Size:	8.1" x 10.8" to 12.6" x 18"
	Paper Weight	Uncoated: 16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
		Coated: 28 lb. Bond to 110 lb. Cover (105 gsm to 300 gsm)
	Trim Amount	
	Face: ¹⁰	0.039" to .63"
	Top/Bottom: ¹¹	0.2" to 1.18"
	Paper Rotating:¹¹	8.1" x 10.9" to 9.1" x 12.7"
	Power Supply:¹²	100-230 V, 50/60 Hz
	Weight:¹²	441 lb.
	Dimensions:¹²	57.8" x 28.8" x 41.4" (WxDxH)

Plockmatic BLM5000 Series Professional Booklet-Maker⁷	Booklet Size:¹	Up to 35/50 Sheets
	Paper Size	5035/5050: 8.1" x 10.8" to 12.6" x 18"
		5035s/5050s: 4.72" x 8.3" to 12.6" x 18"
	Paper Weight:	17 lb. Bond to 130 lb. Cover (64 gsm to 350 gsm)
	Trim Amount	
	Face:	0.0394" to .63"
	Top/Bottom: ¹¹	0.2" to 1.18"
	Paper Rotating:¹¹	8.1" x 10.9" to 9.1" x 12.7"
	Power Supply:¹²	100-240 V, 50/60 Hz
	Weight:¹³	5035/5050: 418 lb. 5035s/5050s: 474 lb.
	Dimensions:¹³	28.3" x 29.9" x 41.3" (WxDxH)

Print Servers

PRISMAsync Print Server	System Software:	Version 10
	CPU:	Intel® Core i7 4770S @ 3.1 GHz
	Memory:	16 GB
	Hard Drive:	1.5 TB
	OS:	Windows® 10
	Standard:	Scheduler, DocBox, G7 Calibration, Page Programmer, Remote Manager, PRISMAlytics Dashboard, Automated Workflows, Multiple Queues, Remote Control
	Optional:	Advanced Imposition, DP Link
imagePRESS Server D3000 V2	Fiery System:	FS600 Pro
	CPU:	Intel® Core i7-8700 Processor
	Memory:	16 GB
	Hard Drive:	256 GB SSD + 1 TB
	OS:	Windows® 10
	Standard:	Fiery® Hot Folders, Virtual Printers, Unity Display, Fiery JDF, Fiery Command WorkStation 6, Paper Catalog, Fiery Spot-On, Fiery Remote Scan, Media Librarian
	Optional:	Graphic Arts Pro Package, Fiery JobMaster, Color Profiler Suite, Fiery JobFlow, Operator Attention Light, Removable HDD, Integrated Interface, and Stand-NX GL, Fiery High Security Kit

¹ Based on 20 lb. Bond.

² Envelope Attachment Kit required.

³ POD Deck Lite-XL or Long Sheet Feed and Catch Tray-B1 required.

⁴ Multi Drawer Paper Deck-E1 or POD Deck Lite-C1 required.

⁵ Staple/Booklet Finisher-AFI or High Capacity Stacker-J1 required.

⁶ Multi Function Professional Puncher-C1 required.

⁷ High Capacity Stacker-J1 with DFD+ Interface Kit or DFD Adapter and Finisher Bridge-B1 required.

⁸ Staple/Booklet Finisher-AFI required.

⁹ Booklet Trimmer-K1 required.

¹⁰ Optional trimmer module required.

¹¹ Optional RCT module required.

¹² Specification is only for booklet maker module.

¹³ Specification is only for booklet maker and finishing module.

Canon

As an ENERGY STAR® Partner, Canon U.S.A., Inc. qualified this model as meeting the ENERGY STAR® energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon and imagePRESS are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. PRISMA is a registered trademark of Canon Production Printing Netherlands B.V. All other referenced product names and marks are trademarks of their respective owners. Some printer output images may be simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors. Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims on unauthorized copying.

©2025 Canon U.S.A., Inc. All rights reserved.



usa.canon.com/production



07/25-2414-13849