

Product Specifications

Marking Engine

Technology	Electrophotography			
Print Resolution	2400 x 2400 dpi			
Print Speed	V900	V800	V700	
8.5" x 11":	Up to 90 ipm	Up to 81 ipm	Up to 71 ipm	
11" × 17":	Up to 45 ipm	Up to 40 ipm	Up to 35 ipm	
12" x 18":	Up to 42 ipm	Up to 40 ipm	Up to 35 ipm	
13" x 19":	Up to 40 ipm	Up to 38 ipm	Up to 33 ipm	
13" x 30":	Up to 23 ipm	Up to 22 ipm	Up to 19 ipm	
Paper Size	Standard:	3.94" x 5.83" to 13" x 19.2"		
	Optional:	5.5" x 5.83" to 13" x 51.2"		
Paper Capacity ¹	Standard:	Up to 1,650 Sheets		
	Maximum:	Up to 10,400 Sheets		
Paper Weight	Standard:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)		
	Optional:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)		
	Envelopes: ²	No. 10 (COM10), ISO-C5, DL, Monarch, 6" x 9", 9" x 12", 10" x 13"		
Long Sheets ³	Duplex:	Up to 13" x 30"		
	Simplex:	Up to 13" x 51.2"		
Automatic	Paper Size:	Up to 13" x 30" ³		
Duplexing	Paper Weight:	Up to 130 lb. Cover (350 gsm) ⁴	

Power Source	200-240 V, 50/60 Hz, 20 A		
Weight	With Canon UI:	573 lb.	
	With PRISMAsync UI:	592 lb.	
Dimensions	With Canon UI:	35.7" W x 34.3" D x 40.9" H	
	With PRISMAsync UI:	59" W x 34.3" D x 54.5" H	

Input Accessories

Color Image	Image Sensor:	CCD		
Reader-P1	Scan Speed:	Up to 270 ipm (Letter, 300 dpi)		
	Document Size:	2.8" x 5.5" to 12" x 24.8"		
	Resolution:	Up to 600 x 600 dpi, 256 Gradations		
	Tray Capacity:1	Up to 250 Sheets		
	Weight:	51 lb.		
	Dimensions:	25.7" W x 23.3" D x 8.6" (WxDxH)		
Multi-Drawer	Paper Capacity:1	Up to 5,000 Sheets		
Paper Deck-E1	Paper Size:	5.5" x 7.2" to 13" x 19.2"		
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)		
	Power Source:	110 – 127 V, 60 Hz, 7 A		
	Weight:	392 lb.		
	Dimensions:	38" x 31.5" x 42.5" (WxDxH)		
POD Deck	Paper Capacity: ¹	Up to 3,500 Sheets		
Lite-C1	Paper Size:	5.5" x 7.2" to 13" x 19.2"		
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)		
	Power Source:	120 – 127 V, 60 Hz, 2.2 A		
	Weight:	168 lb.		
	Dimensions:	24.9" x 27" x 22.6" (WxDxH)		

input Accessories ((Continued).				
POD Deck Lite XL-A2	Paper Capacity ¹ Up to 13" x 19.2":	Up to 3,500 Sheets		Mode:	Log Only Mode, Purge and Recovery Mode
	Up to 13" x 30":	Up to 1,000 Sheets		Inspection Location	•
	Paper Size:	5.5" x 7.2" to 13" x 30"		Intensity Level:	9 Levels
	Paper Weight:			Objects:	Position Gap, Dirt, Streaks
	Up to 13" x 19.2":	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)		Auto Recovery: Purge Unit:	Yes (Purge and Recovery Mode Only) High Capacity Stacker-J1
	Up to 13" x 30":	17 lb. Bond to 110 lb. Cover		Power Supply:	120 - 240 V, 50/60 Hz, 1.4 A
	op to 12 × 20 ·	(64 gsm to 300 gsm)		Weight:	109 lb.
	Power Source:	100-127 V, 60 Hz, 7 A		Dimensions:	9.8" x 31.2" x 40.9" (WxDxH)
	Weight:	249 lb.			, ,
	Dimensions:	40.2" x 27" x 22.6" (WxDxH)	Document	Tray Capacity ¹	
			Insertion	Upper Tray:	Up to 200 Sheets
Stack	Paper Capacity: ¹	Up to 250 Sheets	Unit-R1 ⁵	Lower Tray:	Up to 200 Sheets
Bypass-D1	Paper Size:	3.94" x 5.83" to 13" x 19.2"		Paper Weight:	14 lb. Bond to 130 lb. Cover
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)		Paper Size:	(52 gsm to 350 gsm) 7.2" x 7.2" to 13" x 19.2"
	Weight:	3 lb.		Power Supply:	100 – 240 V, 50/60 Hz, 1.0 A
	Dimensions:	18" x 15.1" x 2.9" (WxDxH)		Weight:	135 lb.
Long Sheet	Paper Capacity:	Up to 1 Sheet		Dimensions:	29.4" x 31.2" x 55.4" (WxDxH)
Feeding	Paper Size:	4" x 5.83" to 13" x 51.2"	Static Eliminator-A1 ⁵	Paper Size:	3.9" x 5.8" to 13" x 51.2"
and Catch Tray-B1	Paper Weight:	17 lb. Bond to 130 lb. Cover (64 gsm to 350 gsm) ⁵		Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
nay bi	Weight:	2 lb.		Power Supply:	100-240 V, 50/60 Hz, 1 A
	Dimensions:	85.6" x 56.1" x 56.1" (WxDxH)		Weight:	110 lb.
Dime	Difficusions.	05.0 x 50.1 x 50.1 (WXDXII)		Dimensions:	9.8" x 31.2" x 41" (WxDxH)
Finishing Ac	cessories		Multi	Paper Weight	7.0 X 71.2 X 41 (WXDXII)
Copy Tray-R2	Paper Capacity: ¹	Up to 250 Sheets	Function	Punching:	20 lb. Bond to 110 lb. Cover
	Paper Weight:	14 lb. Bond to 130 lb. Cover	Professional	J	(75 gsm to 300 gsm)
		(52 gsm to 350 gsm)	Puncher-C1 ⁵	Creasing:	110 lb. Text to 110 lb. Cover
	Paper Size:	4" x 5.83" to 13" x 19.2"			(162 gsm to 300 gsm)
	Weight:	3 lb.		Paper Size	Laura D. Laura Laura 1111 - 1711 1011 - 101
	Dimensions:	16.6" x 15" x 6.8" (WxDxH)		Punching (Single): Punching (Double):	Letter-R, Letter, Legal, 11" x 17", 12" x 18' Letter-R, Legal, 11" x 17", 12" x 18"
Sansing	Tasks:	Front-to-Back Alignment, Color Accuracy		Creasing:	Letter-R, 11" x 17", 12" x 18", 13" x 19"
Sensing Unit-B1 ⁵	idana.	Check, Cross Shade Adjustment, Secondary Transfer Adjustment		Die Set Patterns:	Loose Leaf 3-Hole/5-Hole, Velo Bind
	DFE:	PRISMAsync print server V8.3 or Later; imagePRESS Server N500/P400 or Later			11-Hole, Plastic Comb 19-Hole, Twin Loop 21-Hole/32-Hole, Color Coil 44-Hole, Crease
	Paper Weight:	14 lb. Bond to 130 lb. Cover		Power Supply:	115 V, 60 Hz, 3.8 A
		(52 gsm to 350 gsm)		Weight:	225 lb.
	Paper Size:	5.5" x 5.83" to 13" x 30"			
	Power Supply:	100 – 240 V, 50/60 Hz, 2.5 A		Dimensions:	17.5" x 31.3" x 40.9" (WxDxH)
	Weight:	222 lb.			
	Dimensions:	20.3" x 29.5" x 48.3" (WxDxH)	GBC	Bound Book Size:1	15 to 100 Sheets
			eWire Pro ^{5,6}	Paper Size:	Letter, 5.5" x 8.5", Tab Stock
Inspection Unit-A1 ⁵	Paper Type: Paper Weight:	Plain Paper, Coated Paper 14 lb. Bond to 130 lb. Cover		Paper Weight:	20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm)
	i apei Weigiit.	(52 gsm to 350 gsm)		Wire Choices:	1/4", 5/16", 3/8", 7/16", 1/2", 9/16"
	Paper Size:	3.9" x 7.2" to 11.9" x 19.2"		Stack Capacity:	Up to 35 Books
	Detection Size:	0.2mm x .02mm to 1.4 mm x 1.4 mm		Infeed:	Multi Function Professional Puncher-B1
	Scanning Width:	Up to 11.9"		Power Supply:	115 V, 60 Hz, 2.8A
	Inspection			Weight:	500 lb.
	Workstation	OS: Windows [®] 10 Pro		Dimensions:	42.5" x 35.9" x 31.7" (WxDxH)
	mspection 1001	OS. WITHOUS TO FID		PilifelialOlla.	TL. 7 7 7 7 7 7 1.1 (VVADATI)

, mioriming , toooboon.	ies (continuea).				
Perfect Binder-F1 ^{5,6}	Finished Book Size:	5.4" x 7.99" to 8.5" x 11.69"	_	Corner Stapling: Booklet-	14 lb. Bond to 140 lb. Index (52 gsm to 256 gsm) 14 lb. Bond to 140 lb. Index
	Book Thickness:1	10 to 200 Sheets (Up to 0.98")		Making:	(52 gsm to 256 gsm)
	Body Paper	14 lb. Bond to 43 lb. Bond		Staple Positions:	Corner, Double-Side, Eco
	Weight:	(52 gsm to 163 gsm)	_	Paper Size	
	Cover Paper Weight:	24 lb. Bond to 110 lb. Cover (90 gsm to 300 gsm)		Stapling:	Executive, Letter-R, Letter, Legal, 11" x
	Trimming Method:	3-Side Cut/1-Side Cut/No Cut		Saddle Finisher:	7.7" x 10.6" to 12" x 18"
	Trim Range			Stapling Capacity ¹	
	Top/Bottom:	0.26" to 1.56"		Corner/Double:	Up to 65 Sheets
	Side:	0.26" to 1.95"		Eco-Stitch:	Up to 6 Sheets
	Options:	Perfect Binder Continuous Kit-B1		Saddle-Stitch:	Up to 20 Sheets
	Power Source:	208 V, 60 Hz, 3 A		V-Fold:	Up to 3 Sheets without Stitch
	Weight:	679 lb.		Power Source:	From the Main Unit
	Dimensions:	36.3" x 31.1" x 51.3" (WxDxH)	_	Weight	Trom the Main Offic
High	Stack Capacity: 1	Up to 6,000 Sheets		Staple Finisher:	79 lb.
Capacity	Top Tray Capacity:1	Up to 200 Sheets	_	Booklet Finisher:	
Stacker-J1	Paper Size:	5.5" x 7.2" to 13" x 19.2"			132 lb.
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)	0/7111	Dimensions:	20.8" x 24.5" x 43.3" (WxDxH) 14 lb. Bond to 110 lb. Cover
	Options:	PowerLift	2/3 Hole Puncher	Paper Weight:	(52 gsm to 300 gsm)
	Power Source:	90-264 V AC, 47-63 Hz, 10 A	Unit-A1 ¹⁰	Paper Sizes:	Letter-R
	Weight:	265 lb.		2-Hole:	Legal, Letter-R, Custom Size
	Dimensions:	35.4" x 29.3" x 44.9" (WxDxH)			(7.2" x 7.2" to 11.8" x 17")
Plockmatic	Stack Height		_	3-Hole:	11" x 17", Letter, Executive-R, Custom Size (9.5" x 7.2" to 11.8" x 17'
Multi Purpose	Sheets < 28.1":	Up to 11.8"		Power Supply:	From Finisher
Stacker XL ⁷	Sheets > 28.1":	Up to 5.5"			rioni rinisher
	Paper Size:	8.3" x 8.3" to 13" x 30"	Staple Finisher-AG1/	Tray Capacity ¹	H . 1000 Cl
	Paper Weight:		Booklet	Top Tray: Lower Tray:	Up to 1,000 Sheets Up to 4,000 Sheets
	Up to 18":	21 lb. Bond to 130 lb. Cover (80 gsm to 350 gsm)	Finisher-AG1	,	Continuous by Belt
	Up to 27.5":	80 lb. Text to 110 lb. Cover (120 gsm to 300 gsm		Paper Weight Stacking:	14 lb. Bond to 130 lb. Cover
	Up to 30":	100 lb. Text to 110 lb. Cover (150 gsm to 300 gsm)		Corner	(52 gsm to 350 gsm) 14 lb. Bond to 110 lb. Cover
	Power Source:	100 – 230 V ± 10%, 50-60Hz		Stapling: Booklet- Making: Staple Positions: Paper Size	(52 gsm to 300 gsm)
	Weight:	198 lb.			14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Dimensions:	35.4" x 29.5" x 41.7" (WxDxH)			Corner, Double-Side, Saddle-Stitch
	Davida Davidal Fald	Land Latter D	_		Corner, Double Side, Saddle Stitch
Paper Folding Unit-K1 ⁸	Double Parallel Fold:			Stapling:	8.3' x 11' to 11.7' x 17'
OIIIC-IXI	C/Accordion Fold:	Letter-R	_	Saddle Finisher:	8.27' x 11' to 13' x 19.2'
	Z-Fold:	Letter-R, 11" x 17"			0.27 X II TO 13 X 19.2
	Paper Weight:	14 lb. Bond to 28 lb. Bond (52 gsm to 105 gsm)	_	Stapling Capacity ¹ Corner/Double:	Up to 100 Sheets
	Power Source:	From Finisher	_	Saddle-Stitch:	Up to 25 Sheets
	Weight:	157 lb.		V-Fold:	Up to 5 Sheets without Stitch
	Dimensions:	13.2" x 31.2" x 46.9" (WxDxH)	<u> </u>	Power Source:	120-127 V, 60 Hz, 8 A
Staple	Tray Capacity ¹				120-121 V, 00 FIZ, 0 A
Finisher-AC1/ Booklet Finisher-AC2 ⁹	Top Tray:	Up to 250 Sheets		Weight Staple Finisher:	287 lb.
	Middle Tray: Lower Tray:	Up to 250 Sheets Up to 3,000 Sheets		•	
I IIIISHEL ACZ	,	Up to 3,000 Sneets Up to 30 Booklets		Booklet Finisher:	397 lb.
	Paper Weight	op to 20 bookiets		Dimensions:	31.5" W x 31.2" D x 48.8" H
	Stacking:	14 lb. Bond to 130 lb. Cover			

(52 gsm to 350 gsm)

SDD PTM7600 ¹¹	Included Modules:	Press Trim Module PTM7006	Booklet Trimmer-G1 ¹³	Margin Trimming:	Front-edge Trim
		Conveyor Belt Stacker CBS6060		Trim Amount:	0.08" to 1.1"
	Input Book Size: Book Thickness	8.27" x 11" to 9.6" x 12.6" Up to 25 sheets ¹		Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Paper Weight:	16 lb. Bond to 110 lb. Cover		Power Supply:	From the Finisher
	r aper weight.	(60 gsm to 300 gsm)		Weight:	392 lb.
	Face Trim Amount:	.08" x .98"		Dimensions:	82.5" x 31.1" x 41" (WxDxH)
	Belt Stacker Length:	23.6"			
	Power Source:	2100-240 V, 2.5 A	Trimmer and	Margin Trimming:	Top and Bottom
	Weight:	203 lb.		Trim Amount:	0.08" to 0.59"
	Dimensions:	51.2" x 23.6" x 20.5" (WxDxH)		Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
SDD	Included Modules:	Press Trim Module PTM7006 SquareFold Module 7004 Conveyor Belt Stacker CBS6060		Power Supply:	120-127 V AC, 50/60 Hz, 4 A
PTM7600				Weight:	320 lb.
SFM ¹¹	Input Book Size:	8.27" x 11" to 9.6" x 12.6"		Dimensions:	21.1" x 30.3" x 41" (WxDxH)
	Book Thickness	Up to 25 sheets ¹	SDD	Booklet	
	Paper Weight:	16 lb. Bond to 110 lb. Cover	Square-Fold	Capacity: ¹	Up to 25 Sheets
		(60 gsm to 300 gsm)	Booklet-Maker ¹⁴	Booklet	
	Face Trim Amount:	.08" x .98"		Input Size:	5.5" x 8.27" to 9.6" x 12.6"
	Belt Stacker Length:	23.6"		Booklet	4.7111 . 7.0711 0.711 . 10.711
	Power Source:	2100-240 V, 2.5 A		Output Size:	4.71" x 7.87" to 9.6" x 12.6"
	Weight:	287 lb.		Paper Weight:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	Dimensions:	75.6" x 23.6" x 20.5" (WxDxH)		Power Supply:	120 V, 60 Hz, 15 A
Long Sheet	Stack Capacity:1	Up to 100 Sheets		Weight:	170 lb.
Catch Tray-C1 ¹²	Paper Size:	4" x 5.83" to 13" x 30"		Dimensions:	37.6" x 23.4" x 47" (WxDxH)
Long Sheet	Stack Capacity ¹				
Catch Tray	Up to 30":	Up to 300 Sheets	SDD SFM7804 Two Knife Trim Set ¹⁴	Booklet Capacity: ¹	Up to 25 Sheets
XL-B1 ¹³	Up to 51.2":	Up to 10 Sheets		Booklet	op to 27 Sheets
	Paper Size:	3.93" x 5.83" to 13" x 51.2"		Input Size:	4.88" x 5.51" to 9.6" x 12.6"
Puncher	Paper Sizes			Paper Weight:	16 lb. Bond to 110 lb. Cover
Unit-BS1 ¹³	2-Hole:	Legal, Letter-R, Custom Size (7.2" x 7.2" to 11.8" x 17")			(60 gsm to 300 gsm)
	3-Hole:	11" x 17", Letter, Executive-R,		Trim Amount:	0.08" to 2"
		Custom Size (9.5" x 7.2" to 11.8" x 17")		Power Supply:	120 V, 60 Hz, 15 A
	Paper Weight:	14 lb. Bond to 110 lb. Cover		Weight:	545 lb.
		(52 gsm to 300 gsm)		Dimensions:	66.1" x 27.6" x 52.5" (WxDxH)
	Punch Waste Capacity: Up to 6,000 Sheets				
	Power Supply:	From the Finisher	Plockmatic BLM50/35	Booklet Size:1	Up to 35/50 Sheets
	Supported	Plockmatic BLM50/35 Professional		Paper Size:	8.1" x 10.8" to 12.6" x 18.1"
	Finishing:	Booklet Maker, Plockmatic Multi			0.1 A 10.0 (0 12.0 A 10.1
	Da mulius es e	Purpose Stacker	Professional Booklet-Maker ^{6,}	Uncoated:	16 lb. Bond to 110 lb. Cover
	Requirements:	Staple/Booklet Finisher-AG1			(60 gsm to 300 gsm)
	Weight:	7 lb.		Coated:	28 lb. Bond to 110 lb. Cover (105 gsm to 300 gsm)
DFD Adapter and Finisher	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)		Trim Amount Face:16	0.04" to 0.63"
Bridge-B1 ¹³	Supported Finishing:	Plockmatic BLM50/35, Plockmatic Multi Purpose Stacker		Top/Bottom: ¹⁷	0.196" to 1.18"
	Weight:	198 lb.		Paper Rotating: ¹⁷	8.1" x 10.9" to 9.1" x 12.7"
	Dimensions:	35.4" x 29.3" x 40.9" (WxDxH)		Power Supply: ¹⁸	100-230 V, 50/60 Hz
	2	A 27.2 A 10.7 (WADAII)		Weight ^{:18}	441 lb.
				Dimensions: ¹⁸	57.8" x 28.8" x 41.4" (WxDxH)

Print Servers

imagePRESS	PDL:	UFR II, PS, PCL 5e/6		
Printer Kit-J1	Memory:	4 GB		
	Hard Drive:	1TB		
PRISMAsync Print Server	System Software:	Mark 10		
	CPU:	Intel® Core i5 8500		
	Memory:	8 GB		
	Hard Drive:	1.5 TB		
	OS:	Windows® 10, LTSC		
	Standard:	Scheduler, DocBox, G7 Calibration, Page Programmer, Remote Manager, PRISMAlytics Dashboard, Automated Workflows, Multiple Queues, Remote Control		
	Optional:	E-Shredding		
PRISMAsync	System Software:	Mark 10		
Print Server LP	CPU:	Intel® Core i5 8500		
	Memory:	8 GB		
	Hard Drive:	1.5 TB		
	OS:	Windows® 10, LTSC		
	Standard:	Multiple Queues, Scheduler, Remote Manager, Color Presets, Pixel Precise Preview, Spot Color Editing, Calibration, Realistic Preview, Digital Moire		
	Optional:	Advanced Color Management, Power-Up Package, E-Shredding		

imagePRESS	Fiery System:	FS500 Pro
Server N500	CPU:	Intel Core i5-8500 3.2 GHz up to 4.6 GHz W/ Turbo
	Memory:	8 GB
	Hard Drive:	1.2 TB
	OS:	Windows 10
	Standard:	Fiery Hot Folders, Virtual Printers, Unity Display, Fiery JDF, Fiery Command Workstation 6, Paper Catalog, Fiery Spot-On, Fiery Remote Scan, Media Librarian
	Optional:	Impose/Compose, Graphic Arts Pro Package, Job Master, JobFlow
imagePRESS	Fiery System:	FS500
Server P400	CPU:	Intel Pentium G5400, 3.7 GHz
	Memory:	8 GB
	Hard Drive:	500 GB
	OS:	Linux
	Standard:	Fiery Command WorkStation 6, Paper Catalog, Fiery Spot On, Fiery Remote Scan, Hot Folders License
	Optional:	Impose/Compose, Automation Package, ColorRight Package, Job Master, JobFlow

To view detailed specifications, please consult the Customer Expectations Document.

- ¹ Based on 20 lb. Bond.
- ² Envelope Attachment Kit required.
- $^{\rm 3}$ POD Deck Lite-XL or Long Sheet Feed Tray-B1 required.
- ⁴ Stocks longer than 19.2" support up to 110 lb. Cover (300 gsm).
- 5 Staple/Booklet Finisher-AG1 or
- High Capacity Stacker-J1 required. ⁶ Not available for the imagePRESS V700.
- ⁷ High Capacity Stacker-J1 with DFD+ Interface Kit Set or DFD Adapter and Finisher Bridge-B1 required.
- 8 Staple/Booklet Finisher-AG1 required.
- 9 Not available for the imagePRESS V900.

- $^{\rm 10}$ Staple Finisher-AC1 or Booklet Finisher-AC2 required.
- ¹¹ Booklet Finisher AG1 required.
- ¹² Copy Tray-R2, Staple/Booklet Finisher-AG1 required.
- ¹³ Staple/Booklet Finisher-AG1 required.
- ¹⁴ Booklet Trimmer-G1 required.
- ¹⁵ High Capacity Stacker-J1 or DFD Adapter and Finisher Bridge-A2 required.
- ¹⁶ Optional trimmer module required.
- $^{\rm 17}$ Optional rotator RCT module required.
- ¹⁸ Specification is only for booklet maker module.



















1-844-50-CANON | usa.canon.com/business

As an ENERGY STAR® Partner, Canon U.S.A., Inc. qualified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon and imagePRESS are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. PRISMA is a registered trademark of Canon Production Printing Netherlands B.V. All other referenced product names and marks are trademarks of their respective owners. Some printer output images may be simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims on unauthorized copying.

©2025 Canon U.S.A., Inc. All rights reserved. 01/25-0128-9718