



# imagePRESS V900/V800/V700 COLOR PRODUCTION DIGITAL PRESS



imagePRESS V900 shown with optional accessories.

## Product Specifications

### Marking Engine

<b>Technology</b>	Electrophotography		
<b>Print Resolution</b>	2400 x 2400 dpi		
<b>Print Speed</b>	<b>V900</b>	<b>V800</b>	<b>V700</b>
8.5" x 11":	Up to 90 ipm	Up to 81 ipm	Up to 71 ipm
11" x 17":	Up to 45 ipm	Up to 40 ipm	Up to 35 ipm
12" x 18":	Up to 42 ipm	Up to 40 ipm	Up to 35 ipm
13" x 19":	Up to 40 ipm	Up to 38 ipm	Up to 33 ipm
13" x 30":	Up to 23 ipm	Up to 22 ipm	Up to 19 ipm
<b>Paper Size</b>	<b>Standard:</b>	3.94" x 5.83" to 13" x 19.2"	
	<b>Optional:</b>	5.5" x 5.83" to 13" x 51.2"	
<b>Paper Capacity<sup>1</sup></b>	<b>Standard:</b>	Up to 1,650 Sheets	
	<b>Maximum:</b>	Up to 10,400 Sheets	
<b>Paper Weight</b>	<b>Standard:</b>	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)	
	<b>Optional:</b>	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)	
	<b>Envelopes:<sup>2</sup></b>	No. 10 (COM10), ISO-C5, DL, Monarch, 6" x 9", 9" x 12", 10" x 13"	
<b>Long Sheets<sup>3</sup></b>	<b>Duplex:</b>	Up to 13" x 30"	
	<b>Simplex:</b>	Up to 13" x 51.2"	
<b>Automatic Duplexing</b>	<b>Paper Size:</b>	Up to 13" x 30" <sup>3</sup>	
	<b>Paper Weight:</b>	Up to 130 lb. Cover (350 gsm) <sup>4</sup>	
<b>Power Source</b>	200-240 V, 50/60 Hz, 20 A		
<b>Weight</b>	<b>With Canon UI:</b>	573 lb.	
	<b>With PRISMAsync UI:</b>	592 lb.	
<b>Dimensions</b>	<b>With Canon UI:</b>	35.7" W x 34.3" D x 40.9" H	
	<b>With PRISMAsync UI:</b>	59" W x 34.3" D x 54.5" H	

### Input Accessories

<b>Color Image Reader-P1</b>	<b>Image Sensor:</b>	CCD
	<b>Scan Speed:</b>	Up to 270 ipm (Letter, 300 dpi)
	<b>Document Size:</b>	2.8" x 5.5" to 12" x 24.8"
	<b>Resolution:</b>	Up to 600 x 600 dpi, 256 Gradations
	<b>Tray Capacity:<sup>1</sup></b>	Up to 250 Sheets
	<b>Weight:</b>	51 lb.
	<b>Dimensions:</b>	25.7" W x 23.3" D x 8.6" (WxDxH)
<b>POD Deck-F1</b>	<b>Paper Capacity:<sup>1</sup></b>	Up to 5,000 Sheets
	<b>Paper Size:</b>	5.5" x 7.2" to 13" x 19.2"
	<b>Paper Weight:</b>	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	<b>Power Source:</b>	110 – 127 V, 60 Hz, 7 A
	<b>Weight:</b>	392 lb.
	<b>Dimensions:</b>	38" x 31.5" x 42.5" (WxDxH)
<b>Multi-Drawer Paper Deck-E1</b>	<b>Paper Capacity:<sup>1</sup></b>	Up to 5,000 Sheets
	<b>Paper Size:</b>	5.5" x 7.2" to 13" x 19.2"
	<b>Paper Weight:</b>	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	<b>Power Source:</b>	110 – 127 V, 60 Hz, 7 A
	<b>Weight:</b>	392 lb.
	<b>Dimensions:</b>	38" x 31.5" x 42.5" (WxDxH)
<b>POD Deck Lite-C1</b>	<b>Paper Capacity:<sup>1</sup></b>	Up to 3,500 Sheets
	<b>Paper Size:</b>	5.5" x 7.2" to 13" x 19.2"
	<b>Paper Weight:</b>	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	<b>Power Source:</b>	120 – 127 V, 60 Hz, 2.2 A
	<b>Weight:</b>	168 lb.
	<b>Dimensions:</b>	24.9" x 27" x 22.6" (WxDxH)

Input Accessories (Continued):

<b>POD Deck Lite XL-A2</b>	<b>Paper Capacity</b> <sup>1</sup>	Up to 13" x 19.2": Up to 3,500 Sheets Up to 13" x 30": Up to 1,000 Sheets
	<b>Paper Size:</b>	5.5" x 7.2" to 13" x 30"
	<b>Paper Weight:</b>	Up to 13" x 19.2": 14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm) Up to 13" x 30": 17 lb. Bond to 110 lb. Cover (64 gsm to 300 gsm)
	<b>Power Source:</b>	100-127 V, 60 Hz, 7 A
	<b>Weight:</b>	249 lb.
	<b>Dimensions:</b>	40.2" x 27" x 22.6" (WxDxH)

<b>Stack Bypass-D1</b>	<b>Paper Capacity</b> <sup>1</sup>	Up to 250 Sheets
	<b>Paper Size:</b>	3.94" x 5.83" to 13" x 19.2"
	<b>Paper Weight:</b>	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	<b>Weight:</b>	3 lb.
	<b>Dimensions:</b>	18" x 15.1" x 2.9" (WxDxH)

<b>Long Sheet Feeding and Catch Tray-B1</b>	<b>Paper Capacity:</b>	Up to 1 Sheet
	<b>Paper Size:</b>	4" x 5.83" to 13" x 51.2"
	<b>Paper Weight:</b>	17 lb. Bond to 130 lb. Cover (64 gsm to 350 gsm) <sup>5</sup>
	<b>Weight:</b>	2 lb.
	<b>Dimensions:</b>	85.6" x 56.1" x 56.1" (WxDxH)

## Finishing Accessories

<b>Copy Tray-R2</b>	<b>Paper Capacity</b> <sup>1</sup>	Up to 250 Sheets
	<b>Paper Weight:</b>	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	<b>Paper Size:</b>	4" x 5.83" to 13" x 19.2"
	<b>Weight:</b>	3 lb.
	<b>Dimensions:</b>	16.6" x 15" x 6.8" (WxDxH)

<b>Sensing Unit-B1<sup>5</sup></b>	<b>Tasks:</b>	Front-to-Back Alignment, Color Accuracy Check, Cross Shade Adjustment, Secondary Transfer Adjustment
	<b>DFE:</b>	PRISMAsync print server V8.3 or Later; imagePRESS Server N500/P400 or Later
	<b>Paper Weight:</b>	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	<b>Paper Size:</b>	5.5" x 5.83" to 13" x 30"
	<b>Power Supply:</b>	100 – 240 V, 50/60 Hz, 2.5 A
	<b>Weight:</b>	222 lb.
	<b>Dimensions:</b>	20.3" x 29.5" x 48.3" (WxDxH)

<b>Inspection Unit-A1<sup>5</sup></b>	<b>Paper Type:</b>	Plain Paper, Coated Paper
	<b>Paper Weight:</b>	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	<b>Paper Size:</b>	3.9" x 7.2" to 11.9" x 19.2"
	<b>Detection Size:</b>	0.2mm x .02mm to 1.4 mm x 1.4 mm
	<b>Scanning Width:</b>	Up to 11.9"
	<b>Inspection Workstation</b>	Inspection Tool OS: Windows® 10 Pro

<b>Mode:</b>	Log Only Mode, Purge and Recovery Mode
<b>Inspection Location:</b>	Up to 64 areas
<b>Intensity Level:</b>	9 Levels
<b>Objects:</b>	Position Gap, Dirt, Streaks
<b>Auto Recovery:</b>	Yes (Purge and Recovery Mode Only)
<b>Purge Unit:</b>	High Capacity Stacker-J1
<b>Power Supply:</b>	120 - 240 V, 50/60 Hz, 1.4 A
<b>Weight:</b>	109 lb.
<b>Dimensions:</b>	9.8" x 31.2" x 40.9" (WxDxH)

<b>Document Insertion Unit-R1<sup>5</sup></b>	<b>Tray Capacity</b> <sup>1</sup>	Upper Tray: Up to 200 Sheets Lower Tray: Up to 200 Sheets
	<b>Paper Weight:</b>	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	<b>Paper Size:</b>	7.2" x 7.2" to 13" x 19.2"
	<b>Power Supply:</b>	100 – 240 V, 50/60 Hz, 1.0 A
	<b>Weight:</b>	135 lb.
	<b>Dimensions:</b>	29.4" x 31.2" x 55.4" (WxDxH)

<b>Static Eliminator-A1<sup>5</sup></b>	<b>Paper Size:</b>	3.9" x 5.8" to 13" x 51.2"
	<b>Paper Weight:</b>	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	<b>Power Supply:</b>	100-240 V, 50/60 Hz, 1 A
	<b>Weight:</b>	110 lb.
	<b>Dimensions:</b>	9.8" x 31.2" x 41" (WxDxH)

<b>Multi Function Professional Puncher-C1<sup>5</sup></b>	<b>Paper Weight</b>	
	<b>Punching:</b>	20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm)
	<b>Creasing:</b>	110 lb. Text to 110 lb. Cover (162 gsm to 300 gsm)
	<b>Paper Size</b>	
	<b>Punching (Single):</b>	Letter-R, Letter, Legal, 11" x 17", 12" x 18"
	<b>Punching (Double):</b>	Letter-R, Legal, 11" x 17", 12" x 18"
	<b>Creasing:</b>	Letter-R, 11" x 17", 12" x 18", 13" x 19"
	<b>Die Set Patterns:</b>	Loose Leaf 3-Hole/5-Hole, Velo Bind 11-Hole, Plastic Comb 19-Hole, Twin Loop 21-Hole/32-Hole, Color Coil 44-Hole, Crease
	<b>Power Supply:</b>	115 V, 60 Hz, 3.8 A
	<b>Weight:</b>	225 lb.
<b>Dimensions:</b>	17.5" x 31.3" x 40.9" (WxDxH)	

<b>GBC eWire Pro<sup>5,6</sup></b>	<b>Bound Book Size</b> <sup>1</sup>	15 to 100 Sheets
	<b>Paper Size:</b>	Letter, 5.5" x 8.5", Tab Stock
	<b>Paper Weight:</b>	20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm)
	<b>Wire Choices:</b>	1/4", 5/16", 3/8", 7/16", 1/2", 9/16"
	<b>Stack Capacity:</b>	Up to 35 Books
	<b>Infeed:</b>	Multi Function Professional Puncher-B1
	<b>Power Supply:</b>	115 V, 60 Hz, 2.8A
	<b>Weight:</b>	500 lb.
<b>Dimensions:</b>	42.5" x 35.9" x 31.7" (WxDxH)	

Finishing Accessories (Continued):

<b>Perfect Binder-F1</b> <sup>5,6</sup>	<b>Finished Book Size:</b>	5.4" x 7.99" to 8.5" x 11.69"
	<b>Book Thickness:</b> <sup>1</sup>	10 to 200 Sheets (Up to 0.98")
	<b>Body Paper Weight:</b>	14 lb. Bond to 43 lb. Bond (52 gsm to 163 gsm)
	<b>Cover Paper Weight:</b>	24 lb. Bond to 110 lb. Cover (90 gsm to 300 gsm)
	<b>Trimming Method:</b>	3-Side Cut/1-Side Cut/No Cut
	<b>Trim Range</b>	
	Top/Bottom:	0.26" to 1.56"
	Side:	0.26" to 1.95"
	<b>Options:</b>	Perfect Binder Continuous Kit-BI
	<b>Power Source:</b>	208 V, 60 Hz, 3 A
<b>Weight:</b>	679 lb.	
<b>Dimensions:</b>	36.3" x 31.1" x 51.3" (WxDxH)	

<b>High Capacity Stacker-J1</b>	<b>Stack Capacity:</b> <sup>1</sup>	Up to 6,000 Sheets
	<b>Top Tray Capacity:</b> <sup>1</sup>	Up to 200 Sheets
	<b>Paper Size:</b>	5.5" x 7.2" to 13" x 19.2"
	<b>Paper Weight:</b>	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	<b>Options:</b>	PowerLift
	<b>Power Source:</b>	90-264 V AC, 47-63 Hz, 10 A
	<b>Weight:</b>	265 lb.
<b>Dimensions:</b>	35.4" x 29.3" x 44.9" (WxDxH)	

<b>Plockmatic Multi Purpose Stacker XL</b> <sup>7</sup>	<b>Stack Height</b>	
	Sheets < 28.1":	Up to 11.8"
	Sheets > 28.1":	Up to 5.5"
	<b>Paper Size:</b>	8.3" x 8.3" to 13" x 30"
	<b>Paper Weight:</b>	
	Up to 18":	21 lb. Bond to 130 lb. Cover (80 gsm to 350 gsm)
	Up to 27.5":	80 lb. Text to 110 lb. Cover (120 gsm to 300 gsm)
	Up to 30":	100 lb. Text to 110 lb. Cover (150 gsm to 300 gsm)
	<b>Power Source:</b>	100 – 230 V ± 10%, 50–60Hz
	<b>Weight:</b>	198 lb.
<b>Dimensions:</b>	35.4" x 29.5" x 41.7" (WxDxH)	

<b>Paper Folding Unit-K1</b> <sup>8</sup>	<b>Double Parallel Fold:</b>	Legal, Letter-R
	<b>C/Accordion Fold:</b>	Letter-R
	<b>Z-Fold:</b>	Letter-R, 11" x 17"
	<b>Paper Weight:</b>	14 lb. Bond to 28 lb. Bond (52 gsm to 105 gsm)
	<b>Power Source:</b>	From Finisher
	<b>Weight:</b>	157 lb.
	<b>Dimensions:</b>	13.2" x 31.2" x 46.9" (WxDxH)

<b>Staple Finisher-AC1/Booklet Finisher-AC2</b> <sup>9</sup>	<b>Tray Capacity</b> <sup>1</sup>	
	Top Tray:	Up to 250 Sheets
	Middle Tray:	Up to 250 Sheets
	Lower Tray:	Up to 3,000 Sheets
	Saddle-Stitch Tray:	Up to 30 Booklets
<b>Paper Weight</b>		
Stacking:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)	

Corner Stapling:	14 lb. Bond to 140 lb. Index (52 gsm to 256 gsm)
Booklet-Making:	14 lb. Bond to 140 lb. Index (52 gsm to 256 gsm)

<b>Staple Positions:</b>	Corner, Double-Side, Eco
--------------------------	--------------------------

<b>Paper Size</b>	
Stapling:	Executive, Letter-R, Letter, Legal, 11" x 17"
Saddle Finisher:	7.7" x 10.6" to 12" x 18"

<b>Stapling Capacity</b> <sup>1</sup>	
Corner/Double:	Up to 65 Sheets
Eco-Stitch:	Up to 6 Sheets
Saddle-Stitch:	Up to 20 Sheets
V-Fold:	Up to 3 Sheets without Stitch

<b>Power Source:</b>	From the Main Unit
----------------------	--------------------

<b>Weight</b>	
Staple Finisher:	79 lb.
Booklet Finisher:	132 lb.

<b>Dimensions:</b>	20.8" x 24.5" x 43.3" (WxDxH)
--------------------	-------------------------------

<b>2/3 Hole Puncher Unit-A1</b> <sup>10</sup>	<b>Paper Weight:</b>	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
---	----------------------	--

<b>Paper Sizes:</b>	Letter-R
2-Hole:	Legal, Letter-R, Custom Size (7.2" x 7.2" to 11.8" x 17")
3-Hole:	11" x 17", Letter, Executive-R, Custom Size (9.5" x 7.2" to 11.8" x 17")

<b>Power Supply:</b>	From Finisher
----------------------	---------------

<b>Staple Finisher-AG1/Booklet Finisher-AG1</b>	<b>Tray Capacity</b> <sup>1</sup>	
	Top Tray:	Up to 1,000 Sheets
	Lower Tray:	Up to 4,000 Sheets
	Saddle-Stitch Tray:	Continuous by Belt

<b>Paper Weight</b>	
Stacking:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
Corner Stapling:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
Booklet-Making:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)

<b>Staple Positions:</b>	Corner, Double-Side, Saddle-Stitch
--------------------------	------------------------------------

<b>Paper Size</b>	
Stapling:	8.3' x 11' to 11.7' x 17'
Saddle Finisher:	8.27' x 11' to 13' x 19.2'

<b>Stapling Capacity</b> <sup>1</sup>	
Corner/Double:	Up to 100 Sheets
Saddle-Stitch:	Up to 25 Sheets
V-Fold:	Up to 5 Sheets without Stitch

<b>Power Source:</b>	120-127 V, 60 Hz, 8 A
----------------------	-----------------------

<b>Weight</b>	
Staple Finisher:	287 lb.
Booklet Finisher:	397 lb.

<b>Dimensions:</b>	31.5" W x 31.2" D x 48.8" H
--------------------	-----------------------------

<b>SDD PTM7600<sup>11</sup></b>	<b>Included Modules:</b>	Press Trim Module PTM7006 Conveyor Belt Stacker CBS6060
	<b>Input Book Size:</b>	8.27" x 11" to 9.6" x 12.6"
	<b>Book Thickness</b>	Up to 25 sheets <sup>1</sup>
	<b>Paper Weight:</b>	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	<b>Face Trim Amount:</b>	.08" x .98"
	<b>Belt Stacker Length:</b>	23.6"
	<b>Power Source:</b>	2100-240 V, 2.5 A
	<b>Weight:</b>	203 lb.
	<b>Dimensions:</b>	51.2" x 23.6" x 20.5" (WxDxH)

<b>SDD PTM7600 SFM<sup>11</sup></b>	<b>Included Modules:</b>	Press Trim Module PTM7006 SquareFold Module 7004 Conveyor Belt Stacker CBS6060
	<b>Input Book Size:</b>	8.27" x 11" to 9.6" x 12.6"
	<b>Book Thickness</b>	Up to 25 sheets <sup>1</sup>
	<b>Paper Weight:</b>	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	<b>Face Trim Amount:</b>	.08" x .98"
	<b>Belt Stacker Length:</b>	23.6"
	<b>Power Source:</b>	2100-240 V, 2.5 A
	<b>Weight:</b>	287 lb.
	<b>Dimensions:</b>	75.6" x 23.6" x 20.5" (WxDxH)

<b>Long Sheet Catch Tray-C1<sup>12</sup></b>	<b>Stack Capacity:<sup>1</sup></b>	Up to 100 Sheets
	<b>Paper Size:</b>	4" x 5.83" to 13" x 30"

<b>Long Sheet Catch Tray XL-B1<sup>13</sup></b>	<b>Stack Capacity<sup>1</sup></b>	Up to 30": Up to 300 Sheets Up to 51.2": Up to 10 Sheets
	<b>Paper Size:</b>	3.93" x 5.83" to 13" x 51.2"

<b>Puncher Unit-BS1<sup>13</sup></b>	<b>Paper Sizes</b>	
	2-Hole:	Legal, Letter-R, Custom Size (7.2" x 7.2" to 11.8" x 17")
	3-Hole:	11" x 17", Letter, Executive-R, Custom Size (9.5" x 7.2" to 11.8" x 17")
	<b>Paper Weight:</b>	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	<b>Punch Waste Capacity:</b>	Up to 6,000 Sheets
	<b>Power Supply:</b>	From the Finisher
	<b>Supported Finishing:</b>	Plockmatic BLM50/35 Professional Booklet Maker, Plockmatic Multi Purpose Stacker
	<b>Requirements:</b>	Staple/Booklet Finisher-AG1
	<b>Weight:</b>	7 lb.

<b>DFD Adapter and Finisher Bridge-B1<sup>13</sup></b>	<b>Paper Weight:</b>	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	<b>Supported Finishing:</b>	Plockmatic BLM50/35, Plockmatic Multi Purpose Stacker
	<b>Weight:</b>	198 lb.
	<b>Dimensions:</b>	35.4" x 29.3" x 40.9" (WxDxH)

<b>Booklet Trimmer-G1<sup>13</sup></b>	<b>Margin Trimming:</b>	Front-edge Trim
	<b>Trim Amount:</b>	0.08" to 1.1"
	<b>Paper Weight:</b>	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	<b>Power Supply:</b>	From the Finisher
	<b>Weight:</b>	392 lb.
<b>Dimensions:</b>	82.5" x 31.1" x 41" (WxDxH)	

<b>Two-Knife Trimmer and Conveyor Set<sup>14</sup></b>	<b>Margin Trimming:</b>	Top and Bottom
	<b>Trim Amount:</b>	0.08" to 0.59"
	<b>Paper Weight:</b>	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	<b>Power Supply:</b>	120-127 V AC, 50/60 Hz, 4 A
	<b>Weight:</b>	320 lb.
<b>Dimensions:</b>	21.1" x 30.3" x 41" (WxDxH)	

<b>SDD Square-Fold Booklet-Maker<sup>14</sup></b>	<b>Booklet Capacity:<sup>1</sup></b>	Up to 25 Sheets
	<b>Booklet Input Size:</b>	5.5" x 8.27" to 9.6" x 12.6"
	<b>Booklet Output Size:</b>	4.71" x 7.87" to 9.6" x 12.6"
	<b>Paper Weight:</b>	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	<b>Power Supply:</b>	120 V, 60 Hz, 15 A
	<b>Weight:</b>	170 lb.
	<b>Dimensions:</b>	37.6" x 23.4" x 47" (WxDxH)

<b>SDD SFM7804 Two Knife Trim Set<sup>14</sup></b>	<b>Booklet Capacity:<sup>1</sup></b>	Up to 25 Sheets
	<b>Booklet Input Size:</b>	4.88" x 5.51" to 9.6" x 12.6"
	<b>Paper Weight:</b>	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	<b>Trim Amount:</b>	0.08" to 2"
	<b>Power Supply:</b>	120 V, 60 Hz, 15 A
	<b>Weight:</b>	545 lb.
	<b>Dimensions:</b>	66.1" x 27.6" x 52.5" (WxDxH)

<b>Plockmatic BLM50/35 Professional Booklet-Maker<sup>6,15</sup></b>	<b>Booklet Size:<sup>1</sup></b>	Up to 35/50 Sheets	
	<b>Paper Size:</b>	8.1" x 10.8" to 12.6" x 18.1"	
	<b>Paper Weight</b>	Uncoated:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
		Coated:	28 lb. Bond to 110 lb. Cover (105 gsm to 300 gsm)
	<b>Trim Amount</b>		
	Face: <sup>16</sup>	0.04" to 0.63"	
	Top/Bottom: <sup>17</sup>	0.196" to 1.18"	
	<b>Paper Rotating:<sup>17</sup></b>	8.1" x 10.9" to 9.1" x 12.7"	
	<b>Power Supply:<sup>18</sup></b>	100-230 V, 50/60 Hz	
	<b>Weight:<sup>18</sup></b>	441 lb.	
<b>Dimensions:<sup>18</sup></b>	57.8" x 28.8" x 41.4" (WxDxH)		

## Print Servers

<b>imagePRESS Printer Kit-J1</b>	<b>PDL:</b>	UFR II, PS, PCL 5e/6
	<b>Memory:</b>	4 GB
	<b>Hard Drive:</b>	1 TB

<b>PRISMAsync Print Server</b>	<b>System Software:</b>	Mark 10
	<b>CPU:</b>	Intel® Core i5 8500
	<b>Memory:</b>	8 GB
	<b>Hard Drive:</b>	1.5 TB
	<b>OS:</b>	Windows® 10, LTSC
	<b>Standard:</b>	Scheduler, DocBox, G7 Calibration, Page Programmer, Remote Manager, PRISMAlytics Dashboard, Automated Workflows, Multiple Queues, Remote Control
<b>Optional:</b>	DP Link, E-shredding, Advanced Imposition	

<b>PRISMAsync Print Server LP</b>	<b>System Software:</b>	Mark 10
	<b>CPU:</b>	Intel® Core i5 8500
	<b>Memory:</b>	8 GB
	<b>Hard Drive:</b>	1.5 TB
	<b>OS:</b>	Windows® 10, LTSC
	<b>Standard:</b>	Multiple Queues, Scheduler, Remote Manager, Color Presets, Pixel Precise Preview, Spot Color Editing, Calibration, Realistic Preview, Digital Moire
<b>Optional:</b>	Advanced Color Management, Power-Up Package, E-Shredding, Accounting, Advanced Imposition, X-Rite i1 Basic Pro 3, Operator Attention Light	

<b>imagePRESS Server N500 V2</b>	<b>Fiery System:</b>	FS600 Pro
	<b>CPU:</b>	Intel Core i5-8500 3.2 GHz up to 4.6 GHz W/ Turbo
	<b>Memory:</b>	8 GB
	<b>Hard Drive:</b>	1.2 TB
	<b>OS:</b>	Windows 10
	<b>Standard:</b>	Fiery Hot Folders, Virtual Printers, Unity Display, Fiery JDF, Fiery Command Workstation 6, Paper Catalog, Fiery Spot-On, Fiery Remote Scan, Media Librarian
<b>Optional:</b>	Impose/Compose, Graphic Arts Pro Package, Job Master, JobFlow, Fiery High Security Kit	

<b>imagePRESS Server P400 V2</b>	<b>Fiery System:</b>	FS600
	<b>CPU:</b>	Intel Pentium G5400, 3.7 GHz
	<b>Memory:</b>	8 GB
	<b>Hard Drive:</b>	500 GB
	<b>OS:</b>	Linux
	<b>Standard:</b>	Fiery Command WorkStation 6, Paper Catalog, Fiery Spot On, Fiery Remote Scan, Hot Folders License
<b>Optional:</b>	Impose/Compose, Automation Package, ColorRight Package, Job Master, JobFlow	

To view detailed specifications, please consult the Customer Expectations Document.

<sup>1</sup> Based on 20 lb. Bond.

<sup>2</sup> Envelope Attachment Kit required.

<sup>3</sup> POD Deck Lite-XL or Long Sheet Feed Tray-B1 required.

<sup>4</sup> Stocks longer than 19.2" support up to 110 lb. Cover (300 gsm).

<sup>5</sup> Staple/Booklet Finisher-AG1 or High Capacity Stacker-J1 required.

<sup>6</sup> Not available for the imagePRESS V700.

<sup>7</sup> High Capacity Stacker-J1 with DFD+ Interface Kit Set or DFD Adapter and Finisher Bridge-B1 required.

<sup>8</sup> Staple/Booklet Finisher-AG1 required.

<sup>9</sup> Not available for the imagePRESS V900.

<sup>10</sup> Staple Finisher-AC1 or Booklet Finisher-AC2 required.

<sup>11</sup> Booklet Finisher AG1 required.

<sup>12</sup> Copy Tray-R2, Staple/Booklet Finisher-AG1 required.

<sup>13</sup> Staple/Booklet Finisher-AG1 required.

<sup>14</sup> Booklet Trimmer-G1 required.

<sup>15</sup> High Capacity Stacker-J1 or DFD Adapter and Finisher Bridge-A2 required.

<sup>16</sup> Optional trimmer module required.

<sup>17</sup> Optional rotator RCT module required.

<sup>18</sup> Specification is only for booklet maker module.



# Canon

[usa.canon.com/production](https://usa.canon.com/production)

As an ENERGY STAR® Partner, Canon U.S.A., Inc. qualified these models as meeting the ENERGY STAR® energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon and imagePRESS are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. PRISMA is a registered trademark of Canon Production Printing Netherlands B.V. All other referenced product names and marks are trademarks of their respective owners. Some printer output images may be simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims on unauthorized copying.

©2025 Canon U.S.A., Inc. All rights reserved.

07/25-2416-13851