



imagePRESS V900/V800/V700

COLOR PRODUCTION DIGITAL PRESS



imagePRESS V900 shown with optional accessories.

Product Specifications

Marking Engine

Technology	Electrophotography		
Print Resolution	2400 x 2400 dpi		
Print Speed	V900	V800	V700
8.5" x 11":	Up to 90 ipm	Up to 81 ipm	Up to 71 ipm
11" x 17":	Up to 45 ipm	Up to 40 ipm	Up to 35 ipm
12" x 18":	Up to 42 ipm	Up to 40 ipm	Up to 35 ipm
13" x 19":	Up to 40 ipm	Up to 38 ipm	Up to 33 ipm
13" x 30":	Up to 23 ipm	Up to 22 ipm	Up to 19 ipm
Paper Size	Standard:	3.94" x 5.83" to 13" x 19.2"	
	Optional:	5.5" x 5.83" to 13" x 51.2"	
Paper Capacity ¹	Standard:	Up to 1,650 Sheets	
	Maximum:	Up to 10,400 Sheets	
Paper Weight	Standard:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)	
	Optional:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)	
	Envelopes: ²	No. 10 (COM10), ISO-C5, DL, Monarch, 6" x 9", 9" x 12", 10" x 13"	
Long Sheets ³	Duplex:	Up to 13" x 30"	
	Simplex:	Up to 13" x 51.2"	
Automatic Duplexing	Paper Size:	Up to 13" x 30" ³	
	Paper Weight:	Up to 130 lb. Cover (350 gsm) ⁴	
Power Source	200-240 V, 50/60 Hz, 20 A		
Weight	With Canon UI:	573 lb.	
	With PRISMAsync UI:	592 lb.	
Dimensions	With Canon UI:	35.7" W x 34.3" D x 40.9" H	
	With PRISMAsync UI:	59" W x 34.3" D x 54.5" H	

Input Accessories

Color Image Reader-P1	Image Sensor:	CCD
	Scan Speed:	Up to 270 ipm (Letter, 300 dpi)
	Document Size:	2.8" x 5.5" to 12" x 24.8"
	Resolution:	Up to 600 x 600 dpi, 256 Gradations
	Tray Capacity:¹	Up to 250 Sheets
	Weight:	51 lb.
POD Deck-F1	Dimensions:	25.7" W x 23.3" D x 8.6" (WxDxH)
	Paper Capacity:¹	Up to 5,000 Sheets
	Paper Size:	5.5" x 7.2" to 13" x 19.2"
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Power Source:	110 – 127 V, 60 Hz, 7 A
	Weight:	392 lb.
Multi-Drawer Paper Deck-E1	Dimensions:	38" x 31.5" x 42.5" (WxDxH)
	Paper Capacity:¹	Up to 5,000 Sheets
	Paper Size:	5.5" x 7.2" to 13" x 19.2"
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Power Source:	110 – 127 V, 60 Hz, 7 A
	Weight:	392 lb.
POD Deck Lite-C1	Dimensions:	38" x 31.5" x 42.5" (WxDxH)
	Paper Capacity:¹	Up to 3,500 Sheets
	Paper Size:	5.5" x 7.2" to 13" x 19.2"
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Power Source:	120 – 127 V, 60 Hz, 2.2 A
	Weight:	168 lb.
	Dimensions:	24.9" x 27" x 22.6" (WxDxH)

Input Accessories (Continued):

POD Deck Lite XL-A2	Paper Capacity¹	
	Up to 13" x 19.2":	Up to 3,500 Sheets
	Up to 13" x 30":	Up to 1,000 Sheets
	Paper Size:	5.5" x 7.2" to 13" x 30"
	Paper Weight:	
	Up to 13" x 19.2":	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Up to 13" x 30":	17 lb. Bond to 110 lb. Cover (64 gsm to 300 gsm)
	Power Source:	100-127 V, 60 Hz, 7 A
	Weight:	249 lb.
	Dimensions:	40.2" x 27" x 22.6" (WxDxH)

Stack Bypass-D1	Paper Capacity:¹	Up to 250 Sheets
	Paper Size:	3.94" x 5.83" to 13" x 19.2"
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Weight:	3 lb.
	Dimensions:	18" x 15.1" x 2.9" (WxDxH)

Long Sheet Feeding and Catch Tray-B1	Paper Capacity:	Up to 1 Sheet
	Paper Size:	4" x 5.83" to 13" x 51.2"
	Paper Weight:	17 lb. Bond to 130 lb. Cover (64 gsm to 350 gsm) ⁵
	Weight:	2 lb.
	Dimensions:	85.6" x 56.1" x 56.1" (WxDxH)

Finishing Accessories

Copy Tray-R2	Paper Capacity:¹	Up to 250 Sheets
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Paper Size:	4" x 5.83" to 13" x 19.2"
	Weight:	3 lb.
	Dimensions:	16.6" x 15" x 6.8" (WxDxH)

Sensing Unit-B1⁵	Tasks:	Front-to-Back Alignment, Color Accuracy Check, Cross Shade Adjustment, Secondary Transfer Adjustment
	DfE:	PRISMAsync print server V8.3 or Later; imagePRESS Server N500/P400 or Later
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Paper Size:	5.5" x 5.83" to 13" x 30"
	Power Supply:	100 – 240 V, 50/60 Hz, 2.5 A
	Weight:	222 lb.
	Dimensions:	20.3" x 29.5" x 48.3" (WxDxH)

Inspection Unit-A1⁵	Paper Type:	Plain Paper, Coated Paper
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Paper Size:	3.9" x 7.2" to 11.9" x 19.2"
	Detection Size:	0.2mm x .02mm to 1.4 mm x 1.4 mm
	Scanning Width:	Up to 11.9"
	Inspection Workstation	
	Inspection Tool OS: Windows® 10 Pro	
	Mode:	Log Only Mode, Purge and Recovery Mode

	Inspection Location:Up to 64 areas	
	Intensity Level:	9 Levels
	Objects:	Position Gap, Dirt, Streaks
	Auto Recovery:	Yes (Purge and Recovery Mode Only)
	Purge Unit:	High Capacity Stacker-J1
	Power Supply:	120 - 240 V, 50/60 Hz, 1.4 A
	Weight:	109 lb.
	Dimensions:	9.8" x 31.2" x 40.9" (WxDxH)

Document Insertion Unit-R1⁵	Tray Capacity¹	
	Upper Tray:	Up to 200 Sheets
	Lower Tray:	Up to 200 Sheets
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Paper Size:	7.2" x 7.2" to 13" x 19.2"
	Power Supply:	100 – 240 V, 50/60 Hz, 1.0 A
	Weight:	135 lb.
	Dimensions:	29.4" x 31.2" x 55.4" (WxDxH)

Static Eliminator-A1⁵	Paper Size:	3.9" x 5.8" to 13" x 51.2"
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Power Supply:	100-240 V, 50/60 Hz, 1 A
	Weight:	110 lb.
	Dimensions:	9.8" x 31.2" x 41" (WxDxH)

Multi Function Professional Puncher-C1⁵	Paper Weight	
	Punching:	20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm)
	Creasing:	110 lb. Text to 110 lb. Cover (162 gsm to 300 gsm)
	Paper Size	
	Punching (Single):	Letter-R, Letter, Legal, 11" x 17", 12" x 18"
	Punching (Double):	Letter-R, Legal, 11" x 17", 12" x 18"
	Creasing:	Letter-R, 11" x 17", 12" x 18", 13" x 19"
	Die Set Patterns:	Loose Leaf 3-Hole/5-Hole, Velo Bind 11-Hole, Plastic Comb 19-Hole, Twin Loop 21-Hole/32-Hole, Color Coil 44-Hole, Crease
	Power Supply:	115 V, 60 Hz, 3.8 A
	Weight:	225 lb.
	Dimensions:	17.5" x 31.3" x 40.9" (WxDxH)

GBC eWire Pro^{5,6}	Bound Book Size:¹	15 to 100 Sheets
	Paper Size:	Letter, 5.5" x 8.5", Tab Stock
	Paper Weight:	20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm)
	Wire Choices:	1/4", 5/16", 3/8", 7/16", 1/2", 9/16"
	Stack Capacity:	Up to 35 Books
	Infeed:	Multi Function Professional Puncher-B1
	Power Supply:	115 V, 60 Hz, 2.8A
	Weight:	500 lb.
	Dimensions:	42.5" x 35.9" x 31.7" (WxDxH)

Finishing Accessories (Continued):

Perfect Binder-F1 ^{5,6}	Finished Book Size:	5.4" x 7.99" to 8.5" x 11.69"
	Book Thickness: ¹	10 to 200 Sheets (Up to 0.98")
	Body Paper Weight:	14 lb. Bond to 43 lb. Bond (52 gsm to 163 gsm)
	Cover Paper Weight:	24 lb. Bond to 110 lb. Cover (90 gsm to 300 gsm)
	Trimming Method:	3-Side Cut/1-Side Cut/No Cut
	Trim Range	
	Top/Bottom:	0.26" to 1.56"
	Side:	0.26" to 1.95"
	Options:	Perfect Binder Continuous Kit-BI
	Power Source:	208 V, 60 Hz, 3 A
High Capacity Stacker-J1	Weight:	679 lb.
	Dimensions:	36.3" x 31.1" x 51.3" (WxDxH)
	Stack Capacity: ¹	Up to 6,000 Sheets
	Top Tray Capacity: ¹	Up to 200 Sheets
	Paper Size:	5.5" x 7.2" to 13" x 19.2"
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Options:	PowerLift
Plockmatic Multi Purpose Stacker-XL ⁷	Power Source:	90-264 V AC, 47-63 Hz, 10 A
	Weight:	265 lb.
	Dimensions:	35.4" x 29.3" x 44.9" (WxDxH)
	Stack Height	
	Sheets < 28.1":	Up to 11.8"
	Sheets > 28.1":	Up to 5.5"
	Paper Size:	8.3" x 8.3" to 13" x 30"
Paper Folding Unit-K1 ⁸	Paper Weight:	
	Up to 18":	21 lb. Bond to 130 lb. Cover (80 gsm to 350 gsm)
	Up to 27.5":	80 lb. Text to 110 lb. Cover (120 gsm to 300 gsm)
	Up to 30":	100 lb. Text to 110 lb. Cover (150 gsm to 300 gsm)
	Power Source:	100 – 230 V ± 10%, 50–60Hz
	Weight:	198 lb.
	Dimensions:	35.4" x 29.5" x 41.7" (WxDxH)
Staple Finisher-AC1/Booklet Finisher-AC2 ⁹	Double Parallel Fold:	Legal, Letter-R
	C/Accordion Fold:	Letter-R
	Z-Fold:	Letter-R, 11" x 17"
	Paper Weight:	14 lb. Bond to 28 lb. Bond (52 gsm to 105 gsm)
	Power Source:	From Finisher
	Weight:	157 lb.
	Dimensions:	13.2" x 31.2" x 46.9" (WxDxH)
2/3 Hole Puncher Unit-A1 ¹⁰	Tray Capacity ¹	
	Top Tray:	Up to 250 Sheets
	Middle Tray:	Up to 250 Sheets
	Lower Tray:	Up to 3,000 Sheets
	Saddle-Stitch Tray:	Up to 30 Booklets
	Paper Weight	
	Stacking:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
Staple Finisher-AG1/Booklet Finisher-AG1	Corner Stapling:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Booklet-Making:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Staple Positions:	Corner, Double-Side, Saddle-Stitch
	Paper Size	
	Stapling:	8.3" x 11" to 11.7" x 17"
	Saddle Finisher:	8.27" x 11" to 13" x 19.2"
	Stapling Capacity ¹	
Staple Finisher-AG1/Booklet Finisher-AG1	Corner/Double:	Up to 100 Sheets
	Saddle-Stitch:	Up to 25 Sheets
	V-Fold:	Up to 5 Sheets without Stitch
	Power Source:	120-127 V, 60 Hz, 8 A
	Weight	
	Staple Finisher:	287 lb.
	Booklet Finisher:	397 lb.
Staple Finisher-AG1/Booklet Finisher-AG1	Dimensions:	31.5" W x 31.2" D x 48.8" H

Corner Stapling:	14 lb. Bond to 140 lb. Index (52 gsm to 256 gsm)
Booklet-Making:	14 lb. Bond to 140 lb. Index (52 gsm to 256 gsm)
Staple Positions:	Corner, Double-Side, Eco
Paper Size	
Stapling:	Executive, Letter-R, Letter, Legal, 11" x 17"
Saddle Finisher:	7.7" x 10.6" to 12" x 18"
Stapling Capacity ¹	
Corner/Double:	Up to 65 Sheets
Eco-Stitch:	Up to 6 Sheets
Saddle-Stitch:	Up to 20 Sheets
V-Fold:	Up to 3 Sheets without Stitch
Power Source:	From the Main Unit
Weight	
Staple Finisher:	79 lb.
Booklet Finisher:	132 lb.
Dimensions:	20.8" x 24.5" x 43.3" (WxDxH)
Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
Paper Sizes:	Letter-R
2-Hole:	Legal, Letter-R, Custom Size (7.2" x 7.2" to 11.8" x 17")
3-Hole:	11" x 17", Letter, Executive-R, Custom Size (9.5" x 7.2" to 11.8" x 17")
Power Supply:	From Finisher
Tray Capacity ¹	
Top Tray:	Up to 1,000 Sheets
Lower Tray:	Up to 4,000 Sheets
Saddle-Stitch Tray:	Continuous by Belt
Paper Weight	
Stacking:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
Corner Stapling:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
Booklet-Making:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
Staple Positions:	Corner, Double-Side, Saddle-Stitch
Paper Size	
Stapling:	8.3" x 11" to 11.7" x 17"
Saddle Finisher:	8.27" x 11" to 13" x 19.2"
Stapling Capacity ¹	
Corner/Double:	Up to 100 Sheets
Saddle-Stitch:	Up to 25 Sheets
V-Fold:	Up to 5 Sheets without Stitch
Power Source:	120-127 V, 60 Hz, 8 A
Weight	
Staple Finisher:	287 lb.
Booklet Finisher:	397 lb.
Dimensions:	31.5" W x 31.2" D x 48.8" H

SDD PTM7600¹¹	Included Modules:	Press Trim Module PTM7006 Conveyor Belt Stacker CBS6060
	Input Book Size:	8.27" x 11" to 9.6" x 12.6"
	Book Thickness	Up to 25 sheets ¹
	Paper Weight:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	Face Trim Amount:	.08" x .98"
	Belt Stacker Length:	23.6"
	Power Source:	2100-240 V, 2.5 A
	Weight:	203 lb.
	Dimensions:	51.2" x 23.6" x 20.5" (WxDxH)
SDD PTM7600 SFM¹¹	Included Modules:	Press Trim Module PTM7006 SquareFold Module 7004 Conveyor Belt Stacker CBS6060
	Input Book Size:	8.27" x 11" to 9.6" x 12.6"
	Book Thickness	Up to 25 sheets ¹
	Paper Weight:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	Face Trim Amount:	.08" x .98"
	Belt Stacker Length:	23.6"
	Power Source:	2100-240 V, 2.5 A
	Weight:	287 lb.
	Dimensions:	75.6" x 23.6" x 20.5" (WxDxH)
Long Sheet Catch Tray-C1¹²	Stack Capacity:¹	Up to 100 Sheets
	Paper Size:	4" x 5.83" to 13" x 30"
Long Sheet Catch Tray XL-B1¹³	Stack Capacity¹	
	Up to 30":	Up to 300 Sheets
	Up to 51.2":	Up to 10 Sheets
	Paper Size:	3.93" x 5.83" to 13" x 51.2"
Puncher Unit-BS1¹³	Paper Sizes	
	2-Hole:	Legal, Letter-R, Custom Size (7.2" x 7.2" to 11.8" x 17")
	3-Hole:	11" x 17", Letter, Executive-R, Custom Size (9.5" x 7.2" to 11.8" x 17")
	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Punch Waste Capacity:	Up to 6,000 Sheets
	Power Supply:	From the Finisher
	Supported Finishing:	Plockmatic BLM50/35 Professional Booklet Maker, Plockmatic Multi Purpose Stacker
	Requirements:	Staple/Booklet Finisher-AG1
	Weight:	7 lb.
DFD Adapter and Finisher Bridge-B1¹³	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Supported Finishing:	Plockmatic BLM50/35, Plockmatic Multi Purpose Stacker
	Weight:	198 lb.
	Dimensions:	35.4" x 29.3" x 40.9" (WxDxH)

Booklet Trimmer-G1¹³	Margin Trimming:	Front-edge Trim
	Trim Amount:	0.08" to 1.1"
	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Power Supply:	From the Finisher
	Weight:	392 lb.
	Dimensions:	82.5" x 31.1" x 41" (WxDxH)
Two-Knife Trimmer and Conveyor Set¹⁴	Margin Trimming:	Top and Bottom
	Trim Amount:	0.08" to 0.59"
	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Power Supply:	120-127 V AC, 50/60 Hz, 4 A
	Weight:	320 lb.
	Dimensions:	21.1" x 30.3" x 41" (WxDxH)
SDD Square-Fold Booklet-Maker¹⁴	Booklet Capacity:¹	Up to 25 Sheets
	Booklet Input Size:	5.5" x 8.27" to 9.6" x 12.6"
	Booklet Output Size:	4.71" x 7.87" to 9.6" x 12.6"
	Paper Weight:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	Power Supply:	120 V, 60 Hz, 15 A
	Weight:	170 lb.
	Dimensions:	37.6" x 23.4" x 47" (WxDxH)
SDD SFM7804 Two Knife Trim Set¹⁴	Booklet Capacity:¹	Up to 25 Sheets
	Booklet Input Size:	4.88" x 5.51" to 9.6" x 12.6"
	Paper Weight:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	Trim Amount:	0.08" to 2"
	Power Supply:	120 V, 60 Hz, 15 A
	Weight:	545 lb.
	Dimensions:	66.1" x 27.6" x 52.5" (WxDxH)
Plockmatic BLM450e/435e Professional Booklet Maker^{6,15}	Booklet Size:¹	Up to 35/50 Sheets
	Paper Size:¹⁶	5.7" x 8.3" to 12.6" x 26"
	Paper Weight	17 lb. Bond to 110 lb. Cover (64 gsm to 300 gsm)
	Trim Amount	
	Face: ¹⁷	0.039" to 9.1"
	Top/Bottom: ¹⁸	0.19" to 1.18"
	Paper Rotating:¹⁸	8.1" x 10.9" to 9.1" x 12.7"
	Power Supply:¹⁹	100-230 V, 50/60 Hz
	Weight:¹⁹	532 lb.
	Dimensions:¹⁹	64.5" x 31.5" x 44.9" (WxDxH)

Print Servers

imagePRESS Printer Kit-J1	PDL:	UFR II, PS, PCL 5e/6
	Memory:	4 GB
	Hard Drive:	1 TB
PRISMAsync Print Server	System Software:	Mark II
	CPU:	Intel® Core i5 8500
	Memory:	8 GB
	Hard Drive:	1.5 TB
	OS:	Windows® 11, LTSC
	Standard:	Scheduler, DocBox, G7 Calibration, Page Programmer, Remote Manager, PRISMAlytics Dashboard, Automated Workflows, Multiple Queues, Remote Control
	Optional:	DP Link, Advanced Imposition
PRISMAsync Print Server LP	System Software:	Mark II
	CPU:	Intel® Core i5 8500
	Memory:	8 GB
	Hard Drive:	1.5 TB
	OS:	Windows® 11, LTSC
	Standard:	Multiple Queues, Scheduler, Remote Manager, Color Presets, Pixel Precise Preview, Spot Color Editing, Calibration, Realistic Preview, Digital Moire
	Optional:	Advanced Color Management, Power-Up Package, Accounting, Advanced Imposition, X-Rite i1 Basic Pro 3, Operator Attention Light

imagePRESS Server N500 V2	Fiery System:	FS600 Pro
	CPU:	Intel Core i5-8500 3.2 GHz up to 4.6 GHz W/ Turbo
	Memory:	8 GB
	Hard Drive:	1.2 TB
	OS:	Windows 10
	Standard:	Fiery Hot Folders, Virtual Printers, Unity Display, Fiery JDF, Fiery Command Workstation 6, Paper Catalog, Fiery Spot-On, Fiery Remote Scan, Media Librarian
	Optional:	Impose/Compose, Graphic Arts Pro Package, Job Master, JobFlow, Fiery High Security Kit

imagePRESS Server P400 V2	Fiery System:	FS600
	CPU:	Intel Pentium G5400, 3.7 GHz
	Memory:	8 GB
	Hard Drive:	500 GB
	OS:	Linux
	Standard:	Fiery Command WorkStation 6, Paper Catalog, Fiery Spot On, Fiery Remote Scan, Hot Folders License
	Optional:	Impose/Compose, Automation Package, ColorRight Package, Job Master, JobFlow

To view detailed specifications, please consult the Customer Expectations Document.

¹ Based on 20 lb. Bond.

² Envelope Attachment Kit required.

³ POD Deck Lite-XL or Long Sheet Feed Tray-B1 required.

⁴ Stocks longer than 19.2" support up to 110 lb. Cover (300 gsm).

⁵ Staple/Booklet Finisher-AG1 or High Capacity Stacker-J1 required.

⁶ Not available for the imagePRESS V700.

⁷ High Capacity Stacker-J1 with DFD+ Interface Kit Set or DFD Adapter and Finisher Bridge-B1 required.

⁸ Staple/Booklet Finisher-AG1 required.

⁹ Not available for the imagePRESS V900.

¹⁰ Staple Finisher-AC1 or Booklet Finisher-AC2 required.

¹¹ Booklet Finisher AG1 required.

¹² Copy Tray-R2, Staple/Booklet Finisher-AG1 required.

¹³ Staple/Booklet Finisher-AG1 required.

¹⁴ Booklet Trimmer-G1 required.

¹⁵ High Capacity Stacker-J1 or DFD Adapter and Finisher Bridge-A2 required.

¹⁶ 5.7" x 8.3" to 13" x 24.4" when RCT is attached.

¹⁷ Optional Finishing Module FM400e required.

¹⁸ Optional rotator RCT module required.

¹⁹ Specification is only for booklet maker module.



usa.canon.com/production

As an ENERGY STAR® Partner, Canon U.S.A., Inc. qualified these models as meeting the ENERGY STAR® energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon and imagePRESS are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. PRISMA is a registered trademark of Canon Production Printing Netherlands B.V. All other referenced product names and marks are trademarks of their respective owners. Some printer output images may be simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims on unauthorized copying.

©2026 Canon U.S.A., Inc. All rights reserved.

07/26-0753-13851