

Canon

Quality, Quantity, Speed.

Production Redefined



imagePROGRAF
GP-2600S

imagePROGRAF GP-2600S Specifications

Printhead

PF-10

Number of Nozzles

18,432 nozzles

Droplet Size

Minimum 4 pl per color

Ink Type

MBK, PBK, C, M, Y, GY, O

Ink Tank

Shipped: 160 ml Tank, Each Color GY/PBK, 330 ml Tank, Each Color MBK/C/M/Y/O

Replacement:

160 ml PFI-3100 (PBK, C, M, Y, GY), 160 ml PFI-2100 (MBK, O), 330 ml PFI-3300 (PBK, C, M, Y, GY), 330 ml PFI-2300 (MBK, O), 700 ml PFI-3700 (PBK, C, M, Y, GY), 700 ml PFI-2700 (MBK, O)

Printer RAM

Standard Memory: 3 GB
Hard Disk: 500 GB

Media Feed

Front-Loading Roll Feed: Dual Roll*, Front Output
Cut Sheet: Upper-loading, Front Output (Manual feed using media locking lever)

Media Width

Roll Feed: 6" - 24" (152.4 - 610 mm)
Cut Sheet: 6" - 24" (152.4 - 610 mm)

Media Cutter

Automatic horizontal cutting (Rotary cutter): standard

Media Thickness

0.002" - 0.03" (0.07 mm - 0.8 mm)

Media Core Sizes

2" Core Standard. 2"/3" Core Roll Holder Set (RU-29)

Maximum Roll Outer Diameter

6.7" or less (170 mm or less)

Media Output

Catch Basket

Printing Software Utilities

Accounting Manager, Device Management Console, Direct Print Plus, Free Layout Plus, imagePROGRAF Printer Driver for Windows®/Mac®, Media Configuration Tool, PosterArtist, Canon Print Service, Professional Print & Layout

Operating System

Windows 7 (32/64-bit), Windows 8.1 (32/64-bit), Windows 10 (32/64-bit), Windows 11 (64-bit), Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 (64-bit), Macintosh OS v10.12.6 - v13x

* When multifunction roll unit is used.

* Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.

Print Language

Printer: SGRaster (Swift Graphic Raster), PDF, JPEG

Interface

Standard (Built-in): USB 2.0 Hi-Speed, 10/100/1000Base-T/TX, Wireless LAN (IEEE 802.11 b/g/n) *

Power Supply

AC 100-240 V (50-60 Hz)

Power Consumption

Max: Approx. 91 W
Standby: Approx. 1.7 W
Power Off: Approx. 0.1 W

Certifications

ENERGY STAR® (Worldwide), EPEAT Gold

Operational Environment

Temperature: 59 - 86°F (15 - 30°C)
Relative Humidity: 10% - 80% (Non Condensation)

Printer Dimensions (W x D x H) and Weight

43.7" x 38.7" x 46", 220 lbs. (with stand and basket open)

Printer Package Dimensions (W x D x H) and Weight

52.7" x 36" x 41", 276 lbs. (main unit with pallet)

Multifunction Roll Unit Dimensions

43.1" x 14" x 12.5", 35.3 lbs

Multifunction Roll Unit Package Dimensions

49" x 22.1" x 18.1", 57 lbs

Options

- Multifunction Roll Unit (RU-23)
- 2"/3" Roll Holder Set (RU-29)

User Replaceable Items

- Ink Tank: PFI-3100/PFI-2100 (160 ml), PFI-3300/PFI-2300 (330 ml), PFI-3700/PFI-2700 (700 ml)
- Print Head (PF-10)
- Maintenance Cartridge (MC-30)
- Cutter Blade (CT-07)

What's In The Box

Printer, 160 ml (GY/PBK) / 330 ml (MBK/C/M/Y/O) Starter Ink Tanks, 1 Printhead, Maintenance Cartridge (Installed), 2" Roll Holder with 3" Adapters, Installation Guide, User Registration Card, One Year Printer Warranty Statement, Printhead Warranty Statement, Call Center Notice, Media Compatibility Flyer, PosterArtist Web Notice Flyer, Safety and Environmental Information, iWR Service Terms Leaflet, USB port (High Speed), Power Cable and Screw, Gigabit Ethernet (Built-in)



usa.canon.com/largeformat

Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues.

Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. Some security features may impact functionality/performance; you may want to test these settings in your environment.

Canon and imagePROGRAF are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. PANTONE® is a trademark or registered trademark of PANTONE® LLC in the United States and/or other countries. As of April 1, 2026, according to professional services performed by PANTONE® under License Agreement between Canon, Inc. and PANTONE® LLC. PANTONE® Formula Guide Solid and Coated color gamut coverage rate is 96% for GP-6600S/4600S/2600S when using Premium Semi-Glossy Paper with imagePROGRAF printer driver at (600 dpi). As an ENERGY STAR® Partner, Canon U.S.A., Inc. has qualified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. Wi-Fi is a registered trademark of the Wi-Fi alliance. All other referenced product names and marks are trademarks of their respective owners. All printer output and screen images are simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2026 Canon U.S.A., Inc. All rights reserved.

04.17.26/26-0161-9841