

# WHERE PRECISION MEETS PRODUCTIVITY



imagePROGRAF TZ-32000 MFP Z36

**Canon**

**imagePROGRAF TZ-32000 MFP Z36**

# Printer Specifications

<b>Printhead</b> PF-06
<b>Technology</b> FINE (Photolithography Inkjet Nozzle Engineering)
<b>Print Resolution (Max.)</b> 2400 x 1200 dpi
<b>Line Accuracy<sup>1</sup></b> ±0.1% or Less
<b>Minimum Line Weight<sup>2</sup></b> 0.02 mm
<b>Number of Nozzles</b> Total: 15,360 Nozzles Matte Black: 5,120 Nozzles Other Colors: 2,560 Nozzles per Color
<b>Droplet Size</b> 5 Picoliter
<b>Ink Type</b> Pigment: Matte Black (MBK), Cyan (C), Magenta (M), Yellow (Y), Black (BK)
<b>Nozzle Pitch (Head Resolution)</b> 1200 dpi x Two Rows
<b>Ink Tank</b> Shipped with Printer: 330 ml MBK; 160 ml BK, C, Y, M Replacement: M: PFI-341 (330 ml)/PFI-741 (700 ml), MBK/BK/C/Y: PFI-340 (330 ml)/PFI-740 (700 ml)
<b>Ink Supply Method</b> Tubing System with Sub-tanks for Continuous Ink Supply
<b>Nozzle Recovery System</b> Non-firing Nozzle Detection and Compensation
<b>Printer Controller</b> L-COA PRO
<b>Printer RAM</b> 128 GB (Virtual), 2 GB (Physical)
<b>Hard Drive</b> 500 GB (Encrypted)
<b>Media Feed</b> Roll Feed: Two Rolls, Front Loading Cut Sheet: Front Loading
<b>Media Width</b> Roll Feed: 8" - 36" (203.2 mm - 917 mm) Cut Sheet: 8" - 36" (203.2 mm - 917 mm)
<b>Printable Margins</b> Roll Feed: All Sides: 0.12" (3 mm) or 0" for Borderless
<b>Maximum Print Length<sup>3</sup></b> Roll Feed: 59' (18 m) Cut Sheet: 24" (610 mm)
<b>Borderless Printing Widths (Roll Media Only)</b> Custom roll width 8" - 36" with micro margin technology
<b>Media Cutter</b> Automatic horizontal rotary cutter
<b>Media Thickness</b> 0.07 mm - 0.8 mm
<b>Media Core Sizes</b> 2" with 3" Core Adapters Included
<b>Maximum Roll Outer Diameter</b> 6.9" or Less
<b>Media Output</b> Front Output: Basket Top Output: Stack
<b>Printing Software Utilities</b> Accounting Manager, Canon Print Service, Device Management Console, Direct Print Plus, Printer Driver Extra Kit, Free Layout Plus, Media Configuration Tool, PosterArtist, CPP PRISMA Tech Suite, Canon Printer Driver, CPP Driver Select, Optimized Driver for AutoCAD, Canon PRINT Inkjet/SELPHY

<b>Operating System</b> Windows 7 (32/64-bit), Windows 8.1 (32/64-bit), Windows 10 (32/64-bit), Windows 11 (64-bit), Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 (64-bit), MacOS v10.15.7- MacOS 14
<b>Print Language</b> SGRaster, HP-GL/2, HP RTL, PDF, JPEG, CALS G4
<b>Interface</b> USB B Port: Hi-Speed USB (12 Mbit/sec, 480 Mbit/sec) USB A Port: USB thumb drive Gigabit Ethernet: IEEE 802.3u/ab/x (100/1000Base-T, Full Duplex), SNMP, HTTP, TCP/IP (IPv4/IPv6), FTP Wi-Fi: IEEE 802.11n/g/b
<b>Power Supply</b> AC 100 - 240 V (50 - 60 Hz)
<b>Power Consumption</b> Maximum: 111 W or Less Standby: 1.6 W or Less Power Off: 0.1 W or Less
<b>Certifications</b> International ENERGY STAR® Program (WW), TUV, CB, EPEAT Gold®
<b>Operational Environment</b> Temperature: 59° F - 86°F (15°C - 30°C) Relative Humidity: 10 - 80% (No Condensation)
<b>Printer Dimensions (W x D x H) and Weight</b> 60.9" x 37.8" x 46.8"; 454.2 lb. (Approx.)
<b>Package Dimensions (W x D x H) and Weight</b> 67.1" x 37.2" x 54.1"; 612.9 lb. (Approx.)
<b>Options</b> • 2"/3" Roll Holder Set (RH2-34)
<b>User-Replaceable Items</b> • Ink Tank (MBK/BK/C/Y: PFI-340/PFI-740; M: PFI-341/PFI-741) • Printhead (PF-06) • Maintenance Cartridge (MC-30)

**What's In The Box?**  
Includes Main Unit with Top Output Stacker, Basket, 2" Roll Holder with 3" Adapters, 1 Printhead, 1 Maintenance Cartridge (Installed), Starter Ink Tanks BK/C/M/Y (160 ml) MBK (330 ml), Installation Guide 1&2, User Registration Card, Printer Warranty Statement, Print Head Warranty Statement, Call Center Notice, Media Compatibility Flyer, PosterArtist Web Notice Flyer, iWR Service Terms Leaflet, Safety and Environmental Information, USB port (High Speed), Power Cable and Screw, Gigabit Ethernet (Built-In)

## Z36 Scanner Specifications

<b>Scan Speed<sup>5</sup></b> • 24-bit Color @ 200 dpi: Up to 3" per second • 8-bit Grayscale and Monochrome @ 200 dpi: Up to 13" per second
<b>Copy Speed</b> 24-bit Color @ 200 dpi: Up to 6" per second
<b>Color Space</b> sRGB
<b>Maximum Resolution</b> 1200 dpi (Optical)
<b>Scan Accuracy<sup>6</sup></b> +/- 0.1% : +/- 1 pixel
<b>Maximum Scan Width/Maximum Media Width</b> 36"/38"
<b>Maximum Scan Length</b> 164" (PDF); 315" (JPEG); 598" (TIFF)
<b>Maximum Media Thickness</b> 0.003" - 0.04" (0.07 mm - 1.0 mm)

## imagePROGRAF TZ-32000 MFP Z36

<b>Digital Imaging Technology</b> Contact Image Sensor (CIS) Technology (SingleSensor Assembly) • 24-bit RGB • 16-bit grayscale image capture • Panchromatic monochrome and black and white • Bi-directional LED light system for optimum object illumination and instant-on scanning capability
<b>Included Software</b> SmartWorks MFP Scan-to-Copy/File/Email with Real-time Image Viewer; supports TIFF, JPEG, and PDF
<b>Operating System</b> Windows 11 Enterprise LTSC (x64)
<b>Scanner Interface Kit</b> 3x USB 3.2 and 1x USB 2.0 rear and 1x USB 3.2 front, all type A
<b>Operating Environments</b> 10°C - 35°C, 10 - 90% RH, Non-condensing
<b>External Power Supply</b> 100 - 240 VAC Autosensing +/- 10%, 50 - 60 Hz
<b>Scanner Power Consumption</b> • <b>Controller Power:</b> 35W • <b>Sleep:</b> 0.2 W • <b>Idle:</b> 12.4 W • <b>Scanning Color/Grayscale at 200 dpi:</b> 22.7 W/23.3 W
<b>Compliances</b> ENERGY STAR®, CB(62368-1), CE, FCC(EMC), CuI/UL, CCC, NOM-019, EAC, C-TICK, VCCI, BIS, EMC +LOA, UL AR, WEEE, REACH, RoHS, EU - Tier 3 of Lot 6
<b>Scanner Package Dimensions (W x D x H) and Weight</b> (With Stand, Pallet, and Scanner) 50" x 17" x 19.5", 75 lb. (Approx.)

**What's In The Box?**  
Z36 Scanner with Power Cord, USB 3.0 Cable (2 m), 15.6" System Controller, 3:1 Trident Power Cord, Power Supply, Mount for Printer and System Controller, (2) Paper Edge Guides, (3) Document Return Guides, Calibration Target, Assembly and Startup Guide

<sup>1</sup>14 seconds for an ANSI D print and 4 ANSI D prints/minute speed measured after first print in Fast Q5 mode, using plain paper. Print speed is based on internal testing. Print speed may vary depending on the number of copies selected, as well as on the settings for size, type, and orientation of paper.  
<sup>2</sup>All speeds measured using plain paper, Fast Q5 mode. The 243 ANSI D prints/hour is measured from when the first print begins printing. Print speed is based on internal testing. Print speed may vary depending on the number of copies selected, as well as on the settings for size, type, and orientation of paper.

<sup>3</sup>Line accuracy repeatability is guaranteed after a user performs necessary adjustment and under the same environmental conditions. Applies to media for line drawing (Plain Paper, Coated Paper, CAD Translucent Matte Film, and CAD Tracing Paper) only.  
<sup>4</sup>Theoretical value based on data resolution.  
<sup>5</sup>The maximum printable length varies depending on the application, OS, and RIP used.  
<sup>6</sup>Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.  
<sup>7</sup>The scan rate is proportional across the full range of resolutions supported by the scanner. Actual scan times will depend on the host system performance. Quoted top speeds may be limited by the effective bandwidth of the USB 2 and is not guaranteed for all media types.  
<sup>8</sup>The quoted scan accuracy may vary depending on the operating environment and the thickness of the media.  
*Note: The imagePROGRAF TZ Series MFP Z36 systems contain multiple components, some of which are manufactured by third parties. To the extent that such third-party offerings come with limited warranties, such limited warranties are hereby passed to the purchaser, and Canon shall have no obligation or any liability with respect to such third-party offerings.*



1-844-50-CANON | [usa.canon.com/largeformat](https://usa.canon.com/largeformat)

