



Redefining the Large-Format Printer.

imagePROGRAF™ Series

Up to 2.9 D
Prints/Minute

Vivid, Eye-Catching Prints,
with New Magenta Ink

Creative and Workflow
Solutions Available



imagePROGRAF

TM-250

Printhead PF-06
Number of Nozzles Matte Black: 5,120 Nozzles Other Colors: 2,560 Nozzles per Color
Droplet Size 5 Picoliter
Ink Type Pigment: Matte Black (MBK), Cyan (C), Magenta (M), Yellow (Y), Black (BK)
Ink Tank Shipped with printer: MBK (130 ml), BK, C, M, Y (90 ml) Replacement: MBK, BK, C, Y: PFI-320 (300 ml)/PFI-120 (130 ml) and M: PFI-321 (300 ml)/PFI-121 (130 ml)
Printer RAM 2 GB
Media Feed Roll Feed: One Roll, Top-loading, Front Output
Media Width Roll Feed: 8"-24" (203.2 mm - 610 mm) Cut Sheet: 8"-24" (203.2 mm - 610 mm)
Media Cutter Automatic horizontal cutting (Rotary cutter): standard
Media Thickness 0" - 0.03" (0.07 mm - 0.8 mm)
Media Core Sizes 2" Core Standard. 2"/3" Core Roll Holder Set (RH2-28) Included
Maximum Roll Outer Diameter 5.9" (150 mm)
Media Output Stackable Basket
Printing Software Utilities Accounting Manager, Device Management Console, Direct Print Plus, Free Layout Plus, imagePROGRAF Printer Driver for Windows®/Mac®, Media Configuration Tool, PosterArtist, Canon PRINT Inkjet Selphy
Operating System Windows 7 (32/64-bit), Windows 8.1 (32/64-bit), Windows 10 (32/64-bit), Windows 11 (64-bit), Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 (64-bit), Macintosh OS v10.12.6-v13x
Print Language Printer: SGRaster, HP-GL/2, HP RTL, JPEG, CALS G4

Interface Standard (Built-in): USB 2.0 Hi-Speed, 10/100/ 1000Base-T/TX, Wireless LAN (IEEE 802.11 b/g/n)*
Power Supply AC 100 – 240V (50–60 Hz)
Power Consumption Max: Approx. 62W Standby: Approx. 1.6W Power Off: Approx. 0.1W
Certifications Environmental Certifications ENERGY STAR® certified, EPEAT Gold
Operational Environment Temperature: 59–86 °F (15–30 °C) Relative Humidity: 10% - 80% (Non Condensation)
Printer Dimensions (H x W x D) and Weight (With Basket Open) 41.7" x 38.5" x 34.2", 117.9 lbs.
Package Dimensions (H x W x D) and Weight (with stand, basket and pallet) 37.2" x 45.4" x 35.9", 209.4 lbs.
Options • 2"/3" Roll Holder Set (RH2-28) User-Replaceable Items • Ink Tank (300 ml: PFI-320/PFI-321, 130ml: PFI-120/PFI-121) • Printhead (PF-06) • Maintenance Cartridge (MC-31) • Cutter Blade (CT-08)
What's In The TM-250 Box Printer, Stand with Stackable Basket, Starter Ink Tanks BK/C/M/Y (90 ml) MBK (130 ml), 1 Printhead, Maintenance Cartridge (Installed), 2" Roll Holder with 3" Adapters, Installation Guide, User Registration Card, Printer Warranty Statement, Printhead Warranty Statement, Call Center Notice, Media Compatibility Flyer, PosterArtist Web Notice Flyer, Safety and Environmental Information, iWR Service Terms Leaflet, USB port (High Speed), Power Cable and Screw, Gigabit Ethernet (Built-in) * Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.



usa.canon.com/largeformat