



# Redefining the Large-Format Printer.

## imagePROGRAF™ Series

Up to 3.2 D  
Prints/Minute

Vivid, Eye-Catching Prints,  
with New Magenta Ink

Scan-to-Copy/File/  
Share Solution



**imagePROGRAF**

**TM-350 MFP Lm36**

# Specifications

imagePROGRAF

TM-350 MFP Lm36

<b>Printhead</b> PF-06	<b>Power Consumption</b> Max: Approx. 65W Standby: Approx. 1.6W Power Off: Approx. 0.1W	<b>Maximum Media Width</b> 38"
<b>Number of Nozzles</b> Matte Black: 5,120 Nozzles Other Colors: 2,560 Nozzles per Color	<b>Certifications</b> Environmental Certifications ENERGY STAR® certified, EPEAT Gold	<b>Maximum Scan Length</b> 109" (PDF)
<b>Droplet Size</b> 5 Picoliter	<b>Operational Environment</b> Temperature: 59–86 °F (15–30 °C) Relative Humidity: 10% -80% (Non Condensation)	<b>Maximum Media Thickness</b> 0.003" - 0.03" (0.07 mm - 0.8 mm)
<b>Ink Type</b> Pigment: Matte Black (MBK), Cyan (C), Magenta (M), Yellow (Y), Black (BK)	<b>TM-350 MFP Lm36 Dimension (H x W x D) and Weight</b> 50.24" x 50.6" x 34.2" Approx. 155.4 lb.	<b>Digital Imaging Technology</b> Contact Image Sensor (CIS) Technology (SingleSensor Assembly) <ul style="list-style-type: none"><li>• 24-bit RGB digital color image capture</li><li>• 16-bit grayscale image capture</li><li>• Panchromatic monochrome and black-and-white</li><li>• Bi-directional extra long-life LED light system for optimum object illumination and instant-on scanning capability</li></ul>
<b>Ink Tank</b> Shipped with printer: MBK (130 ml), BK, C, M, Y (90 ml) Replacement: MBK, BK, C, Y: PFI-320 (300 ml)/PFI-120 (130 ml) and M: PFI-321 (300 ml)/PFI-121 (130 ml)	<b>Package Dimensions (H x W x D) and Weight</b> 31.5" x 57.6" x 35.9" Approx. 224.9 lb.	<b>Included Software</b> ScanAppL
<b>Printer RAM</b> 2 GB	<b>Options</b> <ul style="list-style-type: none"><li>• 2"/3" Roll Holder Set (RH2-35)</li></ul> <b>User-Replaceable Items</b> <ul style="list-style-type: none"><li>• Ink Tank (300 ml: PFI-320/PFI-321, 130 ml: PFI-120/PFI-121)</li><li>• Printhead (PF-06)</li><li>• Maintenance Cartridge (MC-31)</li><li>• Cutter Blade (CT-08)</li></ul>	<b>Operating Environment</b> 10–35 °C, 10% - 90% RH
<b>Media Feed</b> Roll Feed: One Roll, Top-loading, Front Output	<b>What's In The Printer Box</b> Printer, Stand with Stackable Basket, Starter Ink Tanks BK/C/M/Y (90 ml) MBK (130 ml), 1 Printhead, Maintenance Cartridge (Installed), 2" Roll Holder with 3" Adapters, Installation Guide, User Registration Card, Printer Warranty Statement, Printhead Warranty Statement, Call Center Notice, Media Compatibility Flyer, PosterArtist Web Notice Flyer, Safety and Environmental Information, iWR Service Terms Leaflet, USB port (High Speed), Power Cable and Screw, Gigabit Ethernet (Built-in)	<b>External Power Supply</b> 100–240 VAC +/- 10%, 50–60 Hz
<b>Media Width</b> Roll Feed: 8"-36" (203.2 - 917 mm) Cut Sheet: 8"-36" (203.2 - 917 mm)		<b>Scanner Power Consumption</b> Sleep/Idle: 0.6W/11.7W Scanning Color/Grayscale @ 200 dpi: 17.5W
<b>Media Cutter</b> Automatic horizontal cutting (Rotary cutter): standard		<b>Compliance</b> ENERGY STAR®, UL, FCC
<b>Media Thickness</b> 0" - 0.03" (0.07 mm - 0.8 mm)		<b>Scanner Dimensions (H x W x D)</b> (With Doc Return Guide - Paper Tray flat) 5.2" x 48.7" x 10"
<b>Media Core Sizes</b> 2" Core Standard. 2"/3" Core Roll Holder Set (RH2-35) Included		<b>Scanner Weight</b> 14.5 lbs.
<b>Maximum Roll Outer Diameter</b> 5.9" (150 mm)		<b>What's In The Scanner Box?</b> <ul style="list-style-type: none"><li>• Lm36 Scanner</li><li>• Printer mounting brackets, fixings, and 3 mm tool</li><li>• 2 paper edge guides</li><li>• Document return guides (3 for Lm36)</li><li>• Calibration target</li><li>• Lm36 Scanner Quick Start Guide</li><li>• Ethernet cable (2 meter)</li><li>• Power supply</li><li>• Power Supply Regional - Mains power cord(s) (2 meter)</li></ul> <ul style="list-style-type: none"><li>■ Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.</li><li>■ The scan rate is proportional across the full range of resolutions supported by the scanner. Actual scan times will depend on the host system performance. Quoted top speeds may be limited by the effective bandwidth of the USB 2 and is not guaranteed for all media types.</li><li>▲ The quoted scan accuracy may vary depending on the operating environment and the thickness of the media.</li></ul> <p>Note: The imagePROGRAF TM Series MFP Lm36 systems contain multiple components, some of which are manufactured by third parties. To the extent that such third-party offerings come with limited warranties, such limited warranties are hereby passed to the purchaser, and Canon shall have no obligation or any liability with respect to such third-party offerings.</p>
<b>Media Output</b> Stackable Basket	<b>Lm36 SCANNER</b>	
<b>Printing Software Utilities</b> Accounting Manager, Device Management Console, Direct Print Plus, Free Layout Plus, imagePROGRAF Printer Driver for Windows®/Mac®, Media Configuration Tool, PosterArtist Lite, Canon PRINT Inkjet Selphy	<b>Scan Speed ■■</b> <ul style="list-style-type: none"><li>• Color: Up to 1.5" per second at 200dpi</li><li>• Mono or B/W: Up to 4.5" per second at 200dpi</li></ul>	
<b>Operating System</b> Windows 7 (32/64-bit), Windows 8.1 (32/64-bit), Windows 10 (32/64-bit), Windows 11 (64-bit), Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 (64-bit), Macintosh OS v10.12.6-v13x	<b>Scan Modes</b> <ul style="list-style-type: none"><li>• 16.7 Million Color RGB (24-bit)</li><li>• 256-level Grayscale (8-bit)</li><li>• Black-and-white (1-bit)</li></ul>	
<b>Print Language</b> Printer: SGRRaster, HP-GL/2, HP RTL, JPEG, CALS G4	<b>Color Space</b> sRGB	
<b>Interface</b> Standard (Built-in): USB 2.0 Hi-Speed, 10/100/1000Base-T/TX, Wireless LAN (IEEE 802.11 b/g/n)■	<b>Maximum Resolution</b> 600 dpi (Optical)	
<b>Power Supply</b> AC 100–240 V (50–60 Hz)	<b>Scan Accuracy▲</b> +/- 0.2% : +/- 1 pixel	
	<b>Maximum Scan Width</b> 36"	



Canon

usa.canon.com/largeformat