

# WHERE PRECISION MEETS PRODUCTIVITY



imagePROGRAF TX-3200 MFP Z36

**Canon**

**imagePROGRAF TX-3200 MFP Z36**

# Printer Specifications

<b>Printhead</b> PF-06
<b>Technology</b> FINE (Photolithography Inkjet Nozzle Engineering)
<b>Print Resolution (Max.)</b> 2400 x 1200 dpi
<b>Line Accuracy<sup>1</sup></b> ±0.1% or Less
<b>Minimum Line Weight<sup>2</sup></b> 0.02 mm
<b>Number of Nozzles</b> Matte Black: 5,120 Nozzles Other Colors: 2,560 Nozzles per Color
<b>Droplet Size</b> 5 Picoliter
<b>Nozzle Pitch (Head Resolution)</b> 1200 dpi x Two Rows
<b>Ink Type</b> Pigment: Matte Black (MBK), Cyan (C), Magenta (M), Yellow (Y), Black (BK)
<b>Ink Tank</b> Shipped with Printer: 160 ml C/Y/M/BK; 330 ml MBK Replacement: M: PFI-111 (160 ml)/PFI-311 (330 ml)/ PFI-711 (700 ml), MBK/BK/C/Y: PFI-110 (160 ml)/PFI-310 (330 ml)/PFI-710 (700 ml)
<b>Ink Supply Method</b> Tubing System with Sub-tanks for Continuous Ink Supply
<b>Nozzle Recovery System</b> Non-firing Nozzle Detection and Compensation
<b>Printer Controller</b> L-COA PRO
<b>Printer RAM</b> 128 GB (Virtual), 2 GB (Physical)
<b>Hard Drive</b> 500 GB (Encrypted)
<b>Media Feed</b> Roll Feed: One Roll, Front-loading, Front Output
<b>Media Width</b> Roll Feed: 6"-36" (152 mm - 917 mm) Cut Sheet: 6"-36" (152 mm - 974 mm)
<b>Printable Margins</b> Roll Feed: All Sides: 0.12" (3 mm) or 0" for Borderless
<b>Maximum Print Length (Single Page)<sup>3</sup></b> Roll Feed: 59' (18 m) Cut Sheet: 63" (1.6 m)
<b>Borderless Printing Widths (Roll Media Only)</b> Custom Roll Width 6" - 36" with Micro Margin Technology
<b>Media Cutter</b> Automatic horizontal rotary cutter
<b>Media Thickness</b> 0.07 mm - 0.8 mm
<b>Media Core Sizes</b> 2" with 3" Core Adapters Included
<b>Maximum Roll Outer Diameter</b> 6.7" (170 mm)
<b>Media Output Options</b> TX Stacker, Multipositional Catch Basket
<b>Printing Software Utilities</b> Accounting Manager, Canon Print Service, Canon Production Printing (CPP) Driver Select, Canon Production Printing (CPP) PRISMA Tech Suite, Device Management Console, Direct Print Plus, Free Layout Plus, imagePROGRAF Printer Driver for Windows®/Mac®, Media Configuration Tool, PosterArtist, Optimized Driver for AutoCAD, Quick Utility Toolbox, Canon PRINT Inkjet/SELPHY
<b>Operating System</b> Windows 7 (32/64-bit), Windows 8.1 (32/64-bit), Windows 10 (32/64-bit), Windows 11 (64-bit), Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 (64-bit), MacOS v10.15.7- MacOS 14

<b>Print Language</b> SGRaster, HP-GL/2, HP RTL, PDF, JPEG, CALS G4
<b>Interface</b> <b>USB B Port:</b> Hi-Speed USB (12 Mbit/sec, 480 Mbit/sec) <b>USB A Port:</b> USB thumb drive <b>Gigabit Ethernet:</b> IEEE 802.3u/ab/x (100/1000Base-T, Full Duplex), SNMP, HTTP, TCP/IP (IPv4/IPv6), FTP <b>Wi-Fi:</b> IEEE 802.11n/g/b
<b>Acoustic Noise</b> <b>Operation Approx:</b> 51 dB (A) <b>Standby Approx:</b> 35 dB (A) <b>Acoustic Power:</b> Approx 6.9Bels
<b>Power Supply</b> AC 100 - 240 V (50 - 60 Hz)
<b>Power Consumption</b> <b>Maximum:</b> Approx. 86 W <b>Standby:</b> Approx. 1.7 W <b>Power Off:</b> Approx. 0.1 W
<b>Certifications</b> ENERGY STAR® certified, EPEAT Gold, TUV, CB
<b>Operational Environment</b> <b>Temperature:</b> 59 °F - 86 °F (15 °C - 30 °C) <b>Relative Humidity:</b> 10% - 80% (No Condensation)
<b>Printer Dimensions (W x D x H) and Weight</b> <b>With Basket Open:</b> 54.7" x 38.7" x 46"; 231.5 lb. (Approx.) <b>With Basket Closed:</b> 54.7" x 30.2" x 46"; 231.5 lb. (Approx.) <b>With Stacker Opened:</b> 54.7" x 46.8" x 46"; 258 lb. (Approx.) <b>With Stacker Closed:</b> 54.7" x 44.2" x 46"; 258 lb. (Approx.)
<b>Package Dimensions (W x D x H) and Weight</b> <b>Printer (Main Unit with Stand and Pallet):</b> 64" x 35.6" x 40.7"; 337 lb. (Approx.) <b>Basket:</b> 56" x 21.9" x 8.4"; 20 lb. (Approx.) <b>Stacker:</b> 49.2" x 35.7" x 11.5"; 60 lb. (Approx.) <b>Roll Unit:</b> 60" x 22.1" x 18.1"; 68.3 lb. (Approx.)

<b>Options</b> <ul style="list-style-type: none"><li>• Multifunction Roll System (RU-32)</li><li>• 2"/3" Roll Holder Set (RH2-34)</li></ul>
<b>User-Replaceable Items</b> <ul style="list-style-type: none"><li>• Ink Tank (PFI-110/111, PFI-310/311, PFI-710/711)</li><li>• Printhead (PF-06)</li><li>• Maintenance Cartridge (MC-30)</li><li>• Cutter Blade (CT-07)</li></ul>
<b>What's In The Box?</b> Includes Main Unit, TX Stacker or Multi-Positional Catch Basket, Stand, (1)Printhead, Starter Ink Tank Set, (1) Maintenance Cartridge (Installed), 2" Roll Holder with 3" Adapters, Installation Guide, User Registration Card, Printer Warranty Statement, Printhead Warranty Statement, Call Center Notice, Media Compatibility Flyer, PosterArtist Web Notice Flyer, iWR Service Terms Leaflet, Safety and Environmental Information, USB port (High Speed), Power Cable & Screw, Gigabit Ethernet (Built-In)

# Z36 Scanner Specifications

<b>Scan Speed<sup>4</sup></b> <ul style="list-style-type: none"><li>• 24-bit Color @ 200 dpi: 3" (Per Second)</li><li>• 8-bit Grayscale and Monochrome @ 200 dpi: 13" (Per Second)</li></ul>
<b>Copy Speed</b> 24-bit Color @ 200 dpi: 6" (Per Second)
<b>Color Space</b> sRGB
<b>Maximum Resolution</b> 1200 dpi (Optical)
<b>Scan Accuracy<sup>6</sup></b> +/- 0.1% : +/- 1 pixel
<b>Maximum Scan Width/Maximum Media Width</b> 36"/38"
<b>Maximum Scan Length</b> 164' (PDF); 315" (JPEG); 598" (TIFF)
<b>Maximum Media Thickness</b> 0.003" - 0.04" (0.07 mm - 1.0 mm)

# imagePROGRAF TX-3200 MFP Z36

<b>Digital Imaging Technology</b> Contact Image Sensor (CIS) Technology (SingleSensor Assembly) <ul style="list-style-type: none"><li>• 24-bit RGB</li><li>• 16-bit grayscale image capture</li><li>• Panchromatic monochrome and black and white</li><li>• Bi-directional extra long-life LED light system for optimum object illumination and instant-on scanning capability</li></ul>
<b>Included Software</b> SmartWorks MFP Scan-to-Copy/File/Email with Real-time Image Viewer; supports TIFF, JPEG, and PDF
<b>Operating System</b> Windows 11 Enterprise LTSC (x64)
<b>Scanner Interface Kit</b> 3x USB 3.2 and 1x USB 2.0 rear and 1x USB 3.2 front, all type A
<b>Operating Environments</b> 10 °C - 35 °C, 10% - 90% RH, Non-condensing
<b>External Power Supply</b> 100 - 240 VAC Autosensing +/- 10%, 50-60 Hz
<b>Scanner Power Consumption</b> <ul style="list-style-type: none"><li>• <b>Controller Power:</b> Approx. 35 W</li><li>• <b>Sleep:</b> Approx. 0.2 W</li><li>• <b>Idle:</b> Approx. 12.4 W</li><li>• <b>Scanning Color/Grayscale at 200 dpi:</b> Approx. 22.7 W/23.3 W</li></ul>
<b>Compliances</b> ENERGY STAR®, CB(62368-1), CE, FCC(EMC), CuI/UL, CCC, NOM-019, EAC, C-TICK, VCCI, BIS, EMC +LOA, UL AR, WEEE, REACH, RoHS, EU - Tier 3 of Lot 6
<b>Scanner Package Dimensions (W x D x H) and Weight</b> (With Stand, Pallet, and Scanner) 50" x 17" x 19.5", 75 lb. (Approx.)

<b>What's In The Box?</b> Z36 Scanner with Power Cord, USB 3.0 Cable (2 m), 15.6" System Controller, 3:1 Trident Power Cord, Power Supply, Mount for Printer and System Controller, (2) Paper Edge Guides, (3) Document Return Guides, Calibration target, Assembly and Start Up Guide, 3:1 Trident Power Cord
---

<sup>1</sup>Line accuracy repeatability is guaranteed after a user performs the necessary adjustment and under the same environmental conditions. Applies to media for line drawing (Plain Paper, Coated Paper, CAD Translucent Matte Film, and CAD Tracing Paper) only.  
<sup>2</sup>Theoretical value based on data resolution.  
<sup>3</sup>The maximum printable length varies depending on the application, OS, and RIP used.  
<sup>4</sup>Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.  
<sup>5</sup>The scan rate is proportional across the full range of resolutions supported by the scanner. Actual scan times will depend on the host system performance. Quoted top speeds may be limited by the effective bandwidth of the USB 2 and is not guaranteed for all media types.  
<sup>6</sup>The quoted scan accuracy may vary depending on the operating environment and the thickness of the media.

Note: The imagePROGRAF TX Series MFP Z36 systems contain multiple components, some of which are manufactured by third parties. To the extent that such third-party offerings come with limited warranties, such limited warranties are hereby passed to the purchaser, and Canon shall have no obligation or any liability with respect to such third-party offerings.

