


More Than Just the Fine Line

- Updated matte black ink for crisper lines and vibrant poster prints on plain paper
- Scan-to-Copy/File/Share solution available
- Security features to help protect your work




imagePROGRAF TX-3300



imagePROGRAF TX-3310 MFP Z36

OCTOBER
11-13
10am-4pm



ACTIVITIES & HIGHLIGHTS:

PUBLISHER SHOWCASES & NEW TITLE PREVIEWS | AUTHOR KEYNOTE SPEECHES BY INDUSTRY LEADERS | DIGITAL RIGHTS & LICENSING EXCHANGE | PROFESSIONAL

Printer Specifications

Printhead

PF-06

Technology

FINE (Photolithography Inkjet Nozzle Engineering)

Print Resolution (Max.)

2400 x 1200 dpi

Line Accuracy¹

±0.1% or Less

Minimum Line Weight²

0.02 mm

Number of Nozzles

Matte Black: 5,120 Nozzles
Other Colors: 2,560 Nozzles per Color

Droplet Size

5 Picoliter

Nozzle Pitch (Head Resolution)

1200 dpi x Two Rows

Ink Type

Pigment: Matte Black (MBK), Cyan (C), Magenta (M),
Yellow (Y), Black (BK)

Ink Tank

Shipped with Printer:
160ml C/Y/M/BK; 330ml MBK

Replacement:

MBK: PFI-113 (160ml)/PFI-313 (330ml)/PFI-713 (700ml)
M: PFI-111 (160ml)/PFI-311 (330ml)/PFI-711 (700ml)
BK/C/Y: PFI-110 (160ml)/PFI-310 (330ml)/PFI-710 (700ml)

Ink Supply Method

Tubing System with Sub-tanks for Continuous Ink Supply

Nozzle Recovery System

Non-firing Nozzle Detection and Compensation

Printer Controller

L-COA PRO

Printer RAM

128 GB (Virtual), 2 GB (Physical)

Hard Drive

256 GB (Encrypted)

Media Feed

Roll Feed: One Roll, Front-loading, Front Output

Media Width

Roll Feed: 6" – 36" (152 mm – 917 mm)
Cut Sheet: 6" – 36" (152 mm – 917 mm)

Printable Margins

Roll Feed: All Sides: 0.12" (3 mm) or 0" for Borderless

Maximum Print Length (Single Page)³

Roll Feed: 59' (18 m)
Cut Sheet: 63" (1.6 m)

Borderless Printing Widths (Roll Media Only)

Custom Roll Width 6" – 36" with Micro Margin Technology

Media Cutter

Automatic horizontal rotary cutter

Media Thickness

0.07 mm – 0.8 mm

Media Core Sizes

2" with 3" Core Adapters Included

Maximum Roll Outer Diameter

6.7" (170 mm)

Media Output Options

TX Stacker, Multipositional Flat Stacking Basket⁷

Printing Software Utilities

Accounting Manager, Canon Print Service, Canon
Production Printing (CPP) Driver Select, Canon Production
Printing (CPP) PRISMA Tech Suite, Device Management
Console, Direct Print Plus, Free Layout Plus, Driver, Media
Configuration Tool, PosterArtist, Quick UtilityToolbox

Operating System

Windows 7, 8.1, 10 (32/64-bit), Windows 11 (64-bit),
Windows Server 2008R2, 2012, 2012R2, 2016, 2019,
2022 (64-bit), MacOS v10.15.7- MacOS 14

Print Language

SGRaster, HP-GL/2, HP RTL, PDF, JPEG, CALS G4

Interface

USB B Port: Hi-Speed USB (12 Mbit/sec, 480 Mbit/sec)
USB A Port: USB drive
Gigabit Ethernet: IEEE 802.3u/ab/x (100/1000Base-T,
Full Duplex), SNMP, HTTP, TCP/IP (IPv4/IPv6), FTP
Wi-Fi: IEEE 802.11n/g/b

Acoustic Noise

Operation Approx: 51 dB (A)
Standby Approx: 35 dB (A)
Acoustic Power: Approx 6.9 Bels

Power Supply

AC 100–240 V (50 – 60 Hz)

Power Consumption

Maximum: Approx. 83 W
Standby: Approx. 1.7 W
Power Off: Approx. 0.1 W

Certifications

ENERGY STAR[®] certified, EPEAT 1.0 Gold

Operational Environment

Temperature: 59°F – 86°F (15°C – 30°C)
Relative Humidity: 10% – 80% (No Condensation)

Printer Dimensions (W x D x H) and Weight (Approx.)

With Basket Open: 54.7" x 41.1" x 46"; 242.5 lbs.
With Basket Closed: 54.7" x 30.2" x 46"; 242.5 lbs.
With Stacker Opened: 54.7" x 46.8" x 46"; 253.5 lbs.
With Stacker Closed: 54.7" x 44.2" x 46"; 253.5 lbs.

Printer Package Dimensions (W x D x H) and Weight (Approx.)

Printer (Main Unit with Stand and Pallet):
62.9" x 35.5" x 44.2"; 352.7 lbs.
Basket: 52" x 34" x 241.4"; 59.5 lbs.
Stacker: 49.2" x 35.7" x 11.5"; 57.3 lbs.
Roll Unit: 60" x 22.1" x 18.1"; 66.1 lbs.

Options

- Multifunction Roll System (RU-34)
- 2"/3" Roll Holder Set (RH2-34)

User-Replaceable Items

- Ink Tank (PFI-110/111/113, PFI-310/311/313,
PFI-710/711/713)
- Printhead (PF-06)
- Maintenance Cartridge (MC-30)
- Cutter Blade (CT-07)

What's In The Box

Includes Main Unit, TX Stacker or Multi-Positional Flat
Stacking Basket, Stand, (1) Printhead, Starter Ink Tank Set,
(1) Maintenance Cartridge (Installed), 2" Roll Holder with 3"
Adapters, Installation Guide, User Registration Card,
Printer Warranty Statement, Printhead Warranty Statement,
Call Center Notice, Media Compatibility Flyer, PosterArtist
Web Notice Flyer, iWR Service Terms Leaflet, Safety and
Environmental Information, USB port (High Speed), Power
Cable & Screw, Gigabit Ethernet (Built-In)

Z36 Scanner Specifications

Scan Speed⁵

- 24-bit Color @ 200 dpi: 3" (Per Second)
- 8-bit Grayscale and Monochrome @ 200 dpi:
13" (Per Second)

Copy Speed

24-bit Color @ 200 dpi: 6" (Per Second)

Color Space

sRGB

Maximum Resolution

1200 dpi (Optical)

imagePROGRAF TX-3300
imagePROGRAF TX-3310 MFP Z36

Scan Accuracy⁶

+/- 0.1% : +/- 1 pixel

Maximum Scan Width/Maximum Media Width

36"/38"

Maximum Scan Length

164" (PDF); 315" (JPEG); 598" (TIFF)

Maximum Media Thickness

0.003" – 0.04" (0.07 mm – 1.0 mm)

Digital Imaging Technology

Contact Image Sensor (CIS) Technology
(SingleSensor Assembly)
• 24-bit RGB
• 16-bit grayscale image capture
• Panchromatic monochrome and black-and-white
• Bi-directional extra long-life LED light system for
optimum object illumination and instant-on
scanning capability

Included Software

SmartWorks MFP Scan-to-Copy/File/Email with
Real-time Image Viewer; supports TIFF, JPEG, and PDF

Operating System

Windows 11 Enterprise LTSC (x64)

Scanner Interface Kit

3x USB 3.2 and 1x USB 2.0 rear and 1x USB 3.2 front,
all type A

Operating Environments

10°C – 35°C, 10% – 90% RH, Non-condensing

External Power Supply

100–240 VAC Autosensing +/- 10%, 50–60 Hz

Scanner Power Consumption

- Controller Power: Approx. 35 W
- Sleep: Approx. 0.2 W
- Idle: Approx. 12.4 W
- Scanning Color/Grayscale at 200 dpi:
Approx. 22.7 W/23.3 W

Compliances

ENERGY STAR[®], CB(62368-1), CE, FCC(EMC), Cu/UL, CCC,
NOM-019, EAC, C-TICK, VCCI, BIS, EMC +LOA, UL AR, WEEE,
REACH, RoHS, EU - Tier 3 of Lot 6

Scanner Package Dimensions (W x D x H) and Weight

(With Stand, Pallet, and Scanner)
50" x 17" x 19.5", 75 lb. (Approx.)

What's In The Box

Z36 Scanner with Power Cord, USB 3.0 Cable (2 m), 15.6"
System Controller, 3:1 Trident Power Cord, Power Supply,
Mount for Printer and System Controller, (2) Paper Edge
Guides, (3) Document Return Guides, Calibration target,
Assembly and Start Up Guide, 3:1 Trident Power Cord

¹ Line accuracy repeatability is guaranteed after a user performs the
necessary adjustment and under the same environmental conditions.
Applies to media for line drawing (Plain Paper, Coated Paper,
CAD Translucent Matte Film, and CAD Tracing Paper) only.

² Theoretical value based on data resolution.

³ The maximum printable length varies depending on the application,
OS, and RIP used.

⁴ Wireless printing requires a working network with wireless 802.11b/g
or 802.11n capability. Wireless performance may vary based on terrain
and distance between the printer and wireless network clients.

⁵ The scan rate is proportional across the full range of resolutions
supported by the scanner. Actual scan times will depend on the host
system performance. Quoted top speeds may be limited by the effective
bandwidth of the USB 2 and is not guaranteed for all media types.

⁶ The quoted scan accuracy may vary depending on the operating
environment and the thickness of the media.

⁷ Expected availability Q4 2026.

*Note: The imagePROGRAF TX Series MFP Z36 systems contain multiple
components, some of which are manufactured by third parties. To the extent that
such third-party offerings come with limited warranties, such limited warranties are
hereby passed to the purchaser, and Canon shall have no obligation or any liability
with respect to such third-party offerings.*



Canon

usa.canon.com/largeformat

Canon and imagePROGRAF are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Wi-Fi is a registered trademark of the Wi-Fi alliance. All other referenced product names and marks are trademarks of their respective owners. PRISMA is a registered trademarks of Canon Production Printing Netherlands B.V. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. Some security features may impact functionality/performance; you may want to test these settings in your environment. All printer output and screen images are simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors. Neither Canon Inc. nor Canon U.S.A., Inc. represents or warrants any third-party product or feature referenced hereunder.

As an ENERGY STAR[®] Partner, Canon U.S.A., Inc. has qualified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency.

The company(ies) portrayed, and the name(s) used herein are fictitious. Any resemblance to any other company or person is coincidental and unintentional.

©2026 Canon U.S.A., Inc. All rights reserved.

09.15.26/26-1153-15644