

WHERE PRECISION MEETS PRODUCTIVITY



imagePROGRAF TZ-32000

Canon

imagePROGRAF TZ-32000

Printer Specifications

imagePROGRAF TZ-32000

Printhead PF-06	Borderless Printing Widths (Roll Media Only) Custom roll width 8" - 36" with micro margin technology	Package Dimensions (W x D x H) and Weight 67.1" x 37.2" x 54.6"; 644 lb. (Approx.)
Technology FINE (Photolithography Inkjet Nozzle Engineering)	Media Cutter Automatic horizontal rotary cutter	Options • 2"/3" Roll Holder Set (RH2-34)
Print Resolution (Max.) 2400 x 1200 dpi	Media Thickness 0.07 mm – 0.8 mm	User-Replaceable Items • Ink Tank (MBK/BK/C/Y: PFI-340/PFI-740; M: PFI-341/PFI-741) • Printhead (PF-06) • Maintenance Cartridge (MC-30)
Line Accuracy¹ ±0.1% or Less	Media Core Sizes 2" with 3" Core Adapters Included	What's In The Box? Includes Main Unit with Top Output Stacker, Basket, 2" Roll Holder with 3" Adapters, 1 Printhead, 1 Maintenance Cartridge (Installed), Starter Ink Tanks BK/C/M/Y (160 ml) MBK (330 ml), Installation Guide 1&2, User Registration Card, Printer Warranty Statement, Print Head Warranty Statement, Call Center Notice, Media Compatibility Flyer, PosterArtist Web Notice Flyer, iWR Service Terms Leaflet, Safety and Environmental Information, USB port (High Speed), Power Cable and Screw, Gigabit Ethernet (Built-In)
Minimum Line Weight² 0.02 mm	Maximum Roll Outer Diameter 6.9" or Less	¹ Line accuracy repeatability is guaranteed after a user performs necessary adjustment and under the same environmental conditions. Applies to media for line drawing (Plain Paper, Coated Paper, CAD Translucent Matte Film, and CAD Tracing Paper) only.
Number of Nozzles Total: 15,360 Nozzles Matte Black: 5,120 Nozzles Other Colors: 2,560 Nozzles per Color	Media Output Front Output: Basket Top Output: Stacker	² Theoretical value based on data resolution.
Droplet Size 5 Picoliter	Printing Software Utilities Accounting Manager, Canon Print Service, Device Management Console, Direct Print Plus, Printer Driver Extra Kit, Free Layout Plus, Media Configuration Tool, PosterArtist, CPP PRISMA Tech Suite, Canon Printer Driver, CPP Driver Select, Optimized Driver for AutoCAD, Canon PRINT Inkjet/SELPHY	³ The maximum printable length varies depending on the application, OS, and RIP used.
Ink Type Pigment: Matte Black (MBK), Cyan (C), Magenta (M), Yellow (Y), Black (BK)	Operating System Windows 7 (32/64-bit), Windows 8.1 (32/64-bit), Windows 10 (32/64-bit), Windows 11 (64-bit), Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 (64-bit), MacOS v10.15.7- MacOS 14	⁴ Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.
Nozzle Pitch (Head Resolution) 1200 dpi x Two Rows	Print Language SGRaster, HP-GL/2, HP RTL, PDF, JPEG, CALS G4	
Ink Tank Shipped with Printer: 330 ml MBK; 160 ml BK, C, Y, M Replacement: M: PFI-341 (330 ml)/PFI-741 (700 ml), MBK/BK/C/Y: PFI-340 (330 ml)/PFI-740 (700 ml)	Interface USB B Port: Hi-Speed USB (12 Mbit/sec, 480 Mbit/sec) USB A Port: USB thumb drive Gigabit Ethernet: IEEE 802.3u/ab/x (100/1000Base-T, Full Duplex), SNMP, HTTP, TCP/IP (IPv4/IPv6), FTP Wi-Fi: IEEE 802.11n/g/b	
Ink Supply Method Tubing System with Sub-tanks for Continuous Ink Supply	Power Supply AC 100–240 V (50–60 Hz)	
Nozzle Recovery System Non-firing Nozzle Detection and Compensation	Power Consumption Maximum: Approx. 111 W Standby: Approx. 1.6 W Power Off: Approx. 0.1 W	
Printer Controller L-COA PRO	Certifications ENERGY STAR® certified, EPEAT Gold, TUV, CB	
Printer RAM 128 GB (Virtual), 2 GB (Physical)	Operational Environment Temperature: 59 °F - 86 °F (15 °C - 30 °C) Relative Humidity: 10% - 80% (No Condensation)	
Hard Drive 500 GB (Encrypted)	Printer Dimensions (W x D x H) and Weight 60.9" x 37.8" x 46.8"; 454.2 lb. (Approx.)	
Media Feed Roll Feed: Two Rolls, Front Loading Cut Sheet: Front Loading		
Media Width Roll Feed: 8" - 36" (203.2 mm –917 mm) Cut Sheet: 8" - 36" (203.2 mm –917 mm)		
Printable Margins Roll Feed: All Sides: 0.12" (3 mm) or 0" for Borderless		
Maximum Print Length³ Roll Feed: 59' (18 m) Cut Sheet: 24" (610 mm)		



usa.canon.com/LargeFormat

