

Environmental Profile Sheet

The imageRUNNER ADVANCE DX 8905i/8995i/8986i models incorporate technologies with a strong environmental focus at every stage of the product life cycle—Produce, Use, and Recycle. The technologies below focus on Energy Conservation, Resource Conservation, and Pollution Prevention and form the foundation of Canon’s Environmental Management System.

	Energy Conservation	Resource Conservation	Pollution Prevention
In order to help reduce dependence on petroleum-based materials, Canon uses 100% reused plastics .*			
A variety of sleep recovery triggers help encourage the use of Sleep Mode , helping to minimize power consumption.			
Power consumption in Sleep Mode is as low as 0.90 W!			
Low Typical Electricity Consumption (TEC) values , which measure power consumption during a one-week period.			
Power consumption is reduced by utilizing White LED array technology in its Color Image Reader versus using a traditional Xenon tube!			
Power consumption is reduced by utilizing Canon Image Sensor technology versus using traditional CCD sensors! Advanced Color RAPID Fusing technologies help reduce power consumption and limit the warm-up period .			
Low Melting Temperature Toner helps reduce fusing temperature requirements .			
All suppliers are required to meet Canon’s stringent Green Procurement policy and environmental terms. This helps Canon exceed the tough European Union’s RoHS Directive, which controls/restricts the use of certain hazardous substances .			
Each system is equipped with paper-, toner-, and energy-saving features that help to cut costs and conserve resources .			
Long-life parts and high-yield supplies help maximize uptime and help reduce the amount of materials consumed during the product life cycle.			

* Excluding a small amount of additives to improve physical properties.

Canon. The Natural Partner for Business.



imageRUNNER ADVANCE DX 8905 shown with optional accessories.

Environment-Related Specifications

System Type

Monochrome Laser Multifunctional

Functions

Standard:	Print (UFR III, PCL® 6, Adobe® PostScript® 3™), Copy, Scan, Send, Store
Optional:	Fax (Up to 4 lines)

Operation Panel

Standard:	10.1" TFT LCD WSVGA Color Flat-Panel
-----------	--------------------------------------

Warm-up Time

From Power On:	Approx. 60 Seconds
From Sleep Mode:	Approx. 60 Seconds

Power Requirements	110-127 V AC, 60 Hz, 16 A
---------------------------	---------------------------

Power Consumption

Maximum:	2,032 W
Sleep Mode:	0.90 W
Copying/Printing:	1,533 W
Plug-in	
Quick Startup Mode "OFF":	0.5 W
Quick Startup Mode "ON":	0.5 W
Production Efficiency (Wh/Image):	
8905i:	0.28 Wh/Image
8995i:	0.28 Wh/Image
8986i:	0.29 Wh/Image

British Thermal Units (BTU)

Maximum (BTU/Hr.):	6,934
Copying/Printing (BTU/Hr.):	5,231

Plug	NEMA 5-20P
-------------	------------

Dimensions (W x D x H)

Standard: 26-3/8" x 30-3/8" x 46-5/8"
(670 mm x 770 mm x 1,185 mm)

Installation Space (W x D)

Fully Configured: 199-1/2" x 55-1/2" (5,068 mm x 1,409 mm)
(POD Deck Lite-C1 + Document Insertion Unit-N1 + Multi Function Professional Puncher-B1 + Paper Folding Unit-J1 + Booklet Finisher-W1 Pro + Booklet Trimmer-F1)

Weight

Standard (with Flat Touch-Panel):	Approx. 487.2 lb. (221 kg)*
-----------------------------------	-----------------------------

Noise Levels (LwA,m [B])**

Standby:***	4.6 B
Copying/Printing:***	7.3 B

Recycled Content

Recycled Primary Package (%) [■]	Approx. 20%
Post-consumer Waste: [†]	0.1%
Secondary Waste Materials: ^{††}	0.0%
Recycled PETE Product: [◆]	0.0%

Recycled Paper Support

100% Post-consumer Content: Yes

Environmental Standards Compliance

ENERGY STAR® Certified

EPEAT® Gold

Environment-conscious Features

Two-sided, Copy Sample, Confirmation/Cancel, Image Combination, ID Card Copy, Secured Print, Job Forwarding, Department ID Management, Access Management System, Authentication (Universal Login Manager), Standard Duplex Driver, Auto/Weekly Sleep Timer, Auto/Weekly Shutdown Timer, Staple-Free Stapling

* Including consumables.

** 1[B] =10[dB].

*** Measured in accordance with ISO7796. Presented in accordance with ISO9296.

■ Percentage based on weight of recycled content.

† The percentage of plastics the device contains that's derived from recycled plastic materials (by weight).

†† The percentage of reused waste material.

◆ The percentage of recycled PETE material.

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has qualified these model as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. PostScript® 3™ is either a registered trademark or trademark of Adobe Systems Incorporated in the United States and/or other countries. PCL 6 is a trademark of Hewlett Packard Company. Canon, imageRUNNER, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2023 Canon U.S.A., Inc. All rights reserved.

05/23-0756-8312

Canon

usa.canon.com

