




varioPRINT 140 series QUARTZ

MONOCHROME
PRODUCTION
DIGITAL PRESSES



varioPRINT 140 QUARTZ shown with optional accessories.

varioPRINT 140 series QUARTZ MONOCHROME PRODUCTION DIGITAL PRESSES

Product Specifications

MAIN UNIT

Marking Engine

Technology:	DirectPress
Print Resolution	
Engine:	600 x 2400 dpi, 200 lpi
PCL:	600 x 600 dpi
Adobe® PostScript® 3:	1200 x 1200 dpi (Enhanced), 600 x 2400 dpi
Max. Print Speed (ipm):	140/130/115 (Letter), 73/68/60 (11" x 17")
First-Copy-Out Time:	3.9 Seconds (Letter)
Paper Size	
Maximum:	12.6" x 19.2" (320 mm x 488 mm)
Minimum:	5.5" x 7.2" (140 mm x 182 mm)
Standard Paper Capacity (iPIM):	4,000 Sheets (20 lb. Bond)
2 x Bulk Tray:	1,500 Sheets (Letter, Statement ¹)
2 x Multisize Tray:	500 Sheets
Tray 3:	5.5" x 7.2" to 12.6" x 17"
Tray 4:	5.5" x 7.2" to 12.6" x 19.2"
Feeding (iPIM):	Friction-fed
Paper Weight:	13 lb. Bond to 110 lb. Cover (50 gsm to 300 gsm) (All Trays)
Duplex:	Up to 300 gsm
Power Source:	208 V/20 A
Options:	Bulk Tray Small Format-A1

Duplex Color Image Reader-N1

Image Sensor:	CCD
Document Size:	Statement to 11" x 17"
Resolution:	Up to 600 x 600 dpi
Tray Capacity:	Up to 200 Sheets (20 lb. Bond)
Paper Weight:	10 lb. Bond to 80 lb. Cover (38 gsm to 220 gsm)
Scan Speed	
BW:	Up to 130 ipm (300 x 300 dpi/600 x 600 dpi)
Color:	Up to 135 ipm (300 x 300 dpi) Up to 37 ipm (600 x 600 dpi)

OPTIONAL INPUT ACCESSORIES

ePIM (External Paper Input Module-D1)

Feeding Technology:	Air Separation, Suction Feeding
Standard Paper Capacity:	4,600 Sheets (20 lb. Bond)
Tray 1 and 2:	600 Sheets
Tray 3 and 4:	1,700 Sheets
	3,400 Sheets (20 lb. Bond, Letter, with Duo Tray installed)
Maximum Capacity:	8,000 Sheets (20 lb. Bond) ²
Acceptable Size:	8" x 8" to 12.6" x 19.2" (All Trays)
Paper Weight:	13 lb. Bond to 110 lb. Cover (50 gsm to 300 gsm)
Power Source:	120 V/15 A
Options:	Duo Tray, Forms Assist Module II

varioPRINT 140 SERIES QUARTZ PRODUCT SPECIFICATIONS

Document Insertion Unit-R1

Tray Capacity

Upper Tray:	Up to 200 Sheets (20 lb. Bond)
Lower Tray:	Up to 200 Sheets (20 lb. Bond)

Paper Weight: 14 lb. Bond to 110 lb. Cover
(52 gsm to 300 gsm)

Paper Size:³ 11" x 17", 12" x 18", 13" x 19", Legal, Letter,
Letter-R, Executive, Custom Size
(7.2" x 7.2" to 13" x 19.2")

Power Source: 120 V/15A

OPTIONAL FINISHING ACCESSORIES

Staple Finisher-AG1/Booklet Finisher-AG1

Tray Capacity

Top Tray:	Up to 1,000 Sheets (20 lb. Bond)
Lower Tray:	Up to 4,000 Sheets (20 lb. Bond)
Booklet Tray:	Up to 30 Booklets or Limitless

Staple Positions: Corner Stapling, Double Stapling, Saddle³

Paper Weight: 14 lb. Cover to 110 lb. Cover
(52 gsm to 300 gsm)

Paper Size³

Stapling:	11" x 17", Legal, Letter-R, Executive, Letter, Custom Size (8.3" x 11" to 13" x 19.2")
Booklet Finisher:	11" x 17", Legal, Letter-R, 12" x 18" Custom Size (8.3" x 11" to 11.7" x 17")

Stapling Capacity: Up to 100 Sheets, Maximum (Letter,
20 lb. Bond)

Booklet Stapling Capacity

Uncoated:	Up to 25 Sheets (20 lb. Bond/80 gsm)
Coated:	Up to 10 Sheets (28 lb. Bond/106 gsm)
V-Folding:	Up to 5 Sheets without Stitch

Power Source: 120 V/15 A

Puncher Unit-BS1

(Option for Finisher-AG1/Booklet Finisher-AG1)

Paper Weight: 13 lb. Bond to 73 lb. Cover
(50 gsm to 200 gsm)

Paper Size

2-Hole:	Legal, Letter-R
3-Hole:	11" x 17", Letter, Executive

Punch Speed: Same as Speed of Marking Engine

Power Source: From Main Unit

High Capacity Stacker-J1

Offset Stack Capacity: Up to 6,000 Sheets (20 lb. Bond)

Top Tray Capacity: Up to 200 Sheets (20 lb. Bond)

Paper Size:³ 5.5" x 7.2" to 13" x 19.2"

Paper Weight: 13 lb. Bond to 110 lb. Cover
(50 gsm to 300 gsm)

Max. Connectivity: 2 Units

Power Source: 120 V/15 A

Multi Function Professional Puncher-C1

Paper Weight

Plain: 20 lb. Bond to 110 lb. Cover
(75 gsm to 300 gsm)

Coated: 32 lb. Bond to 110 lb. Cover
(118 gsm to 300 gsm)

Paper Size: 12" x 18", 11" x 17", 9" x 12", Letter, Legal,
Letter-R, Statement

Die Set Patterns: Loose Leaf 3-Hole/5-Hole, Velo Bind
11-Hole, Plastic Comb 19-Hole, Twin Loop
21-Hole/32-Hole, Color Coil 44-Hole/
e-Wire/Perforation

Power Supply: 120 V/15 A

GBC eWire Pro⁴

Bound Book Size: 15 to 100 Sheets (20 lb. Bond)

Paper Size: Letter, 5.5" x 8.5", Tab Stock

Paper Weight: 20 lb. Bond to 110 lb. Cover
(75 gsm to 300 gsm)

Wire Choices: 1/4", 5/16", 3/8", 7/16", 1/2", 9/16"

Stack Capacity: Up to 35 Books

Infeed: Multi Function Professional Puncher-B1

Power Supply: 115 V, 60 Hz, 2.8A

Weight: 500 lb.

Dimensions (W x D x H): 35.8" x 31.3" x 42.6"

Booklet Trimmer-G1⁵

Margin Trimming: Front-edge Trim

Trim Amount: 0.08" to 1.1"

Trim Thickness: 50 Sheets (25 Sheets, Folded; 20 lb. Bond)

Paper Weight: 14 lb. Bond to 110 lb. Cover
(52 gsm to 300 gsm)

Output Tray Capacity: 30 Booklets

Power Source: From Booklet Finisher-AG1

varioPRINT 140 SERIES QUARTZ PRODUCT SPECIFICATIONS (Continued)

Two-Knife Booklet Trimmer-B1 (Optional for Booklet Trimmer-G1)

Margin Trimming:	Top and Bottom
Trim Amount:	0.08" to 0.59"
Trim Thickness:	50 Sheets (25 Sheets, Folded; 20 lb. Bond)
Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
Power Supply:	120 V/15 A

Paper Folding Unit-K1⁶

Double Parallel Fold:	Legal, Letter-R
C/Accordion Fold:	Letter-R
Z-Fold:	11" x 17"
Half-fold:	Letter-R
Supported Media Weights:	13 lb. Bond to 28 lb. Bond (50 gsm to 105 gsm)
Power Source:	From Finisher-AG1/Booklet Finisher-AG1

Decurler Unit-D1

Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
Paper Size:	5.5" x 7.2" to 13" x 19.2"

DFD Adapter and Finisher Bridge-A2/B1

Paper Weight:	13 lb. Bond to 110 lb. Cover (50 gsm to 300 gsm)
Connectivity:	745 mm Paper Path Height (Input), 860 mm Paper Output Path, CAN Connection, Requires Upper Tray from Finisher-AG1 to be Removed and Replaced by the Finisher Bridge
Requirements:	Staple/Booklet Finisher-AG1
Power Supply:	From Finisher

Plockmatic BLM50/35 Professional Booklet Maker⁷

Booklet Size:	Up to 50 Sheets (20 lb. Bond)
Paper Size:	8.1" x 10.8" to 12.6" x 18"
Paper Weight	
Uncoated:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
Coated:	28 lb. Bond to 110 lb. Cover (105 gsm to 300 gsm)
Trim Amount	
Face:	0.04" to 1"
Top/Bottom:	0.196" to 1.18"
Paper Rotating:	SDD Rotator RTM3550 required
Weight:	1,235.7 lb.
Dimensions (W x D x H):⁸	86.2" x 28.8" x 41.4"

SDD Square Fold Booklet Maker⁹

Booklet Capacity:	Up to 25 Sheets (20 lb. Bond)
Booklet Input Size:	4.71" x 8.27" to 9.6" x 12.6"
Booklet Output Size:	4.71" x 7.87" to 9.6" x 12.6"
Paper Weight:	16 lb. Bond to 110 lb. Cover
Trim Amount:	0.08" to 1.38"
Power Supply:	120 V, 60 Hz, 15 A
Weight:	154 lb.
Dimensions (W x D x H):	44.9" x 23.6" x 44.9"

SDD Square Fold Booklet Maker with Two Knife Trim⁹

Booklet Capacity:	Up to 25 Sheets (20 lb. Bond)
Booklet Input Size:	4.88" x 5.51" to 9.6" x 12.6"
Booklet Output Size:	4.88" x 5.51" to 9.6" x 12.6"
Paper Weight:	16 lb. Bond to 110 lb. Cover
Trim Amount:	0.08" to 1.38"
Power Supply:	120 V, 60 Hz, 15 A
Weight:	573 lb.
Dimensions (W x D x H):	62.7" x 27.6" x 51.2"

varioPRINT 140 SERIES QUARTZ PRODUCT SPECIFICATIONS (Continued)

PRINT SERVER

Processor:	2.7 GHz
Memory:	4 GB
Hard Drive:	500 GB
OS:	Windows 10 LTSC
Supported PDLs:	APPE, PDF/PS, PCL, XPS ¹⁰ , PPML ¹⁰
Standard:	Scheduler, Remote Manager, PRISMAlytics Dashboard, Automated Workflows, Remote Control
Optional:	DocBox, Color Scanning, Multiple Queues, Streaming, Accounting, Integrity Checker, E-Shredding, DP Link, KDK Link

¹ Requires Bulk Tray Small Format-A1.

² With Duo Tray option installed in Tray 3 and 4 of ePIM. Letter only in trays with Duo Tray option installed.

³ Maximum supported size for varioPRINT 140 series QUARTZ engine is 12.6" x 19.2". Document Insertion Unit supports 13" x 19.2".

⁴ Requires Multi Function Professional Puncher-C1 and Decurler Unit-D1.

⁵ Requires Booklet Finisher-AG1.

⁶ Requires Staple Finisher-AG1 or Booklet Finisher-AG1.

⁷ High Capacity Stacker-J1, DFD Interface Kit, and DFD Paper Path, or DFD Adapter and Finisher Bridge-AZ/B1 required.

⁸ Dimensions include Plockmatic BLM 50/35 Booklet-maker, Booklet Fold Module, and Trimmer.

⁹ Booklet Finisher-AG1 and Booklet Trimmer-G1 required.

¹⁰ Optional.

Canon

usa.canon.com/productionprinting



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has qualified these models as meeting the ENERGY STAR® energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. varioPRINT, PRISMA and PRISMA product, logo, and service names are registered trademarks of Canon Production Printing Netherlands B.V. All other referenced product names and marks are trademarks of their respective owners. All output is simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2023 Canon U.S.A., Inc. All rights reserved.

09/23-1005-8431

